

AMERICAN INSTITUTE OF STEEL CONSTRUCTION
The Wrigley Building, 400 North Michigan Avenue
Chicago, IL 60611

A9.27-5

BULK RATE
U. S. POSTAGE
PAID
PERMIT NO. 15
KENT, OHIO

Address Correction Requested

MODERN STEEL CONSTRUCTION

NUMBER 5 • 1987



THIS ISSUE

Special Section:
1987 Architectural Awards of Excellence
United Complex—Framed-for-Tomorrow
Preliminary Design Studies:
AISC Marketing, Inc.
Innovations to Proven Deck Systems






UNITED STEEL DECK, INC.

Uni-lok

Standing Seam Roofing System

A quick erecting standing seam roofing system with superior weather-tightness features.

- Provides a fully floating roof to accommodate expansion and contraction.
- Easy to install:
No seaming tools, No battens,
Snaps into place.
- Solution for nationwide climactic conditions.
- Minimal exposed fasteners penetrate the building envelope.
- Excellent loading characteristics.
- Carries UL 90 classification.
- Available in long lengths (up to 60 ft.).
- Contains factory applied sealant.
- Suitable for new construction.
- Adds value to retrofit structures.
- Works at low slopes (min. 1/4 in 12).



NICHOLAS J. BOURAS INC.
P.O. BOX 662, 475 SPRINGFIELD AVE.,
SUMMIT, NEW JERSEY 07901 (201) 277-1617

UNITED STEEL DECK, INC.




ASSOCIATE MEMBER

**A GRAPHIC
EXAMPLE
OF WHAT
SEPARATES**

Scada

**FROM
PROGRAMS
COSTING
TEN TIMES
AS MUCH.**



If an \$1,800 base price seems too low for advanced finite element analysis and design software, you can always spend ten times more on a competitive program. But look what you'll be missing:

- ▲ The world's most powerful and versatile 2-D and 3-D desktop finite element analysis system.
- ▲ Graphics capabilities only available in far more expensive programs.
- ▲ SEDIT. A state-of-the-art, interactive and menu-driven preprocessor offered by SCADA at no extra charge, and unlike anything attempted by any other FEA developer.
- ▲ Plus the ability to add, for \$1,000 more, either concrete or steel design capabilities including AISC's latest Load Resistance Factor Design (LRFD) Code.



AMERICAN COMPUTERS & ENGINEERS

11726 San Vicente Blvd., Suite 212,
Los Angeles, CA 90049

Tel.: (213) 820-8998 Telex: 493-0363 ACE UI

Taken as a whole, SCADA represents the finest integrated design and analysis software available today. SCADA's integrated modular configuration makes it the only program that can grow without any change to its architecture. Add flat-slab or shear-wall design—even buckling and nonlinear capabilities. Whether you're a big organization designing some of today's largest structures, or a smaller firm with simpler requirements, you'll find SCADA adapts easily to the projects at hand.

SCADA is available exclusively through American Computers & Engineers. For a brochure detailing the full scope of its capabilities, simply contact us at the address below. And prove to yourself that a powerful engineering program needn't come with an overpowering price.

MODERN STEEL CONSTRUCTION

VOLUME XXVII • NUMBER 5
SEPTEMBER-OCTOBER 1987

American Institute of Steel Construction, Inc.

The Wrigley Building
400 North Michigan Avenue
Chicago, Illinois 60611-4185

OFFICERS

Werner H. Quasebarth
Chairman

Samuel Y. Golding
First Vice Chairman

Oscar W. Stewart, Jr.
Treasurer

Neil W. Zundel
President

William W. Lanigan
Secretary & General Counsel

Lewis Brunner
Vice President, Membership Services

Geerhard Haaijer
Vice President, Technology & Research

Morris Caminer
Vice President, Finance Administration

William Y. Epling
Vice President, Government Affairs

EDITORIAL STAFF

George E. Harper
Director of Publications

Brenda Follmer
Assistant Editor

Lona Babbington
Business

ADVERTISING REPRESENTATIVE

The PATTIS GROUP
Kirby Palait
4761 West Touhy Avenue
Lincolnwood, Ill.
312/679-1100

ON OUR COVER:


1987 AAE Award-winning Pier 17 Pavilion,
in the shadow of Manhattan

-
- 5 United Airlines-O'Hare
Framed for Tomorrow



-
- 14 Preliminary Design Studies
by AISC Marketing, Inc.

-
- 16 Steel-grid Bridge Flooring
Recent Innovations to Proven
Modular Decking Systems



-
- 35 Special Section:
1987 Architectural Awards of
Excellence Winners

-
- 46 Steel Notes



Innovative Engineering

UNITED AIRLINES— O'HARE

Framed for Tomorrow


by Charles H. Thornton, Udom Hungspruke, Robert P. DeScenza and Martin Wolf

O'Hare Airport in Chicago, already one of the world's busiest airports, is currently undergoing a \$1.5-billion redevelopment program scheduled for completion in the 1990s. The architectural centerpiece of this development is the \$450-million United Airlines "Terminal for Tomorrow." The two highlighting features of this extraordinary project are the exposed steel structural systems supporting the roof at the 1,730-ft long vaulted gate areas and the exposed steel folded plate roof trusses over the 120-ft x 810-ft column-free ticketing pavilion areas. Phase I construction was completed in July 1987, with Phase II scheduled for completion in mid-1988.


The Terminal I complex is split into two parallel sets of gates—Concourse B and C. The two are separated by 800 ft. Passengers enter the main ticketing pavilion, a column-free area 810 ft wide by 120 ft deep. After passing security, they proceed to their assigned concourse. Passengers for Concourse B, located next to the main access roadway, proceed directly to their gate. Passengers for Concourse C must go through the 800-ft long, 300,000-sq. ft underground passage and baggage handling area connecting the two concourses. The 350-ft x 800-ft roof over the passage and baggage area, of post-tensioned con-



Overall of mammoth United Airlines new Chicago terminal.



Spectacular use of steel in soaring complex in B Concourse



Plan of United Airlines Terminal I Complex



Unclad folded-plate trusses and struts

crete, supports loads from airplane traffic to the two concourses. Each concourse consists of long corridors with 40-ft high glass ceilings with gates and passenger hold rooms off to either side of the main corridor.

Folded Truss Ticketing Pavilion

The column-free ticketing pavilion area is one of the architectural highlights of the building. Located between Concourse B and the roadway, this area serves as the entrance to the building. Fifty-four exposed steel, folded-plate trusses span 120-ft from the roadway to the Concourse B main corridor. The steel used in the trusses conformed to the following ASTM specifications A500 Gr. C modified for 50-ksi yield strength, A618 Gr. 1a, A53 Gr. B, A252 and A333; in addition, API Gr. XL-52 with a minimum yield strength of 50 ksi was used. Each fold of the trusses is 14 ft-4 $\frac{1}{2}$ in. in depth (the maximum depth that can be shipped) and is set at an angle of 37° from horizontal. The trusses are shop-welded, with 8 $\frac{1}{2}$ -in. dia. pipe top and bottom chords and 6 $\frac{1}{2}$ -in. dia. pipe diagonals. At the ridges, the top chords of adjacent trusses are spaced 5 ft apart. At the valleys, the bottom chords of adjacent trusses are spaced 2 ft-6 in. apart.

A series of 8-in. wide-flange members spaced at 10-ft intervals undulate up and down directly over the folded trusses in a direction perpendicular to the span of the trusses. These W8 members make the individual planar trusses act as a folded plate system. This combination of the flexural W8 members and the planar trusses allowed for the components to easily be individually shipped to the site and erected as a unit. In addition, the W8 members simplified the connections of the architectural cladding by providing a planar surface. The connections of the W8 members to the pipe trusses are all bolted connections to allow for simplicity of erection. Two adjacent planar trusses and the W8 members were assembled in the shape of an inverted "V" at the opposite end of the site. After the assembly was completed, the 30-ft wide units were pulled on a wheeled vehicle by a tractor $\frac{1}{4}$ -mile and then lifted into place. Each truss took about four hours to move and install. After the trusses were lifted into place, the W8 members were connected to the adjacent inverted truss with simple bolted connections. Horizontal shear plates were field-bolted to insure that wind loads could be transferred to locations with X-bracing.

FIRST. LAST. ALWAYS.

We created the *first* name in computer aided steel detailing — SDS/2. The *last* system you will ever need to buy. Because we are *always* enhancing our software to achieve unsurpassed efficiencies. More structural steel is detailed by SDS/2 than with any other computer aided system.

First. Last. Always. SDS/2.


**DESIGN
DATA**

"Software For The Professional"
800-443-0782


It's Time...

Along the main elevated roadway, parts of the folded plate trusses and their supports are exposed to the cold weather of Chicago's winters. As a result, these elements require specific toughness to improve their low temperature resistance to brittle fracture. The project specifications required that steel used in these areas be silicon-killed and fully fine-grained. A Charpy V-notch impact value of 25 ft lbs. at +40° F. was required for base metals and a Charpy V-notch impact value of 25 ft lbs. at -20° F. was required for weld metals used in these areas. Special marking and identification procedures were developed to control the traceability of this non-typical steel at critical locations.

Special consideration and analysis was required at both ends of the folded plate structure and at all of the interior expansion joints. At these locations, under vertical loads, the outer bottom chords of the fold-




WB strut at connection at adjacent bottom chords of folded plate (top, r). Drawing (r) details *WB* strut and horizontal shear plate connections.



Folded-plate support detail at end fold (above). View of two-column cluster supporting folded-plate trusses at roadway side (r.)



Concourse C vaults



Metal Building Bolts

Serving the nation with the world's largest stock of A-325 Bolts under one roof.



Ask for a copy of our Price Catalog featuring A325

We carry a complete line of bolts and nuts for the building trade

METAL BUILDING BOLTS CORPORATION


10934 HAZELHURST, HOUSTON, TEXAS 77043
TELEPHONE (713) 461-0505



Vault to Vierendeel column connection Concourse B (3-column cluster)



Vault to Vierendeel column connection Concourse C (3-column cluster)



ed plate system tend to spread apart; hence, the effectiveness of the folded plate system will be impaired and the horizontal displacements too great. Tie rods connecting the bottom chords are typically used to stabilize the exterior flanks' folded plates. However, the tie rod solution at those isolated locations creates an architectural appearance which is aesthetically undesirable. The final stabilization scheme selected at the two ends of the folded plate area consisted of installing columns 20 ft o.c. along the edge and stiffening the W8 beams on the edge segment. At the two expansion joint locations the W8 member size was increased and a W6 tie was added two ft below the ridge.

Battened Columns

The columns supporting the folded plate area are 8⁵/₈-in. dia. pipes in clusters of from one to five. The pipes were clustered to simplify the support detail for the two

Vault to Vierendeel column connection at folded-plate intersection (4-column cluster)



STRUCTURAL DESIGN USING LOTUS 1-2-3® + ENERCALC™



Use LOTUS 1-2-3® as your personal structural designer. Your \$795, 26 program "library" supplies design & analysis in steel, timber, retaining walls, concrete, masonry and can perform structural analysis.

Forward thinking engineers will realize this software is REQUIRED MATERIAL in today's competitive design office, and our nationwide user's are available as impartial references. Receive our brochure or demonstration packages by contacting:

ENERCALC™

160 Newport Center Drive, Suite 125
Newport Beach, CA 92660 • (714) 720-1865

discrete bottom chords. The clustered pipe columns were connected together with 12-in. deep vertical batten plates. A 6-in. dia. hole, located at the center of each of the battens, links the ticketing area architecturally to the vaulted corridor areas. The battens connect the individual pipe columns together to create a single Vierendeel column.

Stability and lateral wind load resistance in the folded plate area is accomplished by using exposed solid rods 4 in. in diameter. These rods are connected to the columns with pins and clevises.

Concourse B and C Vaulted Corridors

The second major architectural feature is the welded steel vaulted arches that form the roofs of Concourses B and C. Since the structure is exposed—and *becomes* the architecture—strict attention to the connection details was required by the entire design team. The roof over both the corridor areas and the hold room areas are skylit. The skylight glass is a ceramic fritted panel with an opaque grid pattern to reduce glare.



Moving sidewalks transport passengers through underground corridor. Overhead kinetic lighting sculpture—744 ft long—is synchronized to background music.

**“You specify
DTIs.
American
Bridge
will use
them.”**

**—Brock Rowley
President and CEO
American Bridge Co.**

Direct Tension Indicators

Brock Rowley knows a wise investment when he sees it. That's why he bought American Bridge Co., the century old structural steel giant that built some of the world's tallest buildings and most impressive bridge structures.

And that's why Brock supports the use of Direct Tension Indicators on structural steel projects where high clamping forces are critical, such as: high rise buildings and bridges. Because DTIs assure proper bolt tension every time, there's no guesswork. Expensive, inaccurate and potentially hazardous torque wrench inspection is eliminated. DTIs are also a wise investment because they save on inspection costs.

Direct Tension Indicators from J&M Turner, Inc. An excellent investment in quality assurance.

Specify American-made Direct Tension Indicators on your next structural steel project, ASTM F959-85. For a side-by-side inspection cost comparison, or a copy of our free video, "The Dependable Connection," write to Jonathan Turner, J&M Turner, Inc., 200 Rittenhouse Circle, Bristol, PA 19007 or call 1-800-525-7193.



J & M Turner Inc.

The main support system for the corridor roof is a series of steel-vaulted arches spaced 30 ft o.c. The steel used for the vaulted girders conformed to ASTM A36. In Concourse B, the arches span 40 ft to form a 1,730-ft long corridor. In Concourse C, the arches span 50 ft to form a 1,610-ft long corridor. The vaulted arches are shop-fabricated in an I-shape cross section, with continuous welds between flanges and web. Because of the size of the vaults, two splices are required in each of the girders. These splices are fully welded and ground so as not to detract from the architectural appearance. The 24-in. deep vault girders are perforated with 12-in. holes 24 in. o.c.

To support the glass mullion system, purlins spaced 5 ft o.c. span between the vaulted girders. The purlins are built-up members of a 8 $\frac{1}{2}$ -in. dia. pipe and a WT4. The WT web is oriented perpendicular to the plane of the glass to improve the flexural strength of the purlins. Parallel to the segmental planes of the glass, a series of

1 $\frac{1}{2}$ -in. dia. sag struts stiffens the pipe purlins about their weak axis and transmits unsymmetrical loads through the structure. Cross-bracing members are placed intermittently within the planes of the sag struts to stabilize laterally the vaulted arches. Five expansion joints were required in each concourse to reduce thermal expansion movements. All of the pipe purlins were fitted with stainless steel pins and Lubrite sleeve-type bushings at these locations.

The vaulted arches are again supported on a series of clustered pipe columns similar to those at the folded-plate trusses. Each of the different support details was planned carefully both structurally and aesthetically. The cluster columns support the vault creating an impression that the vault is floating between columns. To make the wind frame an effective interface between the vault and Vierendeel batted column, the connection was detailed as a moment connection.

Both ends of each of the two cylindrical concourse roofs terminate with domes. The domes are created by gracefully extending and curving the pipe purlins around the dome to form horizontal rings. Sag struts located on vertical great circles emanating from a central hub at the high point of the dome transmit vertical loads to the steel grillage supporting the dome at the lower roof level.

Conclusion

Steel proved to be the material of choice for the United Airlines "Terminal for Tomorrow." The flexibility and aesthetic nature of steel combined to create an innovative and efficient structure that forms the architectural centerpiece for one of the nation's busiest airports. □

Architects

O'Hare Associates / Murphy/Jahn
Chicago, Illinois
and
A. Epstein and Sons, Inc.
Chicago, Illinois

Structural Engineer—Architecturally

exposed steel
Thornton-Tomasetti, P.C., The office of
Lev Zetlin Associates, Inc.,
New York, New York

Engineer-of-Record

A. Epstein and Sons, Inc.
Chicago, Illinois

General Contractor

Turner Construction Company
Chicago, Illinois

Steel Fabricator

Mosher Steel Company
Houston, Texas

Steel Erectors

Broad, Vogt and Conant, Inc.
Cleveland, Ohio
and
Hi-Gate Erectors
Addison, Illinois

Owner

City of Chicago

Charles Thornton, Ph.D., P.E., is president; Udom Hungspruke is vice president, Robert DeScenza, P.E. is project engineer in the firm of Thornton-Tomasetti, P.C., New York, New York.

Martin Wolf, AIA, is vice president of Murphy/Jahn, Chicago, Illinois.

FREE GRATING INSTALLATIONS?



Almost. The Struct-Fast System can secure grating of all standard types and sizes to customary support steelwork with minimum installation labor. The process eliminates the traditional fastening methods of welding, drilling and tapping, or a labor intensive improvisation on the job site.

Also available for fastening beam to beam and attaching checkered plate flooring. For more information and technical data write or phone...

STRUCT-FAST INC.

20 WALNUT ST., SUITE 101 • WELLESLEY HILLS, MA 02181
TEL (617) 235-6734

Tel _____

Struct-Fast Inc. 20 Walnut Street Suite 101 Wellesley Hills MA 02181

Address _____

Company _____

Position _____

Name _____

Please send me details

New for 1988

PERSONAL COMPUTER DETAILING SYSTEM


High Speed, Low Price

COMPUDRON KEEPS PACE WITH THE FUTURE.

**Our new system
gives maximum
performance
at a fraction
of the cost.**

Compudron is the only computerized structural detailing and information system offering both graphic and batch input to produce:

- Beams
- Columns
- Vertical Bracing
- Stair Stringers



- Erection Plans
- Advance Bills of Material
- Fitting Gather Sheets
- Full Size Templates
- N. C. Equipment Data
- AISC Connection Design
- Cost Coding
- Erection Sequencing

**Call today for a
demonstration.**

THE STEEL INFORMATION SYSTEM

P. O. BOX 767596 • ROSWELL, GA 30076 • (404) 992-0062
TOLL FREE 1-800-438-8587 (TONE) 303

compudron
INCORPORATED

A CIVES COMPANY

Preliminary Design Studies for Structural Steel Bridge and Building Frames

AISC Marketing, Inc. is a new company which has as its objective increasing fabricated structural steel's share of the building and bridge market. The sponsors of AISC Marketing, Inc., are The American Institute of Steel Construction, Bethlehem Steel Corporation and United States Steel Division of USX Corporation.

AISC Marketing maintains a national network of Regional Engineers—ten for buildings, four for bridges—located strategically around the country to assist the influences that design and specify structural products for buildings and bridges. Each of these Regional Engineers is uniquely qualified to assist engineers, contractors, construction managers, architects and anyone else who may be in the decision-making path for the choice of structural material on his project.

While each Regional Engineer has his own capability to assist the decision-maker, there is often the need for a design proposal which can be studied and priced to assist in the determination of the best structural arrangement for a steel solution to the structural problem. The headquarters staff of AISC Marketing, located in Pittsburgh, Pa., is equipped to prepare these design proposals, called Preliminary Design Studies. These studies are prepared under the supervision of experienced, recognized expert engineers who are fully familiar with the codes and standards which govern the design of buildings and bridges. Through their own knowledge and the input of the Regional Engineers, they are also familiar with the local conditions and practices which affect the use of fire protection, forming and other systems used with steel frames.

Studies can be prepared offering a single design which represents a best or optimal design, given the parameters that limit the number of alternates possible; or parametric studies can be prepared which show a range of values allowing the engineer to design his project with an optimization of structure and other functional requirements of the project. In each case, a fully documented presentation, with expla-

nation of the thinking which went into the preparation of the Preliminary Design Study, is presented.

Preliminary Design Studies are done at the request of consulting engineers, contractors, state DOTs and others who make decisions regarding the choice of structural materials. Of particular interest to AISC Marketing, Inc., are projects where structural steel is not being considered, its potential is not understood, or where there is confusion about which structural steel system would be the most economical. In these cases, AISC Marketing, Inc., believes a specific example tailored to the project in question would be helpful and increase the chances for a structural steel frame to be specified.

A word about budget estimates. Budget estimates are not included in the study presentation. The studies are prepared with an understanding of the relative costs of different systems in different parts of the country. This information comes from the Regional Engineers or the person who requests the study. This allows the Preliminary Design Study to be prepared in such a way as to reflect the best and most economical choices of floor systems, fire protection, etc. for a given geographical area. Budget estimates can then be developed in a variety of ways. Local AISC member fabricators can quickly prepare estimates for the structural steel requirements. The Regional Engineers, who have contacts with contractors and suppliers of formwork or precast deck, will develop budget estimates for these materials using these sources. Similarly, fire protection and drywall costs, when needed, can be developed by the Regional Engineers. But very often it turns out that the contractor, construction manager or state DOT already involved in the project has the knowledge and capability or a preferred system to develop a realistic budget for comparison with other structural systems being evaluated.

Timing. From the time a Regional Engineer is asked to help by having AISC Marketing, Inc., prepare a Preliminary Design

REGIONAL ENGINEERS—BRIDGES

Pittsburgh, Pa.

(FHWA Regions 1 & 3)
Carl Angeloff
119 Jenny Lynn Drive
Aliquippa, Pa. 15001-1407
412/774-1155

Atlanta, Ga.

(FHWA Regions 4 & 6)
Dwight Williams
1057 Manning Farms Ct.
P.O. Box 467039
Atlanta, Ga. 30346-7039
404/395-1746

Chicago, Ill.

(FHWA Regions 5 & 7)
Robert S. Crooks
400 N. Michigan Ave.
Chicago, Ill. 60611-4185
312/670-5407

Denver, Colo.

(FHWA Regions 8, 9 & 10)
Lewis MacDonald
666 Sherman Street
Denver, Colo. 80203-4401
303/831-4622

REGIONAL ENGINEERS—BUILDINGS

Atlanta, Ga.

David A. Magee
1976 River Forest Dr., NE
Marietta, Ga. 30068-1170
404/642-9707

Boston, Mass.

78 Airport Road
Warwick, R.I. 02889-1037
401/738-5338

Study, until the study is in the hands of the person requesting the study can be as short as one week. But the complexity of the study requested and the number of other studies being prepared at the same time can stretch this delivery time out two or three weeks. If the requester will indicate the priority of the project, the schedule can usually be accommodated.

If you think that a Preliminary Design Study would help you in the decision-making stage of your project when the choice of structural framing materials is being made, call your local AISC Marketing, Inc., Regional Engineer, or at the Pittsburgh headquarters call Heinz Pak at 412/394-3704 for a building study; or Roy Mion at 412/394-3706 for a bridge study.

Chicago, Ill.

James M. Beamer
400 N. Michigan Ave.
Chicago, Ill. 60611-4185
312/670-5430

Columbus, O.

William D. Liddy
1241 McKinley Ave.
Columbus, O. 43222-1198
614/274-3151
or: 312/670-5423

Houston, Tex.

James L. Fulton
5925 Sovereign Drive #101
Houston, Tex. 77036-2309
713/270-6363

Los Angeles, Cal.

James W. Marsh
9420 Telstar Ave. #207
El Monte, Cal. 91731-2906
818/444-4519

New York City, N.Y.

Frank A. Petrigliano
1605 John Street #206
Fort Lee, N.J. 07024-2581
201/585-2837

St. Louis, Mo.

Douglas A. Fisher
15943 Chamfers Farm Road
P.O. Box 4187
Chesterfield, Mo. 63006-4187
314/532-9008

San Francisco, Cal.

Rudolph Hofer
1250 Pine Street #301
Walnut Creek, Cal. 94596-3633
415/932-0909

Washington, D.C.

Herbert W. Mills
505 Kings Highway
Fredericksburg, Va. 22405-2627
703/371-2766

You
can't
get
heat
treated
plate
any
longer.

STEEL-GRID BRIDGE FLOORING

Recent Innovations to Proven Modular Decking System


by Gene R. Gilmore

In the 1920s, engineers looking for a lightweight but high strength deck alternative butted flanges of tees together and filled the structure with concrete. These early grid reinforced concrete bridge decks spawned many variations in the years ahead, and were the birth of the most time-tested and most durable of all bridge decks.

Today, four types of steel grid flooring are in everyday use (Fig. 1). They are: (1) Full-depth grid reinforced concrete decks (using 3-in. tees or 4 $\frac{1}{4}$ -in. I-sections as main reinforcement), (2) Half-depth grid reinforced concrete decks (using 5- $\frac{7}{16}$ -in. I-sections as main reinforcement), (3) Exodermic bridge grid decking (variable depth unfilled grid with a composite slab on top of the grid network) and (4) open steel grid bridge flooring (either welded or riveted construction).

The grid reinforced concrete decks have, and are, playing an ever increasing role in bridge rehabilitation. Product design advantages such as reduced dead load, durability (many bridges have grid reinforced concrete decks with more than 50 years of service), composite action with supporting steel, coupled with construction advantages such as speed of deck replacement and ease of precasting have brought grid flooring to the forefront as the premier deck replacement material. All these advantages blend with attractive in-place costs of \$20 to \$25 psf, including a wearing course and corrosion protection. This paper examines the products' history, the design differences among the various types, the latest precasting and connection

Figure 1



01164
details, case histories of recent projects, corrosion protection and finally, recent and future testing and the "lost report" on composite action with supporting steel.

Product History

As indicated, the first grid reinforced concrete decks were made from structural tees. Figure 2 shows the 10th Street Bridge in Pittsburgh, which opened to traffic in 1932. This photo was taken prior to its 1981 rehabilitation. At that time, the deck was still in excellent condition. Now in service for 55 years, it has endured heavy truck traffic and de-icing chemicals for most of its life.

Figure 3 is certainly the mainstay of grid reinforced concrete bridge decks. The I-beam Interlock floors were introduced in the 1930s. At one time, there was a family of the I-beam sections; 2½ in., 3 in., 3½ in., 4¼ in. and 5 in. Only the 4¼-in. I-beam section has survived the lean years of bridge rehabilitation and the mill closings of the 1970s and 1980s. However, as demand continues to rise, this family will make a comeback.

Figure 4 shows the Half-depth grid reinforced concrete deck developed in the 1950s. To decrease weight even further, an intermediate flange was added to the I-section to allow placement of a form pan halfway down in the grid network. Including a 2-in. cover, the bridge industry now had a deck that weighed less than 70 lbs. psf and with span capabilities up to 13 ft.

(continued on p. 22)



Fig. 2. 10th Street Bridge, Pittsburgh, Pa. Deck type, 3-in. tee, installed 55 yrs. At major rehab in 1981, deck was in excellent structural condition, overlaid with rubberized asphalt.





Fig. 3. 4-¼ in. I-beam interlock. Many bridges built in the 30s and 40s with this design are still in use. Most popular of full-depth-filled grids, and most economical.

Or heavier.

Only Lukens offers heat treated plate that's as long as 890"—or that weighs 50 tons. We can also supply widths to 195". So the easiest way to fill your tall orders is to contact the Plate Products Division, Lukens Steel, Coatesville, PA 19320. (215) 383-2452

Lukens Steel
The specialist in plate steels.

Now you *can* put all of your eggs in one basket.




STAAD-III based ISDS

The first structural analysis/design software with built-in drafting
(all for only \$3,400*)

The Integrated Structural Design System: classic STAAD-III analysis and design, STAADPL graphics, *plus* STAAD-DRAFT—the brand new drafting facility designed especially for structural engineers. One complete package. \$3,400.

This unprecedented level of integration is a much needed breakthrough for structural engineers. Previously, to generate drawings from design data, some sort of interface package was necessary to link the two programs. This cumbersome process involved purchasing, maintaining, and learning two (or more) programs from different vendors.

ISDS solves this problem with its unique capability



to create engineering drawings directly from the same input used for analysis, design, and graphics.

Furthermore, this information is held in a central database maintained by ISDS. User interaction is minimized, improving both efficiency and data integrity.

It makes sense.

At the heart of ISDS, STAAD-III performs static and dynamic analyses on two- and three-dimensional structures and designs

members in steel or concrete based on user-selected standard codes. Available codes include AISC working strength and the new LRFD specifications involving member deflection considerations, as well as ACI and AASHTO codes. STAAD-III handles a wide variety of loading conditions, including internally generated moving loads.


For more details on STAAD-III based ISDS or a demonstration version, please call or write: Research Engineers, 303 Pavilions at Greentree, Marlton, NJ 08053. Phone: (609) 983-5050. TLX: 4994385.

In Europe, Research Engineers, 17 Lansdowne Rd., Croydon CR9 3UN, U.K. Phone: 01 6867672 TLX: 929181.

*Licensing fee on MS-DOS based PCs

Research Engineers, Inc.
A REPUTATION YOU CAN BUILD ON.

Hambro®...the most cost efficient floor system you can use.



Bostonian Hotel, Arch: Mintz Assoc./Eng: David M Berg, Inc./Cont: Perini Corp.

“The Hambro composite floor system saved us over 33 tons of steel and one month’s erection time.”

Peter Rizzuto, Project Manager, Perini Corp.,
contractor for Bostonian Hotel

Perini Corporation estimates that the Hambro system for the Bostonian cost 20% less than ordinary joist construction. Savings were in labor as well as material. Erection was faster because they could “cast today and strip tomorrow.” Entire bays were gang formed in the atrium and flown into place.

Hambro’s UL fire ratings are achieved without applying the 22/30 factor for reduction of capacity required for conventional “H” series joists. This, together with Hambro’s superior sound rating of STC 57, make it the ideal floor construction system for high or low rise commercial and residential buildings. Call or write for brochure.



P.O. Box 223, Needham Heights, MA 02194 (617) 444-5504

Regional Offices and Distributors throughout the U.S.

In NYC, NJ, Eastern PA, MD, VA and DE: Mid-Atlantic Hambro, Inc.
114 East 25th St., Baltimore, MD 21218 (301) 338-1122 Telex: 87938

A subsidiary of  canam manac

L.R.F.D. OR A.S.D.???

IT'S YOUR CHOICE WITH THE ECOM STRUCTURAL ENGINEERING SERIES

Confused about which design method is best for your project? ECOM can end the confusion as both methods are built-into our Steel Design "C" Package. With just a few key strokes YOU CAN DESIGN a series of beams or columns BOTH WAYS. SAVE TIME ELIMINATE ERRORS.

ECOM STRUCTURAL ENGINEERING SERIES IS:

- *COMPREHENSIVE*
- *INTEGRATED STEEL DESIGN*
- *EFFICIENT*
- *STATE-OF-THE-ART*
- *LINKED TO AISC'S NEW SECTION DATA BASE*
- *INTEGRATED TO AUTOCAD™*
- *ALLOWS LRFD OR ASD DESIGN*
- *EASY TO USE*
- *QUICK RERUNS*

Push your productivity to new heights. Join over 1,500 firms who for over 14 years have looked to ECOM for excellent engineering software backed by a staff of professional engineers ready to assist you.



8634 W. Brown Deer Rd., Milwaukee, WI 53224
(414) 354-0243

**CALL TODAY
FOR A FREE BROCHURE
AND SPECIAL OFFER ON THE
ECOM S.E. SERIES
CALL 800-558-5137
TOLL FREE**

ADVANCING THE STATE OF STRUCTURAL SOFTWARE . . . AGAIN

ECOM is an authorized dealer of IBM and COMPAQ. AUTOCAD is a registered trademark of Autodesk, Inc.



INRYCO N·R·G FLOR[®]

It's Entered A New Dimension.

Inryco NRG Flor[®] for steel frame construction provides a cost-efficient distribution system for your building's wiring management. And now it's better than ever, supported by the largest family of PLEC (power, lighting, electronics and communications) distribution systems in the industry.

Nationwide distribution. Inryco NRG Flor is now available all over the country through the Walker agent network. Your local Walker agent is an experienced PLEC systems professional, ready to work with you in designing an NRG Flor system to meet the specific needs of your building. And he'll be there to provide whatever service you need in the future.

Backed by the top name in PLEC distribution. All of the Inryco organization's structural expertise and experience—over 30 years of it—is still built into NRG Flor. But now it's also available through Walker, the

leader in design and development of PLEC distribution systems for over 60 years. So the combined experience of Inryco and Walker ensures that the PLEC distribution system designed for your building will meet the needs of its occupants for the life of the building.

Find out more about what Inryco NRG Flor—backed by Inryco and Walker—has to offer. Call 1-800-222-PLEC (In Ohio 614-373-4441). Or write NRG Flor, P.O. Box 1828, Parkersburg, WV 26102.

INRYCO
N·R·G FLOR[®]
AVAILABLE THROUGH
Walker[®]
P.O. Box 1828, Parkersburg, WV 26102 (304) 485-1811

A DIVISION OF BUTLER MANUFACTURING COMPANY




Figure 4




Fig. 5. Exodermic deck system

Note that the 3-in. and 4¼-in. grids also require a wearing course on top of the steel grid network. Riding on the armored surface will eventually cup the concrete and expose the grid bars. This can result in a bumpy ride and it could be slippery. For these reasons, a wearing course is always recommended for Full-depth of Half-depth grid reinforced concrete decks.

However, the exodermic deck in Fig. 5 does not require a wearing course. Its 3-in. or 4-in. composite concrete overlay is a wearing course in itself. As a result, this design yields the lightest concrete deck alternative. This innovation, developed in the 1980s, was tested extensively by the Fritz Laboratories. Its unique structure is a miniature T-beam composite cross section. The neutral axis of this variation is near the top of the steel grid. In positive moment, the concrete is in compression while the steel grid is in tension. Also, welds on the steel grid are near the low stress area of the neutral axis. The slab is connected to the grid by shear studs and an elevated grid bar that penetrates about 1 in. into the slab. Because of all these positive design features, the Lehigh University study stated, "... that an infinite in-service fatigue life can be expected . . .".** While Full-depth and Half-depth grids can be either precast or poured-in-place, the exodermic grid type is supplied only as a precast deck slab.

Figure 6 depicts the two types of open grids, welded and riveted construction. Riveted design evolved first in the 1920s. However, because of the riveted floor's greater weight, welded floors eventually dominated this market. Recent testing, however, indicates the riveted floor should not have been shelved so quickly.

Based on recent bids and discussions with the bridge community, Fig. 7 was developed to present reasonable expected in-place costs, including a protective wearing course for the various alternatives.

Design and Performance

To assist in the reader's understanding the design and performance characteristics of these products, Fig. 8 was prepared. Based on design and performance criteria presented, the exodermic grid offers the best performance, although some of its comparison factors are based on laboratory results. The precast grid follows closely, but its performance factors have been field verified. For the best blend of performance and value, the cast-in-place grid fulfills this

*Daniels, J.H. and R.G. Slutter Behavior of Modular Unfilled Composite Steel Grid Bridge Deck Panels Lehigh University, January 1985 (p. 21).



JEFF DAVIES says:

TRUSS ME!!

Don't waste your time on complicated steel truss analysis and design problems. Call or write for a **FREE** copy of our famous steel truss analysis and design program, TRUSS:



Features:

- Analyzes any statically determinant, pin-jointed 2-d truss
- designs structural tees or double angles
- 100 joints, 200 members (more if necessary)
- horizontal and vertical loads on any/all joints
- follows AISC 8th edition
- user-friendly
- runs on IBM-PC/XT/AT and most compatibles.

Your order includes all required instructions for operation, disks and documentation, PLUS a copy of our latest brochure describing our 60+ programs for concrete, steel, timber, and post-tensioned concrete design. This offer is valid only until September 30, 1987, so CALL ME NOW, toll free: 1-800-635-6366 (814).

Ⓢ \$15 charge for materials and handling. (Foreign orders add \$15 for air mail.) Offer expires September 30, 1987. Florida residents add sales tax. VISA, Mastercard welcome.

The Most Productive Structural Design Software Since 1966



STRUCTURAL ANALYSIS, INC.

30 S.E. Seventh St., Suite D2, Dept. T1 • Boca Raton, FL 33432
1-800-635-6366 (dial tone 814) or 1-305-392-6597

objective. With in-place costs of \$20 psf average, it is the prime candidate for value.

Open decks must be considered separately since they are not considered acceptable, and are rarely used, on primary highway structures. The riveted floor has the best performance characteristics, but is also generally heavier and more costly to manufacture and erect. However, it may be money well spent when the superior fatigue life it offers over its welded counterpart is considered.

Connection Methods and Precasting

The method of connection is obviously an important detail to be considered when using any form of grid deck. Furthermore, precasting the grid prior to placement requires additional considerations over and above the traditional cast-in-place connection details. Let us examine these important and various installation details.


Figure 9 displays the traditional method of deck connection: welding the grid to supporting steel. This method, although still used on many projects, is rapidly being replaced by the use of shear studs. Precasting grids that are either welded or studded to supporting members require pockets in the precast grid reinforced concrete panels. The connection pockets, which permit field welding of the main grid elements to the stringers, were grouted after all the deck panels had been placed. An asphalt overlay was then placed over the armored surface. All deck work was done at night and the bridge was opened fully to traffic during the day. The 133,000 sq. ft of deck was replaced in eight months. The more current and preferred method of deck connection is to use shear studs. Using studs eliminates many of the question marks associated with welding. Figure 10 shows various details of deck connection using studs. When the deck units are precast, a leveling bolt can be used similar to attachment method No. 5. After proper elevation is achieved, the joint is grouted and the leveling bolt removed. Since shear studs are used, the deck develops full composite action with the support system. The isometric drawing in Fig. 11 depicts the exodermic deck attached by shear studs to the structural beams. The concrete overlay is composite with the grid, which in turn is composite with the structural steel. This results in a very efficient combination of lightweight decking and composite design.

Threaded shear connectors were chosen for the replacement decks on the Queensboro Bridge ramps in New York City. As Fig. 12 shows, the threaded studs permitted raising or lowering deck panels

(continued on p. 27)



Figure 6



Riveted open grid

5-in., 4-way open grid

**WE
PUT
100
YEARS
OF
EXPERIENCE
IN
EVERY
BOLT WE MAKE**

We operate the largest facility in the country for making big and special bolts. Just as important, we're big on dependable service and reliable delivery.

We're St. Louis Screw & Bolt and we make a full range of heavy structural bolts. Our entire manufactured product line, including Types I and III, is made from domestic materials and tested in our St. Louis plant. We're big on quality, too.

After 100 years, we know big bolts in a big way.


ST. LOUIS SCREW & BOLT COMPANY
6901 N. Broadway/St. Louis, MO 63147/(314) 389-7500

SINCE 1887

MEMBER
INDUSTRIAL
FASTENERS
INSTITUTE


ASSOCIATE MEMBER

VULCRAFT SUPER LONG



185' 4" and 166' 8" super long span joists, both 120" deep, reach across the Lund Center sports complex.

SPANS GO THE DISTANCE.



The Lund Center of Gustavus Adolphus College



To build a sports complex as large and expansive as the Lund Center at Gustavus Adolphus College in St. Peter, Minnesota required a structural system that could go the distance. Vulcraft super long span joists were clearly the front runner.

As a result of careful analysis, Vulcraft super long span joists were selected over the other two alternatives: conventional trusses and rigid frame construction. The open configuration of Vulcraft super long spans provided a number of advantages. While long enough to span a basketball court, indoor tennis courts, and a running track as well as spectator seating, Vulcraft super long spans provided a strong, lightweight, and easy to install system. The open configuration of the Vulcraft joists also permitted the heating and ventilation ducts and electrical systems to be run through the spans. This created an *uninterrupted ceiling line for the automated divider screens* which separated the different sections of this vast sports complex.

Since the college is dependent on private funding, the savings afforded by using Vulcraft joists helped make it possible for the college to initiate the project. Also, by using Vulcraft's economical 3" N 20 gage deck, joists could be spaced farther apart. So, fewer joists were needed and construction costs were further reduced.

When your job has to go the distance, let Vulcraft put you out front. For more information concerning Vulcraft steel joists, joist girders and steel deck; or, for copies of our joist and steel deck catalogs, contact the nearest Vulcraft plant listed below. Or, see Sweet's 5.2/Vu and 5.5/Vu.

P.O. Box 637, Brigham City, UT 84302 801/734-9433
P.O. Box F-2, Florence, SC 29502 803/662-0381
P.O. Box 169, Fort Payne, AL 35967 205/845-2460
P.O. Box 186, Grapeland, TX 75844 409/687-4665
P.O. Box 59, Norfolk, NE 68701 402/644-8900
P.O. Box 1000, St. Joe, IN 46785 219/337-5411

VULCRAFT

A Division of Nucor Corporation

Architects/Structural Engineers: Toltz, King, Duvall, Anderson & Associates. Steel Fabricator: Ted Mannstedt and Son, Inc. General Contractor: Kraus-Anderson Construction Company, Minneapolis Division. Steel Erector: Vickerman Construction Company.

Soda... designs your least-weight steel structure fast... and automatically

Finally, a practical structural engineering software package that not only analyses but automatically designs a least-weight (optimal) steel structure.

SODA represents the perfect blending of state of the art structural engineering and modern optimization research. SODA is a truly practical steel design optimization package that permits the designer to concentrate on engineering instead of routine calculations, thereby reducing design time and costs.




SODA automatically and completely designs a least-weight planar steel frame or truss from section databases in complete conformance with design code requirements. The design by SODA is complete, constructable and ready to implement. There is no need to re-analyse and re-size as is the case with other steel design programs. The software designs not only member by member, but by considering

the entire structure as a system. The design satisfies both strength and deflection requirements.


- Design codes supported:
 - AISC WSD 1978 Specification
 - AISC LRFD
 - Canadian CAN3 - S16.1 - M84 Limit States Design
- Microsoft® Windows environment
- Mouse or keyboard interaction

- Members selected from AISC or CISC database or from user's custom data base
- Comprehensive yet concise user's manual
- 30 day evaluation period, refund if not satisfied
- Runs on IBM PC XT/AT or compatible
- Minimum 512 KB and hard disk required


* - Microsoft is a registered trademark of Microsoft Corporation.




Input and editing is quick and easy.



User interface is accomplished with mouse and drop down menus.



Graphics displays are accessible at any time.



The optimal design is presented in a logical and concise manner.

To get more information on SODA and to receive your free demonstration diskette:

CALL TOLL FREE (in continental U.S.)
1-800-265-2766
or COLLECT (519) 885-2450

or WRITE
WATERLOO ENGINEERING SOFTWARE
A Member of the NEXA Group

Park Avenue Atrium
237 Park Ave., Suite 2143
New York, NY 10017

180 Columbia Street West
Waterloo, Ontario
Canada N2L 3L3

soda

**STRUCTURAL
OPTIMIZATION
DESIGN AND ANALYSIS**

	Type of Deck						
	Precast decks		Cast-in-place decks			Open decks	
	Exodermic grid	Precast grid	Precast concrete	Cast-in-place grid	Cast-in-place concrete	Riveted	Welded
Manufacturing Cost	\$14	\$9		\$9		\$14	\$12
Concreting Cost	6	4		2		-	-
Erection Cost	6	6		6		12	6
Corrosion Protection* (or) Protective** overlay	2	2		2		2	2
	(Not Req'd)	4		4		-	-
Totals	\$28	\$21 (or) \$23	\$20	\$19 (or) \$21	\$15	\$28	\$20

*Assumed to be galvanizing
 **Assumed to be latex-modified concrete

Fig. 7. In-place deck costs in psf

Comparison factor	Type of Deck						
	Precast decks			Cast-in-place decks		Open decks	
	Exodermic grid	Precast grid	Precast concrete	Cast-in-place grid	Poured-in-place concrete	Riveted	Welded
Cost of deck installed	2	3	4	4	5	2	4
Cost of traffic maintenance	5	5	4	4	1	4	4
Weight	4	3	1	3	1	5	5
Future replacement	5	4	4	3	1	4	4
Ease of installation	5	4	4	3	1	4	5
Quality control	5	4	5	3	2	4	3
AASHTO standards	5	5	5	5	5	5	1*
Remaining useful life-rehabilitation project	5	4	1	4	1	5	5
Deck service life	5**	5	2	5	2	4	2
Totals	41	37	30	34	19	37	33

Key: 1 = Poor (or lowest)
 2 = Below average
 3 = Average
 4 = Above average
 5 = Best (or highest)


*Meets AASHTO standards, but there is an inadequacy in method of wheel distribution
 **According to lab tests

Fig. 8. Relative value comparison of bridge decks

T.S. Bolts & Tools

I.C.B.O. Listed

Full range of certified A325 and A490 bolts and complete complement of tools for installation, including "Tone" tools and the new TSW 60LC high speed, swivel head tool.



FULL 360 ROTATION

NEWEST OF FULL LINE OF LIGHT WEIGHT TOOLS

BRISTOL MACHINE COMPANY
cfs Construction Fastener Systems Division

630 E. Lambert Road, Brea, CA 92621 • 714-990-6555
 WATS 1-800-872-6587





Figure 9


into desired position. They also served as temporary support for the unfilled deck, which was haunched at varying depths. The ramps had horizontal and vertical curves in combination with super elevations and varying roadway widths. The haunches were field-formed and continuously poured with the grid and a 2-in. concrete wearing surface. Finally, the double-duty threaded shear studs provide a

positive connection for composite action with supporting steel after the cure. Note that welding of grid reinforced concrete decks to supports provides composite action also.


The use of shear studs with grout on top of the structural steel flange is also worthy of note. Figure 13 shows the final form of this attachment method. As an added benefit, the concrete cover provides pro-




ATTACHMENT METHOD #2



ATTACHMENT METHOD #3



ATTACHMENT METHOD #5



ATTACHMENT METHOD #6

Figure 10

MODERN STEEL CONSTRUCTION

METAL DECKS STEEL JOISTS TRUSS GIRDERS

- Fast Estimates: Send Us Your Plans
- Quick In-House Detailing
- Delivery When You Want It

For over 32 years, Riopelle has been providing customers with high quality, S.J.I. Specification steel bar joists, S.D.I. metal decks.

We serve all fabricators and structural engineers. Our large volume assures both fast delivery and highly-competitive quotes. No job is too big or too small.

For unbeatable prices and favorable credit terms, give us a call today.



8817 West Lynx Avenue
Milwaukee, Wisconsin
53225-1833
(414) 353-8080 CALL COLLECT
Jim VanDien • Dan Zane
FAX: 414-353-8093




Figure 11



Figure 13

tection for the beam flanges, sometimes an objection when an open grid deck is proposed. Again, any questions involved with field welding are minimized.

Recent Case Histories and In-place Costs

Thousand Islands Bridge Over St. Lawrence Seaway, Upstate New York

Probably no other recent project expresses so completely the positive benefits of grid reinforced concrete decks as does the Thousand Islands Bridge. Built in the 1930s, this bridge (the American crossing) and its twin (the Canadian crossing), span the St. Lawrence Seaway in the picturesque area known as the Thousand Islands. Its long approach ramps were reinforced concrete decks. These had deteriorated badly due to the action of de-icing compounds and extreme freeze/thaw cycles over the years. However, the main span of the structure was a 4 1/4-in. grid filled flush with concrete and never overlaid. It had performed admirably in this severe environment and required no repairs, although the roadway was widened during rehabilitation.

Construction was limited to night work only, but one lane had to be maintained during the night. And the entire bridge had to be open to traffic during the day. The contractor would precast the grids at the




Figure 12

BEAM AND COLUMN DESIGN USING YOUR PC!!!

- Any Beam or Column Design
- Solution in Under 28 Seconds
- Automatic Retrieval of . . .
Moment, Section Modulus
Area, Radius of Gyration
- AISC, LRFD or ASD Specs
- Complete System Only - \$495

QuickBEAM

- Indeterminate Cases
- Varying Cross Section
- Stress & Deflections
- Reactions

QuickCOLUMN

- Biaxial Design
- Any Shape
- AISC Specs

QuickSHAPE

- Retrieves 1,102 Shapes
- Selects Lightest Weight
- Over 20,000 Properties
- Integrates with Beam and Column Design

- Any Load or Support
- Shear Moment Diagram

DEMONSTRATION AVAILABLE

ENGINEERING SOFTWARE COMPANY
Search Plaza, Suite 780
 10670 North Central Expressway
 Dallas, Texas 75231
 (914) 361-8431

Number 5 / 1987

29



Thousand Islands Bridge

jobsite during the daytime hours. His pre-casting hut was under the bridge approaches. The panels, one half the roadway in width (13½ ft) and up to 39 ft long, were delivered to the bridge. Since the deck was precast, form pans in the grid were not required.

The decks were then brought into the precast hut and filled with concrete, including a 2-in. overfill for a wearing course. The finished precast decks were placed in the storage area for nighttime installation. Holes were drilled in the precast decks to permit field attachment. The eroded concrete slab was then removed at night and replaced with the precast grid system. The grid, precasting and installation was bid in 1985 at \$22 psf, according to the contractor. This project displays all the grid deck advantages: ease of precasting and traffic maintenance, durability in severe environments and cost-competitive replacement with a lighter weight, superior product.

*Allegheny River Bridge,
Pennsylvania Turnpike Commission*

This ongoing replacement, again, shows the many advantages of grid reinforced concrete decks. This four-lane bridge was


4-¼ in. Grid installed	\$13.45 psf
4-¼ in. Concrete	2.50 psf
1-½ in. Latex overlay	3.50 psf
Total in-place cost	\$19.45 psf

Fig. 14. Allegheny River bridge bid prices

widened by 12 ft under traffic conditions, with no summer deck work permitted. Also, two and three lanes of traffic had to be maintained during the deck replacement and all four lanes made available in summer and winter. The grid was delivered to the jobsite and placed on the bridge stringers. Another benefit of using grids is evident here. The grid, which serves as a working platform during reconstruction, greatly improves installation time and permits increased traffic flow.

Figure 14 is a summary of the bid prices for the replacement deck. The complete 4¼-in. grid system was bid in the Fall of 1985 at less than \$20 psf, including a 1½-in. latex modified concrete overlay. It should be noted that all expansion and relief joints, and all scuppers, were factory-installed, once again highlighting the product's flexibility and factory-controlled, quality benefits.

Spanning the gap in bridge construction



A single Mi-Jack TRAVELIFT crane replaced two hydraulic boom cranes and numerous hydraulic jacks on the Ben Franklin Bridge renovation project, reducing equipment and maintenance costs, personnel requirements and extending the hours worked per day.

Installation of new orthotropic bridge panels took just half the time required previously. Traffic flow on the bridge was maintained in both directions for the duration of the construction project.

A spokesman for the construction firm said, "The TRAVELIFT crane has met all our needs." And no wonder! Backed by 30 years of experience and over \$7,000,000 in spare parts inventories nationwide, Mi-Jack's Service and Parts departments specialize in keeping machine downtime to a minimum.

Let a Mi-Jack representative show you how a TRAVELIFT crane can span the gap in your next bridge construction project.

Mi-Jack TRAVELIFT, 3111 West 167th Street, Hazel Crest, IL 60429. (312) 596-5200.

Missouri DOT Five-year Average Prices

The Missouri DOT, over the past dozen years, has an aggressive bridge rehabilitation program underway. They have used extensively the Half-depth Grid Reinforced Concrete Deck system and kept very detailed deck reconstruction costs. The Half-depth grid reinforced concrete deck met their needs because it reduced dead load by 30 to 50 lb. psf and served as a working platform for the contractor. The working platform facilitates assembly-line deck replacement and makes more deck area available for traffic maintenance. Naturally, the reduced dead load, as is the case for most grids, decreases the need for extensive structure repair and reinforcing or increases live-load capacity. Half-depth grids, in their unfilled state, can usually carry HIS loading without overstress.

Figure 15 shows the most recent (1982-1987) five-year average costs for the in-place grid decks, including waterproofing and wearing course. Once again, the total system cost is less than \$20 psf. Recently, where dead load was not critical, Missouri has gone to the 4¼-in. Full-depth grid in anticipation of even lower in-place costs.


5-¾ in. Half-depth grid, installed with concrete \$15.48 psf
Waterproof membrane & 2-in. asphalt wearing course	... 4.17
Total in-place cost \$19.65 psf

Fig. 15. Missouri DOT 5-yr. average pricing

Corrosion Protection

Corrosion protection of steel grids, specifically concrete-filled grids, has been a matter for much debate. Many theories, both positive and negative, have come out of this subject. It is difficult to draw conclusions on this matter, but examine the evidence. Figure 16 summarizes a study in 1976 on various western Pennsylvania bridges, some with grid decks and others with reinforced concrete slabs.* The comparison is dramatic. Chloride ion contents in the grids are high, but their average age is considerably greater than the reinforced slabs, yet their surface condition is far better. These decks had no corrosion protection, neither protective overlay or coated steel. Certainly this is a positive statement for deck performance without corrosion protection. This study brought to light that steel grids are grounded systems which limit stray corrosive currents present in reinforced concrete slabs. Copies of this study are available direct from Greulich.

Also, many grid floors are 50 years and



Allegheny River Bridge, Pennsylvania Turnpike

WHO KNOWS MORE ABOUT IMPROVING THE EFFICIENCY OF DRAFTSMEN THAN DRAFTSMEN?



Ex-draftsmen,
Robert Pettitt and
Lawrence Shinkaruk,
creators of the
STEELCAD II
Software Program
for structural
steel detailing.

ALL THE STEEL FABRICATORS WHO'VE TESTED STEELCAD II HAVE ONE THING IN COMMON

THEY BOUGHT IT.

PETTITT LAWRENCE LTD.
STEELCAD II
550 Alden Road, Suite 201
Markham, Ontario L3R 6A8
TELEPHONE (416) 479-0399



	Date built:	Salt content/ cu. yd. concrete:	Deck area:	Deck area damaged:
Concrete-filled steel grid	1934	10.490 lbs.	468 sq. ft	0.0%
	1940	4.412 lbs.	4,669 sq. ft	0.0%
	1958	0.246 lbs.	2,596 sq. ft	0.0% (asphalt)
	1932	2.902 lbs.	50,000 sq. ft	0.0%
	1932	1.070 lbs.	13,770 sq. ft	0.0%
	1937	1.900 lbs.	31,000 sq. ft	0.0% (asphalt)
	1931	6.575 lbs.	35,430 sq. ft	0.0% (asphalt)
	1940	3.496 lbs.	96,240 sq. ft	0.0% (asphalt)
Reinforced concrete	1958	3.572 lbs.	49,704 sq. ft	0.0% (asphalt)
	1956	5.016 lbs.	1,332 sq. ft	50.0%
	1952	5.510 lbs.	7,327 sq. ft	32.0%
	1950	5.130 lbs.	11,616 sq. ft	18.0%
	1962	2.710 lbs.	17,200 sq. ft	7.0%
	1962	0.207 lbs.	11,000 sq. ft	3.0%
	1965	1.290 lbs.	44,145 sq. ft	0.5%
	1973	0.796 lbs.	8,325 sq. ft	0.0%

Note: "0.0% (asphalt)" in damage column denotes normal wear of wearing surface. Reinforced concrete chart is composed of every fifth bridge listed in original study.*

Fig. 16. General damage comparison: concrete-filled steel grid decks vs. reinforced concrete slab decks

older and have performed admirably under de-icing chemicals and severe environments, such as the existing Thousand Islands grid deck. This combination of a grounded deck system and superior performance life indicates corrosion is not a significant problem.

Those are the positives, but what about the negatives? What about the deck growth phenomena? Figure 17 outlines this negative factor. At the bottom of Fig. 17 are the positives for deck performance in corrosive environments. Ultimately, the owner must decide whether corrosive protection is desirable, and at what cost. Waterproofing overlays can cost (in 1987) anywhere from \$2 psf up to \$10 psf for thin, exotic wearing surfaces. Galvanizing the grid after fabrication adds about \$2 psf to the cost of the system and is a relatively low-cost, but proven method. Coatings such as zinc paints and epoxy coatings have also been used. These add \$2 to \$6 psf to the price of the entire deck system. Therefore, a value judgment must be made concerning the need, and the extent of corrosion protection. The use of a lower cost method for corrosion protection might be the best decision.

It is important to point out another feature of the exodermic grid decking. It cannot exhibit the deck growth phenomena, since the grid cells are not filled with concrete as are conventional grid floors.

Testing

The "Lost" Study on Composite Action

A report by USS in 1960 indicates positively that full, composite action between concrete-filled grid decks and supporting steel is realized via full scale testing outlined in this report. Many times the question of composite action has arisen, and many times composite action has been assumed. That question can now be laid to rest since the "discovery" of this report which had been "lost" in the archives of USS for over 25 years. The report shows conclusively no slip between the deck and supporting system. Furthermore, a summary analysis done recently by the University of Pittsburgh supports the composite action conclusion of this study. Copies of the Test Report and Summary are available from the Bridge Grid Flooring Manufacturers Association.

Present Testing—West Virginia University—Open Grids

Dr. Hota Ganga Rao of West Virginia University completed in May 1987 a two-year, in-depth study of the performance characteristics of various open welded grids and riveted bridge decks.

DECK GROWTH PHENOMENA

Theory	After 40 yrs. ± of service, steel in grids expands due to "expansion" in highly compressed concrete cubes.
Limitations	95% of cases wherein very old decks finished flush with concrete and no overlay, not even asphalt
Other Theories	Concrete used; poor quality steel; insufficient expansion allowance
Possible Actions	Prime steel inside and out Water proof systems Concrete additives Always use overlay, at least asphalt—from riding quality standpoint also!
Effects of Salt	Superior performance (Angleoff report) Grounding aspects of grids Lack of stray corrosive currents Grid bridges in study, C1—content/cu. yd. and age of deck

10th Street	2.9 lbs.	54 yrs.
Highland Park	3.5 lbs.	47 yrs.
Boston Bridge	6.6 lbs.	49 yrs.

Figure 17

*Angeloff, Carl An Evaluation of the Comparative Effect of Chlorides on the Deterioration of Reinforced Concrete Slab and Concrete-filled Grid Bridge Decks presented at Transportation Research Board 56th Annual Meeting, Jan. 26, 1977, Washington, D.C.

FILLED GRIDS

- 1. History**
 - First use in 1920s—tee type
 - I-beam type 1930s
 - Half-filled type 1950s
 - Exodermic type 1980s
- 2. Design**
 - Similar to rebar slab-composite
 - Transformed area method for section properties
 - Distribution of load by AASHTO 3.24.3.1 & 3.24.3.2
- 3. Construction Flexibility**
 - Precast option
 - Shop attachment of structural steel
 - Acts as working platform during construction
- 4. Product Advantages**
 - Dead-load reduction
 - Speed of deck replacement
 - Simplifies maintenance of traffic
 - Durability
 - Factory controlled quality
 - Price—yes, price



Figure 18

Early fatigue studies reveal that riveted decks have a significantly longer fatigue life than welded floors. This is because they are generally heavier and their riveted connection provides a method for the riveted design to relieve stresses under live loads. Conversely, welded open grids rely on stiffness. And if transverse stiffness is not adequate, welds will break and fatigue cracks develop. Dr. Rao found high residual stresses in the welded panels. To lower these stresses, he recommends heat treating or galvanizing. Galvanizing, he believes, will perform the same function as heat treating at lower cost and will also provide corrosion protection. He likely will recommend a stiffer transverse bar also. Due to his study, we are likely to see a resurgence of the riveted design along with heavier open decks in general.

Future Testing

The Bridge Grid Flooring Manufacturers Association is considering tests on filled grids using shear-stud connections to supporting steel to verify composite action. Along with this study, wheel distribution will be examined to see if the AASHTO distribution formula for reinforced concrete decks is too conservative when applied to a filled grid. The grid network should provide superior distribution.

Summary

Figure 18 highlights the advantages and features of grid-reinforced concrete decks. These benefits, combined with new connection techniques and design features, make these products the leading candidates for bridge deck construction. □

Gene R. Gilmore is manager of sales and marketing, IKG Industries, Pittsburgh, Pennsylvania.

Queensboro Bridge

Construction Services:

- Geotechnical Engineering • Preliminary Soils Investigations
- Geology • Fault Hazard Studies
- Concrete Mix Design • Curtain and Window Wall Services
- Construction Inspection and Materials Testing
We have provided this service continuously since the 1906 San Francisco Earthquake.
- Hazardous Waste
Asbestos • Petrochemical • Underground Tank Monitoring



SMITH-EMERY COMPANY

The Full Service Independent Testing Laboratory, Established 1904

Los Angeles	Anaheim	San Francisco
213/749-3411	714/630-4910	415/822-8880

Computer Data Base



FOR STRUCTURAL SHAPES

In a continuing effort to provide steel design aids to structural engineers, the American Institute of Steel Construction has **improved** and **expanded** its Computer Data Base for properties and dimensions of structural steel shapes, corresponding to data published in Part 1 of the 1st Edition, *AISC LRFD Manual of Steel Construction*, as well as properties needed for Allowable Stress Design according to the 8th Edition, *AISC Manual of Steel Construction*.

PROGRAM PACKAGE

1. Computer Data Base in binary format for the properties and dimensions of the following structural shapes:
 - a. W Shapes (**many new sections**)
 - b. S Shapes
 - c. M Shapes
 - d. HP Shapes
 - e. American Standard Channels (C)
 - f. Miscellaneous Channels (MC)
 - g. Structural Tees cut from W, M and S shapes (WT, MT, ST)
 - h. **Single & Double Angles**
 - i. **Structural Tubing**
2. Explanation of the variables specified in each of the data fields.
3. Listing of a BASIC read/write program and **sample search routine**.
4. **Utility program to convert** data file to ASCII format for FORTRAN applications.

ORDER FORM

I enclose payment of \$_____ for qty. of _____
NEW LRFD/ASD COMPUTER DATA BASE-DIMENSIONS AND
PROPERTIES OF STRUCTURAL SHAPES AT \$60 each.
(Member price: \$45. Members & non-members with trade-in*: \$35.)

PERSONAL COMPUTER DISKETTE FOR:

- IBM-PC (& Compatibles) DEC Rainbow PC
 HP-150 Wang PC

*For discounted "trade-in" price, the original copy of the previous AISC shape data base must be returned with your remittance. Offer good on diskettes only.

Visa & MasterCard accepted

Card No. _____

Name _____ Title _____

Company _____

Address _____

City _____

State _____ Zip _____

Please enclose remittance. No C.O.D. orders. In New York, California and Illinois, add sales tax. Shipping charges prepaid in the U.S. On shipments outside the U.S., add 10% of total purchase for postage and handling. Visa and MasterCard accepted.

Signature _____

Exp. Date _____

MAIL TO: NEW LRFD/ASD COMPUTER DATA BASE
AMERICAN INSTITUTE OF STEEL CONSTRUCTION, INC.
P.O. Box 4588, Chicago, IL 60680-4588

1987 Architectural Awards of Excellence



Special Section



1987 Architectural Awards of Excellence

This Special Section of *Modern Steel Construction* is a salute to the winners of the 1987 Architectural Awards of Excellence competition. This biennial event, sponsored by the American Institute of Steel Construction, recognizes and honors outstanding architectural achievement in building design.

All registered architects practicing professionally in the United States are eligible for the competition. They are invited to enter buildings of their design constructed anywhere in the United States or its territories. For the 1987 competition, each project must have been designed, fabricated and erected in the U.S. during the calendar years 1985 or 1986.

Buildings of all classifications are eligible, with equal emphasis given to all sizes and types in the judging. The structural frame must be steel, although it is not a requirement that the steel be exposed and a part of the architectural expression. Older structures which have undergone major reconstruction/rehabilitation may also be entered. There is no limitation on the number of entries by any individual or firm.



On Our Cover . . .

A Joe Kinkel sculpture on permanent display at AISC headquarters, "The Long Reach," is the motif for AAE and Prize Bridge Awards presented by AISC. Award winners receive bas relief plaques adapted from the sculpture.

THE AWARDS JURY



(left to right)

DONALD J. HACKL
President
Lobel Schlossman Hackl
Chicago, Illinois
(and 1987 President,
American Institute of Architects)

TED A. NIEDERMAN
Principal
RTKL Associates, Inc.
Baltimore, Maryland

HAL IYENGAR
Partner
Skidmore, Owings & Merrill
Chicago, Illinois

PROFESSOR WILLIAM McGUIRE
School of Civil & Environmental Engineering
Cornell University
Ithaca, New York

BRUNO D'AGOSTINO
Senior Vice President
Benjamin Thompson and Associates, Inc.
Cambridge, Massachusetts



CLARKE COLLEGE

Dubuque, Iowa

Replacing key buildings lost in a fire, designers created a new "hub" for this 57-acre campus, echoing the character of the original group of closely linked buildings through a single large structure. It accommodates administrative offices, central library, chapel, recital hall, art gallery, post office and bookstore. The roof line has three individual peaks, one of which—the glazed atrium—reinforces the hub concept. Exposed bundled steel tube columns and vaulting are utilized to dramatically shape the space in forms reminiscent of a Gothic cathedral. Similar exposed bundled steel tube columns and vaulting are expressed in the two-story reading room of the library and chapel. The design integrates adjacent campus architecture and the masonry tradition of Dubuque architecture, consisting primarily of brick and limestone resting on the structural steel frame.

Architect

VOA Associates Incorporated
Chicago, Illinois

Structural Engineer

Shive-Hattery Engineers, Inc.
Moline, Illinois

Construction Manager

Conlon C.M.
Dubuque, Iowa

Steel Fabricators

Bradley Iron Works, Inc.
Dubuque, Iowa
and
Venetian Iron Works, Inc.
Des Moines, Iowa

Steel Erector

Northwest Erection Services, Inc.
Des Moines, Iowa

Owner

Clarke College
Dubuque, Iowa

Juror comments: "Historically, spirituality has often been expressed in structural terms. Clarke College's design and use of materials epitomizes that mode of expression."





345 CALIFORNIA CENTER

San Francisco, California

An elegant and unique form on the cityscape, this is one of the first major projects using a multiple tube and eccentric brace concept: a welded ductile, moment-resisting space framed tube at the exterior of the building, two transverse interior frames with an eccentrically braced core. Both frame and concept were selected because of ductility considerations and the fact that steel, light and flexible, reduced the inertia forces due to earthquake load. Steel framing also provided flexibility for inter-floor stairs for two-floor tenants; and erection of the tower's concrete-backed granite wall system. Rising 47 stories above grade, the project includes several parts: at the top, in two separate towers emerging from the office building and linked together with glazed skybridges, are 11 floors of hotel rooms; at the base is a full floor of mechanical equipment; then 31 floors of office space, two large podium office floors and—at street level and one above—two floors of office building and hotel lobbies, retail and restaurant space.

Jury comments: "A very aggressive, robust and powerful building statement."



Architect/Structural Engineer

Skidmore, Owings & Merrill
San Francisco, California

General Contractor


Dinwiddie Construction Company
San Francisco, California

Steel Fabricator/Erector


The Herrick Corporation
Hayward, California

Owner


California Center Partners,
Norland Properties
San Francisco, California



ELEVATION-
DUCTILE MOMENT FRAME



TYPICAL HOTEL FLOOR
FRAMING PLAN



TYPICAL OFFICE FLOOR
FRAMING PLAN

TRW WORLD HEADQUARTERS

Lyndhurst, Ohio

Expressive use of steel and aluminum emphasizes the technological sophistication of this company headquarters. Steel columns and beams are clad in bronze anodized aluminum with window frames and other components set in from the steel building frame. The 450,000-sq. ft building steps down in terraces; four narrow, pavilion-like office wings with full-height glass walls radiate from the central atrium.

Jury comments: *"An almost timeless piece of corporate architecture, as fresh and wonderful 20 years from now as it is today."*



Architect

Lohan Associates
Chicago, Illinois

Structural Engineer

KKBNA Unlimited, Inc.
Chicago, Illinois

General Contractor

Gilbane Building Company
Cleveland, Ohio

Steel Fabricator/Erector

Kilroy Structural Steel Company
Cleveland, Ohio

Owner

TRW, Inc.
Lyndhurst, Ohio



Jury comments: "This type of building brings life into the city, captivates and holds shoppers in a pleasant, stimulating environment."

PIER 17 PAVILION

New York, New York

This final element of the South Street Seaport in lower Manhattan is a three-story steel frame structure with painted metal siding and a standing-seam metal roof. Interior circulation is oriented around two three-story atria, one running north/south parallel to the shoreline, the other running east/west to the river. Retail stores and specialty shops focus inward; restaurants, cafes and public spaces focus outward, overlooking the waterfront.

Architect

Benjamin Thompson & Associates, Inc.
Cambridge, Massachusetts

Structural Engineer

Severud-Szegezdy Consulting Engineers P.C.
New York, New York

General Contractor

Tishman Construction Corp. of New York
New York, New York

Steel Fabricator

Mosher Steel Company
Birmingham, Alabama

Steel Erector

American Steel Erectors
South Plainfield, New Jersey

Owner

Seaport Marketplace Limited Partnership,
Affiliate of The Rouse Company
Columbia, Maryland

VACATION HOUSE

New England Coast

This family complex of autonomous units includes parents', children's and guest houses, and studio, with the parents' dwelling composed of two pavilions under a glass "tent," master bedroom and living-dining-kitchen, each defined by piers at the corners supporting tubular steel space trusses spanning the entire space to carry the roof deck.

Architect

Peter Forbes and Associates, Inc.
Boston, Massachusetts

Structural Engineer

Zaldastani Associates, Inc.
Boston, Massachusetts

General Contractor

Prin A. Allen & Sons
Brooklin, Maine

Steel Fabricator

Maine-Cascade Iron Works
Clinton, Maine

Steel Erector

Nancy's Welding
Freedom, Maine



Jury comments: "A modern house that fits beautifully into the rugged landscape."

VIRGINIA POWER'S INNSBROOK TECHNICAL CENTER

Glen Allen, Virginia

The open structural steel frame used throughout this utility's new center achieves the visual impact needed for the building's central architectural element, a 189-ft microwave tower. And it enabled the erector to lift pre-assembled platforms like building blocks. Building modules of open office are organized along an open 3-story circulation spine. The frame and exterior envelope were being constructed while the design team completed the interior package. Steel framing also permitted minor adjustments on the interior without major cost.

Architect/Structural Engineer/General Contractor

Virginia Power, E & C Division
Glen Allen, Virginia

Steel Fabricator

Owen Steel Company, N.C., Inc.
Gastonia, North Carolina

Steel Erector


W. O. Grub Steel Erection, Inc.
Richmond, Virginia

Owner

Virginia Power
Glen Allen, Virginia



Jury comments: "Integration of a new technology with forms that go back historically."



MORROW HYDROELECTRIC DAM

Kalamazoo County, Michigan

Generating facility is crisp and prismatic. Primary triangular bents of built-up architecturally exposed structural steel elements form the design icon, linked by tubular steel sections. Secondary and tertiary structural steel elements frame the entire exterior glass wall system, and form graceful catwalks, stair and craneway elements.

Architect/Structural Engineer

Skidmore, Owings & Merrill
Chicago, Illinois

General Contractor

Erhardt Construction Company
Ada, Michigan

Steel Fabricator

Grand Rapids Steel & Supply
Grand Rapids, Michigan

Steel Erector

Steelcon
Kalamazoo, Michigan

Owner

STS Consultants, Ltd.
Northbrook, Illinois



Jury comments: "This simple, elegant enclosure becomes architecture. It's direct, powerful and has a real poetry."



LLOYD CENTER CINEMAS

Portland, Oregon

The design for this multi-screen cinema complex is intended to "rekindle the spirit and excitement of the 20s, when a night out at the movies was a grand event." Red-painted exposed structural steel lends a lightness throughout, starting with an entrance gallery, moving through a transitional rotunda and ending in the "street of theatres." Each movie house has its own identity and sparkling neon. All detailing is exposed where appropriate; fasteners and cable structures are used to suspend light fixtures and neon artwork.

Jury comments: *"Totally unique . . . they put some real show business into this."*

Architect

Broome, Oringdolph, O'Toole, Rudolf, Boles & Associates, PC
Portland, Oregon

Structural Engineer

KPFF Consulting Engineers
Portland, Oregon

Steel Fabricator

Fought & Company, Inc.
Portland, Oregon

General Contractor

Hoffman Construction Co.
Portland, Oregon

Steel Erector

REFA Erection, Inc.
Tigard, Oregon

Owner

Tom Moyer Theaters
Portland, Oregon

RADIO STATION K92FM/WDBO

Orlando, Florida

Two major components of this broadcast facility and corporate office have been integrated into the overall design: the 200-ft tower and the satellite dish. A 10-ft x 150-ft skylight-covered corridor permits viewing of both elements from within the building. Because the building is severed literally into two pieces by the barrel arch skylight, an exceptionally strong column system was required to resist hurricane force winds. Steel truss columns resist wind shear by triangulation in a manner similar to the 200-ft broadcast tower.

Architect

Helman Hurley Charvat Peacock/Architects,
Maitland, Florida

Structural Engineer

Allan and Conrad, Inc.
Winter Park, Florida

General Contractor

R.C. Stevens Construction Co.
Orlando, Florida

Steel Fabricator/Erector

Southern Central Steel
Sanford, Florida

Owner

NewCity Communications, Inc.
Orlando, Florida



Jury comments: *"Refreshing and very laid back; a building that says the public is welcome."*

INDUSTRIAL TECHNOLOGY INSTITUTE

Ann Arbor, Michigan

A steel frame provides the "high-tech" image for this project, and curved stainless steel panels for the facade enforce the dynamic projection of a progressive corporation whose work is in "factories of the future." The interior integrates three functions: corporate headquarters, industrial research laboratories and training facilities. The corporate offices, a series of pods which include the training center, are sheathed in stainless steel and two shades of gray spandrel glass. The two-story industrial-bay laboratories are identified with black masonic tile.

Jury comments: "A high-tech solution, using both symmetry and materials very nicely."

Architect

William Kessler and Associates, Inc.
Detroit, Michigan

Steel Fabricator

Service Iron Works, Inc.
Livonia, Michigan

Structural Engineer

Robert Darvas Associates, P.C.
Ann Arbor, Michigan

Steel Erector


McGuire Steel Erection, Inc.
Northville, Michigan

General Contractor

O'Neal Construction
Ann Arbor, Michigan

Owner

Industrial Technology Institute
Ann Arbor, Michigan



GEORGIA STATE BOTANICAL GARDEN CONSERVATORY VISITOR'S CENTER

Athens, Georgia

The steel frame, painted white, ensures lightness and elegance for this great glass box. The aluminum skylight and curtain wall system is broken thermally and glazed with insulating glass. The main purpose of this teaching/visitor complex was the development of a tropical rain forest as part of the University's research efforts in biotechnology. However, it is also the setting for many special events, including lectures, parties and weddings. For general use, large exhaust fans in connection with motorized greenhouse window sash allow air circulation; for special events, the conservatory is air-conditioned.

Architect

Hall, Norris & Marsh, Inc.
Atlanta, Georgia

Structural Engineer

Sedki & Russ Engineers
Atlanta, Georgia

General Contractor/Steel Erector

Terry Development Corporation
Athens, Georgia

Steel Fabricator

Thackston Steel Co., Inc.
Statesboro, Georgia

Owner

University of Georgia
Athens, Georgia



Jury comments: "A very simple, natural expression of exposed structural steel . . . clarity and order are apparent."



McCORMICK PLACE EXPANSION FACILITY

Chicago, Illinois

A steel-framed low-rise building utilizing a cable-suspended structural steel roof system, the McCormick Expansion resolves site constraints, yet remains harmonious with adjacent lakefront environs. It augments the existing McCormick Place Exhibit Hall to form the world's largest contiguous exhibition facility, and has a 480 ft x 780 ft long-span roof, suspended from cables supported by 12 concrete pylons projecting 60 ft above roof level. The 3-3/4 in. diameter galvanized steel cables, six at each pylon, are jacketed by an extruded white PVC protective sheath with polished stainless steel anchorage fittings.

Jury comments: "*An extremely delicate way of handling a gigantic structure.*"

Architect/Structural Engineer

Skidmore, Owings & Merrill
Chicago, Illinois

Steel Fabricator/Erector

Bristol Steel Corporation
Bristol, Virginia

Construction Manager

Schal/McHugh
Chicago, Illinois

Owner

Metropolitan Fair & Exposition Authority
Chicago, Illinois

OWINGS MILLS TOWN CENTER

Owings Mills, Maryland

Structural steel creates a light, airy, upscale and sophisticated statement within a low-maintenance, highly durable framework. The food court's conservatory appearance was achieved using bent structural steel T-sections to support curved glass skylights. Exposed Vierendeel steel roof trusses serve both as stabilizers and decorative elements throughout the mall, forming the feature design element. Exposed steel columns are built up from one WF-shape and two T's welded together to make cruciform columns.

Jury comments: "*A very sophisticated, state-of-the-art type structure.*"

Architect/Structural Engineer

RTKL Associates, Inc.
Baltimore, Maryland

General Contractor

HCB Contractors
Baltimore, Maryland

Steel Fabricator

Strait Manufacturing
Greencastle, Pennsylvania

Steel Erector

L. R. Willson & Sons, Inc.
Gambrills, Maryland

Owner

The Rouse Company
Columbia, Maryland



THE HARTFORD LIFE INSURANCE HEADQUARTERS

Simsbury, Connecticut

Stub girders proved cost-effective while minimizing floor-to-floor height in this 4-story building. Ducts serving three separate wings run parallel to the beams, through the girders. The composite steel beams afforded great design flexibility, allowing openings to be cut in the field. The exterior is clad in 2-in. pink Connecticut granite. The 650,000 sq. ft campus-style building includes a computer center, corporate office space for 2,000 employees, cafeteria, private dining rooms and conference center, and a 100-seat multi-purpose auditorium.

Architect

Thompson, Ventulett, Stainback & Associates, Inc.
Atlanta, Georgia

Structural Engineer

Ross Bryan Associates, Inc.
Nashville, Tennessee

General Contractor

Bartlett, Brainard, Eacott/Dugan & Meyers, a Joint Venture
Bloomfield, Connecticut

Steel Fabricator/Erector

The Berlin Steel Construction Co.
Berlin, Connecticut

Owner

The Hartford Insurance Group
Hartford, Connecticut



Jury comments: *"Traditional mainstream architecture, eminently well-executed."*



Steel Notes

LRFD TEACHING GUIDE OFFERED

A new publication, *Elements of Teaching LRFD* (S332), is now available in manuscript form from AISC for educators who plan to incorporate Load and Resistance Factor Design (LRFD) in their structural curriculum. The new teaching tool is based on a syllabus prepared by Prof. Joseph A. Yura, Dept. of Civil Engineering, University of Texas at Austin. Yura is a contributor to the 1st Edition of AISC's *Load and Resistance Factor Design Manual of Steel Construction*, and has been teaching LRFD as a part of the university's structural design program.

LRFD is a design procedure based on the actual strength of a member or component, rather than on an arbitrary calculated stress. It is an ultimate strength concept wherein both working loads and resistance are multiplied by factors, and the design performed by assuming that the strength exceeds the load.

Teachers of structural design may obtain one complimentary copy of the new *Elements of Teaching LRFD* by requesting it in writing. Send requests to Robert F. Lorenz, director of education and training, AISC, 400 N. Michigan Ave., Chicago, Ill. 60611-4185. For further information, call him at 312/670-5406.

BOOKLET SHOWS STUDENTS' BEST

Winners of the 1986 AISC/American Institute of Architecture Students (AIAS) student design competition are featured in a 30-pg. booklet available from AISC.

The competition, titled "Bridges of Steel," involved the hypothetical reconstruction of the historic Smithfield Street Bridge in Pittsburgh. The student was asked to design a new bridge using the latest advances in theory and technology. But the student also had to preserve the memory of the original bridge within the urban fabric of Pittsburgh. Emphasis was

placed on aesthetic design with steel and the relationship between the new bridge and the urban context of renaissance Pittsburgh.

The booklet includes an explanation of the competition, profiles on the jurors, jurors' comments, photos of the winning entries and the students' design statements. For a free copy of the booklet (quantities are also available), contact William Noble, AISC headquarters, 312/670-5422.

COMBINED CONFERENCE FOR THE COMING YEAR

For the second consecutive year, the Conference of Operating Personnel and the National Engineering Conference (COP/NEC) will be combined. The conference will be held at the Hilton Fontainebleau Hotel, Miami Beach, Fla., June 8-11, 1988. A call for papers has already been issued. And the committees for the two meetings, chaired by Victor H. Thompson, Jr., Mosher Steel Company and Larry A. Kloiber, L.L. LeJeune Company, are now conducting planning meetings to prepare for technical sessions. The Hilton Fontainebleau Hotel offers excellent facilities for the numerous workshop sessions planned and for the more than 100 exhibitors expected to display their products and services. With more than 1,000 attendees at last year's combined conference in New Orleans, AISC anticipates an even larger representation from engineers, fabricators and consultants in 1988.

LIGHTWEIGHT MANUAL AVAILABLE AGAIN

A limited number of the *Manual of Steel Construction*, 8th Ed.—Lightweight (M012) has been reprinted and is now available. At 1 lb.-5¼ oz. and 7/8-in. thick, this lightweight Manual is ideal for both jobsite and traveling. Printed on opaque "bible" paper, it is unabridged and complete in every detail. The 832-pg. Manual still contains the provisions of the November 1978 AISC *Specification for the*

Design, Fabrication and Erection of Structural Steel for Buildings. Data is divided into six basic sections: (1) Dimensions and Properties, (2) Beam and Girder Design, (3) Column Design, (4) Connections, (5) Specifications and Codes and (6) Miscellaneous Data and Mathematical Tables. To order, send check, money order or Visa/MasterCard information (state type of card, number and expiration date) to AISC Publications Dept., P.O. Box 4588, Chicago, Ill. 60680-4588.

FELLOWSHIP APPLICATIONS NOW ACCEPTED

AISC's Education Foundation is now accepting applications from engineering students for \$8,000 scholarships. A maximum of five fellowships will be awarded to those senior or graduate civil or architectural engineering students majoring in structural engineering who propose a one-year project dealing with some aspect of steel construction. Entries must be received no later than April 1, 1988. For an application, contact Robert Lorenz, AISC Education Foundation, 400 N. Michigan Ave., Chicago, Ill. 60611-4185; 312/670-5406.

NOMINATIONS INVITED FOR 1988 T.R. HIGGINS LECTURESHIP AWARD

Applications are now being accepted for the 1988 Theodore R. Higgins Lectureship Award, which recognizes the author of the most significant engineering paper related to steel in the five-year period from Jan. 1, 1982 to Jan. 1, 1987.

The winner, who receives a \$5,000 cash award, presents his paper on six occasions during 1988. A jury of six distinguished engineers from the fields of design, education and the fabricated structural steel industry selects the winning author. Nominations, which should be directed to the Committee on Education, AISC, 400 N. Michigan Ave., Chicago, Ill. 60611-4185, must be received by Nov. 13, 1987. □

81179

EPIC LONG-SPAN DECKS



E750-SPANS TO 32 FT.
E600-SPANS TO 26 FT.
E450-SPANS TO 23 FT.
E300-SPANS TO 15 FT.

AVAILABLE FOR DELIVERY—NOW

Galvanized G60-G90
Lengths to 50 ft.

Plated Decks—Plain or perforated
Most complete line of deck products
in $\frac{5}{8}$ " to $7\frac{1}{2}$ " depths

OUR SERVICE WILL SAVE YOU TIME & MONEY

Epic has these profiles available for shipment on an A.S.A.P. Basis!

Your order will be processed in One Week in most cases. Ask about our A.S.A.P. Service.

Call (412) 351-3913 today for price and delivery information and for product advice on all types of Form Decks, Composite Decks, Long-Span and Roof Decks.

Manufacturing Plants:

- Pittsburgh, Pa.
- Chicago, Ill.
- Lakeland, Fla.

Dealer Inquiries Invited


EPIC®
METALS CORPORATION

Eleven Talbot Avenue, Rankin, PA 15104
PHONE: 412/351-3913
TWX: 710-664-4424
EPICMETAL BRDK

CONTINUING A TRADITION OF RELIABILITY

...Launching A New Era
in Steel Design!

1ST
EDITION



1927...

1986...

**It's Here! The Book We've
All Been Waiting For...**

- based on the 1986 AISC "LRFD" Specification for Structural Steel Buildings.
- grounded in the tradition of the AISC "bible" —the *Manual of Steel Construction*, introduced in 1927 and now in its 8th Edition.
- meshing the familiar and accepted basics with the very latest approaches to steel design, derived from current research and technological advances.
- helping you design more reliable, more economical steel-framed buildings.

MANUAL OF STEEL CONSTRUCTION

LOAD &
RESISTANCE
FACTOR
DESIGN

FIRST EDITION



ORDER YOUR COPY NOW!

AMERICAN INSTITUTE OF STEEL CONSTRUCTION-DEPT B
P.O. BOX 4588, CHICAGO, IL 60680-4588

Enclose payment of \$ _____ for _____ copies of the First Edition Load and Resistance Factor Design Manual of Steel Construction at \$56.00 each.

Name & Title _____

Company _____

Address _____

City _____

State _____

Zip _____

Please enclose remittance. No C.O.D. orders. In New York, California and Illinois add sales tax. Shipping charges prepaid in the U.S. On shipments outside the U.S., add 10% of total purchase for postage and handling. Visa and MasterCard accepted.

Charge My Card No. _____ Exp. _____