

MODERN STEEL CONSTRUCTION

May 1992


\$3.00




Long-Span
Steel

CUSTOM DECKS


THESE SECTIONS ARE ALL DIFFERENT. NOT ONE IS A "STANDARD" DECK SHAPE. BUT, THEY DO HAVE ONE THING IN COMMON — THEY WERE ALL MADE AT **UNITED STEEL DECK, INC.** TO SERVE A NEED FOR A PROJECT THAT REQUIRED A CUSTOM DESIGN. CALL IF YOU HAVE AN APPLICATION THAT REQUIRES CUSTOM BENDING. YOU MIGHT BE PLEASANTLY SURPRISED AT THE SAVINGS A SPECIFICALLY ENGINEERED PRODUCT CAN PROVIDE.




16 GAGE FORM DECK — USED TO BUILD A PIER WITH AN 18" SLAB.



12 GAGE 28' LONG DECK WAS USED TO ROOF AN EXISTING TANK. 15" SLAB; 6" WIDE RIBS USED AS REINFORCED CONCRETE JOISTS AT 15" CENTERS.



12 GAGE TOP AND 16 GAGE BOTTOM CELLULAR DECK USED TO SPAN BETWEEN BOTTOM BEAM FLANGES IN A POWERPLANT. VERY THICK SLAB — FLAT UNDERSIDE LEFT EXPOSED.



16 GAGE LONG SPAN CANOPY DECK MADE FROM PREPAINTED STEEL.

CUSTOM DECK SECTIONS ARE AVAILABLE IN LENGTHS UP TO 34' IN A WIDE VARIETY OF FINISHES. QUOTES CAN ALSO BE PROVIDED FOR STAINLESS, ALUMINUM, AND FOR BENT PLATE UP TO 1/2" THICK.

A COMPLETE LINE OF ROOF DECK, FORM DECK, LONG SPAN DECK, AND COMPOSITE FLOOR DECK IS ALSO OFFERED — WRITE FOR OUR CATALOG.



NICHOLAS J. BOURAS, INC.
P.O. BOX 662, 475 SPRINGFIELD AVE.
SUMMIT, NEW JERSEY 07902-0662 (908) 277-1617



ASSOCIATE MEMBER

FabriCAD

A revolutionary
advance in
computer-aided
detailing from Structural Software

VERSION
SIX!

The new graphical, mouse-driven version of our automated detailing system generates E-plans, anchor bolt plans, elevation views, template sheets, vertical bracing, beam-to-column and beam-to-beam details with a variety of connections. The program is fast and accurate down to the last detail. You can complete two or three times as many sheets per day using the same personnel. That means you can start realizing a return on your investment as soon as you install the program. Our customers agree that FabriCAD Six is easy to learn and simple to use.

"We believe the new input system to be 100% better and faster than FabriCAD II, which was already a good system."

*Fred Keaton
Triad Steel Company*

"The new version makes entering steel easy and logical. You don't have to do a lot of preliminary work. You just open up the drawings, turn on the computer and go to work."

*Larry West
West Detailing Services*

"Structural Software's FabriCAD is the best software for the structural steel industry I have used. I found the organized database with on-screen prompts and helps very user-friendly, well worth the investment."

*Dave Newell
J C Truitt Steel Constructors*

"You can see the whole erection plan on screen. The menu structure has prompts to tell you what to do next. I don't have to sit down and prep the job. Actually, the bigger the job, the more time you'll save, because the input is so fast and easy."

*Bob Hill
James A. McBrady Inc.*

"It's almost self-explanatory to learn how to use it. It took me about a half a day to learn."

*John Teeter
Herb Teeter & Associates*

Call (800) 776-9118 for details on FabriCAD Six and other Structural Software programs, including:

- *Estimating - Generates more accurate estimates for higher profit margins
- *Inventory Control, Production Control and Purchase Orders - Material Allocation programs that link purchasing with production to cut waste and boost profits. Structural Software Co., 5012 Plantation Road, Roanoke, VA 24019.




STRUCTURAL SOFTWARE CO.
SOFTWARE FOR THE STEEL INDUSTRY
(800) 776-9118

MODERN STEEL CONSTRUCTION

Volume 32, Number 5

May 1992



To simplify erection on the Rain Forest Pyramid on Galveston Island in Texas, all field connections were designed with slip critical bolts in oversized or slotted holes. To find out more about this fascinating project, turn to page 34.

Modern Steel Construction (Volume 32, Number 5). ISSN 0002-8445. Published monthly by the American Institute of Steel Construction, Inc. (AISC), One East Wacker Dr., Suite 3100, Chicago, IL 60601-2001.

Advertising office: Pattis/3M, 7161 North Cicero, Lincolnwood, IL 60646.

Subscription price:
Within the U.S.—single issues \$3; 1 year \$30; 3 years \$85.
Outside the U.S.—single issues \$5; 1 year \$36; 3 years \$100.

Postmaster: Please send address changes to Modern Steel Construction, One East Wacker Dr., Suite 3100, Chicago, IL 60601-2001.

Second-class postage paid at Chicago, IL and at additional mailing offices.

FEATURES

- 18 **AIRPORT OVERHANG**
Providing the needed column-free space for an airplane maintenance facility required cantilevering long-span steel trusses 282'
- 29 **LONG-SPAN PERFORMANCE**
Steel trusses clear-spanning 287' create the wide-open space needed for a combined basketball arena/performance center
- 34 **STEEL PYRAMID**
A pyramid proved the ideal structure for a rain forest exhibit

NEWS AND DEPARTMENTS

- | | |
|---|--|
| 6 EDITORIAL | 16 STEEL CALENDAR |
| 9 STEEL INTERCHANGE | 16 PEOPLE IN THE NEWS |
| • When To Use Doubler Plates | 17 CORRESPONDENCE |
| • Analyzing Steel Beams And Members To Aid Erection | 33 NATIONAL STEEL CONSTRUCTION CONFERENCE CALL FOR PAPERS—1993 |
| 12 SOFTWARE REVIEWS | 40 FIRE-PROTECTION PRODUCTS |
| • Engineering Software Company | 42 AD INDEX |
| • Graphic Magic | |

65759



HISTAR[®]

**A new generation
of rolled beams
and column shapes
for economical
steel construction.**

Once again, ARBED leads the industry by featuring a trendsetting combination of mechanical, chemical and technological properties:

- HIGH YIELD STRENGTHS (up to 65 KSI) - even for ultra-heavy sections.
- OUTSTANDING TOUGHNESS PROPERTIES.
- EXTREMELY LOW CARBON EQUIVALENT — ensures excellent weldability.

A NEW PROCESS... QST.

The secret is in ARBED's revolutionary new in-line QST process.

OTHER RECENT ARBED INNOVATIONS:

ARBED-ROLLED 40", 44", and "TAILOR-MADE" (WTM) series — famous for high section moduli, great lateral buckling resistance, and big savings in fabrication costs and weights. These products are also available in the new HISTAR quality as is our standard WF series and H BEARING PILES.

NEW LITERATURE AVAILABLE

Send now for complete data on all these ARBED products, contact Trade ARBED, INC., 825 Third Ave., New York, NY 10022. (212) 486-9890, FAX 212-355-2159/2421. In Canada: TradeARBED Canada, Inc., 3340 Mainway, Burlington, Ontario, Canada L7M 1A7. (416) 335-5710, FAX 416-335-1292.

TRADE ARBED Inc.

INNOVATORS OF STEEL CONSTRUCTION PRODUCTS.

Editorial Staff

Scott Melnick,
Editor
Patrick M. Newman, P.E.,
Senior Technical Advisor
Cynthia J. Zahn,
Senior Technical Advisor
Charlie Carter,
Technical Advisor

Editorial Offices

Modern Steel Construction
One East Wacker Dr.
Suite 3100
Chicago, IL 60601-2001
(312) 670-5407

Advertising Sales

Pattis-3M
7161 North Cicero
Lincolnwood, IL 60646
(708) 679-1100
FAX (708) 679-5926

AISC Officers

Stephen E. Egger,
Chairman
Frank B. Wylie, III,
First Vice Chairman
Robert E. Owen,
Second Vice Chairman
Robert H. Woolf,
Treasurer
Neil W. Zundel,
President
David Ratterman,
Secretary & General Counsel
Lewis Brunner,
Vice President,
Membership Services
Geerhard Haaijer,
Vice President,
Technology & Research
Morris Caminer,
Vice President,
Finance/Administration

Making Better *Designers*

A friend of mine works in the marketing department of a large financial firm in New York. I asked him if the recession was cutting into his marketing budget and he said no, just the opposite. And then he proceeded to lecture me—despite my protestations that he was preaching to the converted—about how smart companies increase their marketing and advertising in tough times to take market share from their competitors and to better position themselves for the imminent recovery.

The advertising community has been singing their song about increasing ad budgets during slow periods for more than 20 years and savvy firms are starting to listen.


But for design firms, there's a corollary tune that's at least as important. No matter how good your marketing is, you still need a good product to sell. And the only way a practicing designer will substantially improve his "product" is through continuing education—a budget area that too many firms are trimming.

In February we printed one of the best received issues in MSC's history—our "Special Report On How Designers Can Cut Fabrication Costs" (if you missed that issue, 16-page reprints are available free to AISC Members and for \$2 per copy to non-members; for more information call 312/670-5421). And while the information in that issue may have been news to many practicing engineers, it was old hat for the thousands who attended the National Steel Construction Conference during the past few years.

Next month we'll publish copies of selected papers from this year's conference. But given our space limitations, we can barely breach the surface of available information. And, of course, there's no substitute to attending a presentation and then taking advantage of the opportunity to discuss the subject with your peers.

There's a lot of firms out there that are producing good designs today. But unless they also concentrate on producing *good designers*, there's no guarantee they'll still be producing good designs tomorrow.

To receive more information on the National Steel Construction Conference, call (312) 670-5422. I hope to see all of you in Las Vegas next month. SM



STAAD-III/ISDS - Ranks #1 in America.

A recent ENR/McGraw Hill survey of the Architectural/Engineering/Construction industry has ranked STAAD-III/ISDS, from Research Engineers, as the #1 structural engineering software in the market today.

The choice of engineers since 1978, STAAD-III/ISDS is being used worldwide as an everyday companion in the design office. The first truly integrated structural engineering software, STAAD-III/ISDS combines geometric layout, analysis, design and drafting in a single software system.



Simple to use, yet sophisticated in application, STAAD-III/ISDS offers the most comprehensive solution to your structural engineering needs. Today, Research Engineers, with six offices in four continents, is setting the structural engineering standard worldwide.

STAAD-III/ISDS - #1 For a Reason.



*Research
Engineers, Inc.*

A reputation you can build on.

For Information Call: 1-800-FOR-RESE
1-800-367-7373

1570 N. Batavia St, Orange, CA 92667
Phone: (714) 974-2500 Fax: (714) 974-4771

RESEARCH ENGINEERS WORLDWIDE:

UK: Research Engineers (Europe) Ltd., 19 Lansdowne Court, Brighton Road, Purley Surrey CR8 2BD Phone: (081) 763-1393 Fax: (081) 763-1379 Telex: 929181
France: Research Engineers, 18 rue de Moresville, 28800 FLACEY Phone: 37.47.51.63 Fax: 37.47.44.63

W. Germany: Research Engineers, Wilhelm-Busch-Str.23, 6140 BENSHEIM 3 AJERBACH Phone: 06251-79577 Fax: 06251-75437
India: Research Engineers Pvt. Ltd, 40 B Darga Road, Calcutta 700 017 Phone: 448914 Telex: 214102

Grade School.

A36

A572 Grade 50

Economical and readily available

Mill certified 50,000 minimum yield

A36/A57250

Economical Readily available Mill certified 50,000 minimum yield

Introducing the one steel for North America: Chaparral Steel's A36/A57250 steel. This mill-certified steel satisfies multigrade requirements in the U.S., Canada and Mexico. The A36/A57250 steel meets all the specifications of our A36, A572 Grade 50, 44W and 50W. It's everything you like about these grades rolled into one. Plus, it costs the same as the A36, and has the same carbon equivalent range, an important factor for welding and formability. It's also just as easy to get, thanks to our innovative shipping techniques and central location. Call your Chaparral representative today and order the structural steel that makes the grade a number of ways: Chaparral's A36/A57250.

**CHAPARRAL
STEEL**

300 Ward Road Midlothian, Texas 76065-9651
Toll Free (800) 527-7979 U.S. and Canada
Local (214) 775-8241 Fax (214) 775-6120

Steel Interchange

Steel Interchange is an open forum for *Modern Steel Construction* readers to exchange useful and practical professional ideas and information on all phases of steel building and bridge construction. Opinions and suggestions are welcome on any subject covered in this magazine. If you have a question or problem that your fellow readers might help to solve, please forward it to *Modern Steel Construction*. At the same time feel free to respond to any of the questions that you have read here. Please send them to:

Steel Interchange
Modern Steel Construction
1 East Wacker Dr.
Suite 3100
Chicago, IL 60601

Answers and/or questions should be typewritten and double spaced. Submittals that have been prepared by word-processing are appreciated on computer diskette (either as a wordperfect file or in ASCII format).

The opinions expressed in *Steel Interchange* do not necessarily represent an official position of the American Institute of Steel Construction, Inc. It is recognized that the design of structures is within the scope and expertise of a competent licensed structural engineer, architect or other licensed professional for the application of principles to a particular structure.

Information on ordering AISC publications mentioned in this article can be obtained by calling AISC at 312/670-2400 ext. 433.

The following responses to questions from previous *Steel Interchange* columns have been received:

How do you decide when to use doubler plates and when to increase the size of a column?


Unfortunately, many engineers release structural drawings without analysis and include a statement to provide a doubler plate "if needed". It is too late, at this stage, to pick a column with a thicker web. Most fabricators would be more than happy to help the designer with this decision during the design stage. Designers should ask for this advise.

Robert O. Disque, P.E.
Besier Gibble Norden
Old Saybrook, CT

The design of steel structures is clearly discussed in the AISC Manuals and publications; however, how does one design and analyze the steel beams and members used to aid in erection?

The design of steel members used in the hoisting process during construction is discussed in the *Engineering Journal* article by Dave Ricker titled, *Design and Construction of Lifting Beams*. This article appeared in the fourth quarter 1991 issue starting on page 149 and will be summarized here.

Lifting beams which are used during erection



can also be called spreader beams. Some examples of lifting beams are shown in the figures printed above.

Figure A is the basic lifting beam and provides two places of attachment to the object being lifted, this avoids the possibility of overstressing if a single attachment were used. This also allows for a straight pull on the object rather than an oblique pull as would result if chokers alone were used. It is sometimes important to minimize unwanted erection stresses or to prevent reversal of stress in certain portions of the lifted object. For instance an oblique pull may cause excess compression in the top chord of the truss at a time when that chord is laterally unbraced. A lifting beam can be used as a "strong back" to provide multiple lifting points on a relatively flexible object.

Other elements commonly associated with lifting beams are hooks, shackles, chokers, and slings. Shackles are used to connect the lines to the lifting beams. Shackles come in various patterns and capacities. Chokers are often used to wrap around the object to be lifted and are usually fastened to the underside of the lifting beam by means of shackles. Slings are used to suspend the lifting beam from the main hook. Hooks are often used with shackles or oblong rings. Hooks with safety latches which prevent the shackles or lines from escaping the throat of the hook are recommended.

A lug plate with its pin hole is an important component of the lifting beam assembly. Tests have indicated that the ratio of pin diameter to hole diameter has little influence on the ultimate strength of the lug material. The diameter of the hole in the lifting lug should be at least 1/16 in greater than the largest pin (or bolt) diameter which is anticipated. However, it is not necessary to have the pin fit snugly in the hole. In fact, the pins are apt to be rough cast and not perfectly round. More often than not, the pin

Steel Interchange

may be considerably smaller than the hole. Pins as small as one half the hole diameter are not rare.

If the lug plate proves to be deficient in bearing strength, washer plates can be welded around the hole to increase the thickness. If the pin is less than a snug fit the lug plate must be designed to prevent tearing failure at the plate edge. Tear-out results when the pin attempts to plow through the plate edge, often resulting in a bulge whose outer edge is in severe local tension. The dimension must be adequate to prevent tear-out but small enough so it will accommodate the shackle length.

In order to prevent the line or shackle from fouling the square corner of the lug plate, the corner may be cut on a diagonal or it may be rounded.

Since lifting beams are often used and stored outdoors, it is recommended that welds be made water tight to prevent hidden corrosion. The weld should be sized to account for any eccentricities which may result from various angles of pull. The thickness of the lug should be such that it will accommodate the "jaw" opening of the shackle. It is not necessary that the lug plate fit snugly in the jaw opening. However, a gross mismatch may cause the lifting beam to hang slightly out-of-vertical which may result in undesirable torsion stresses. A suggested rule of thumb is lug thickness should be no less than one-half the jaw opening. Bottom lugs are treated much the same as top lugs except that they are apt to be continuous plates in order to be more versatile.

Since dead weight is sometimes a factor it may be desirable to use high-strength steel. Lifting beam deflection is hardly ever a governing factor. Column sections, that is wide-flange shapes that are approximately as wide as they are deep, are popular for lifting beams because they generally have longer L and L_U lengths. The unsupported length of a lifting beam is the length between the outermost lifting holes.

In establishing the lifting capacity of a lifting beam, several factors must be considered in addition to the static weight of lifting beam, shackles, and lines must be included. In addition, the effects of impact, acceleration, deceleration, wear, deterioration, and abuse must be considered. An effective way to account for these unknowns is to apply an additional factor of safety to the static load. If the normal allowable stresses are reduced by a factor of 1.8, the resulting maximum working bending stress in the lifting beam will be about a fifth of the minimum ultimate bending strength of the steel. This is in line with other components of the lifting assembly such as the shackles, lines, and hooks, which are usually load rated for 1/4, 1/5, or 1/6 of their ultimate capacity. ANSI/ASME Standard B30.20 requires that lifting beams be designed using a minimum design factor of 3 based on yield strength.

Lifting beams and associated lines and equipment should be inspected before and after use.

After the beam has been assembled and welded, it is usually cleaned and given a coat (or coats) of rust-inhibitive paint. The color should be light in hue and one which contrasts sharply with the primer colors normally used by the fabricator. The lifting capacity of the beam in tons should be clearly stenciled on both sides of the beam in block numbers and letters at least 5 in. in height. If the lifting beam must be used in the upright position only, the top of the beam must be stenciled: USE THIS SIDE UP ONLY. Very often the fabricator or erector will want to stencil the company name on the lifting beam for advertising and identification purposes. Although stenciling in paint is the most common means of marking, a more positive method consists of bead welding the messages onto the beam. Welded figures will endure even if the beam is repainted at a future time.

Equally important as the strength of the lifting beam is the strength of the other components used in conjunction with the beam. These are lines, chokers, hooks, and shackles. Only a knowledgeable experienced rigger should be entrusted with the selection of these other items.

New Questions

Listed below are some questions that we would like the readers to answer or discuss. If you have an answer or suggestion please send it to the Steel Interchange Editor. Questions and responses will be printed in future editions of Steel Interchange. Also if you have a question or problem that readers might help solve, send these to the Steel Interchange Editor.

- 1. Consider eccentricity and what has to be done to accommodate it in various connections.**
- 2. AISC says end-plates and shear tabs shouldn't be more than 6 or 7 bolts deep and clips shouldn't be thicker than 5/8". Can these rules be relaxed if the connection is only on one side of a header beam?**
- 3. Are there concerns about bending of the tube wall in shear tab type connections? When should the shear plate be carried through the tube section?**
- 4. When would you justify the additional cost of high bond epoxy paint and coating for an exterior steel frame exposed to weather and water? What if there is standing water at the base of the column?**

Don't Get Caught In The Mousetrap

When CAD programs were introduced to the drafting world, many people jumped on the CAD wagon.

What detailing professionals found was that, while your sheets looked great and correction time dropped, total time was about the same, or longer, than using a pencil. Graphic oriented detailing software improved the process a little, but corrections and modifications were a nightmare.

That's why STEELCAD skipped the nonsense and moved directly to keyboard input for our line of STEELCAD products. It's 8 to 10 times faster than manual detailing, and 3 to 4 times faster than graphic based systems. Corrections and modifications are a snap, and the flexibility is astounding.

With STEELCAD you don't have to draw it, you just have to think it.



1-800-456-7875

Engineering Software Company's Advanced Integrated Beam Design Program

By Ahmad Rahimian, Ph.D., P.E.

Advanced Integrated Beam Design by Engineering Software Co. is a special purpose computer program for analysis of continuous beams. The program functions under a spread sheet format, which simplifies problem definition as well as error correction. The ease of inputting variable cross sections as well as irregular loadings is one of the strong features of this program.

The program consists of two modules.

The Beam Module performs the analysis of continuous beams, while the Properties Module includes a structural data base as well as features to calculate sectional properties for irregular shapes. The first module can be purchased separately for \$495, or both can be purchased together for \$995.

The package is basically an analysis program. However, Safety Factors for each section are reported on the ratio of S_{max} divided by the calculated stress for that section. Extreme caution should be exercised when using this feature since the value is dependent on more than just the material and an engineer must consider such factors as the design Specification, loading, boundary conditions, and stability.

The program was reviewed in five areas: system requirements; ease of loading the program onto a computer; documentation clarity; performance of stated function; and ease of use for practicing engineers. Each area was ranked from 1 to 5, using the following criteria:

5: This is a great program and I'd like to buy a copy.

4: This is a very effective, very useful program.

3: This program performs its stated goals adequately.

2: The program could be useful but needs to be improved.

1: The program is inadequate.

Because software reviews in *Modern Steel Construction* are written by different engineers at different firms, program ratings cannot be directly compared with previous reviews.

System Requirements

Rating: 5.0

This program runs on a wide variety of IBM compatible computers with minimum hardware requirements and restrictions. These hardware requirements include: PC (8086-based), XT (8088-based), AT (80286-based), PS/2 (80386-based) machines; 512K RAM; one hard disk drive; one floppy disk drive; MS-DOS or PC-DOS versions 2.0 or greater; color graphics adapter; color/composite/EGA/VGA monitor; and an IBM or Epson compatible graphics printer.

Loading

Rating: 2.0

The installation requires the user to be familiar with DOS since a directory has to be created by the user. The files on floppies are compressed and have to be expanded during installation. The installation could become confusing if the user copies all floppies to the hard disk and then tries to install them. What the manual does not clearly specify is that each floppy should be installed separately, one after another.



Some computer knowledge is required to load the program for the first time. But once it is loaded, inputting data is very simple.

Documentation

Rating: 3.5

The documentation is divided into the following sections:

- Section 1: Preliminaries
- Section 2: Introduction
- Section 3: Beam Design
- Section 4: Beam Example
- Section 5: Properties Module

The Preliminaries section covers the license agreement and installation process, which was discussed above. The Introduction explains the program's features, as well as other packages offered by the same company. The latter would be more appropriately included as an appendix or as a separate flyer, rather than as part of the body of the manual.

Sections 3, 4, and 5 are explained adequately using screen printout illustrations. For Section 3, "Beam Analysis" may be a more appropriate title since the program basically obtains the member forces, nodal displacements and reactions. Section 4 includes several examples with Input and Output. Section 5 explains the Properties Module, which by itself has two parts: MOMENTS (Properties Calculator) and QUICK-SHAPE (Materials Library). The Properties Calculator assists in the calculation of sectional properties for nine common geometrical sections as well as user defined irregular sections comprised of rectangular pieces. The Quick Shape submodule contains a data base for AISC sectional properties. An optional data base for wood sections may be obtained from the software supplier.

Program Functioning

Rating: 3.0

The program is very easy to work with because of its spread sheet format. The Properties Module also could be very handy. The Input sheet is very concise, which is a positive point in error corrections and documentation. Also, the program execution is as fast as advertised.

However, there are areas in which the program could be improved:

Units. Program allows the use of either any consistent set of units or the U.S. Customary system. However, the input sheet does not indicate any unit flags. The only way of knowing under what units the system is operating is through a parameter

(Fmt) shown at the lower right hand corner of the screen. Ignoring this coded parameter could have serious consequences. The program should flag the units in each appropriate column.

Reactions. Features should be added for spring reactions as well as displaced reactions. These features are not currently included.

Shear deformation. The program should include, or at least give the user the option of including, the shear deformation in the analysis.

Loading sign. The program assumes the positive sign is upward. This means that for the majority of gravity loading cases the user has to input a negative sign in front of the loading value, which requires extra work. Also, partial omission of this sign could be serious. It is better to assume the downward load as positive, which simplifies input and lessens the chance of error. Alternatively, the user could choose to ignore this sign but the moment diagrams will be reversed in respect to common practice.

Loading case. The program allows only one loading case. Features for additional loading case would be helpful.

Design features. The package does not currently offer any design features. A more complete package would integrate design and analysis to reduce the amount of design effort required.

Safety factor. The potential problem with this safety factor was discussed above. Attempts should be made either to clarify the intent better or to incorporate it separately with a design package.

Conclusions

Overall Rating: 3.0

The program performed the goals stated in its manual adequately, even though the title of the program may lead a user to expect a design package. The drawbacks outlined above do not diminish the program's ability to perform the designated task. However, these shortcomings mean that the program is designed for a limited task on a special class of structures: To analyze continuous beams only.

Ahmad Rahimian, Ph.D., P.E., is a vice president with The Office of Irwin G. Cantor, P.C., a nationally respected consulting engineering firm headquartered in New York City.

While not a true design package, the program does adequately perform continuous beam analysis

Graphic Magic's Multiframe 2D & 3D

By S. B. Haley, P.E., and J. P. Morgan Jr., P.E.

Macintosh-based Multiframe 2D, Multiframe 3D, and Section Maker by Graphic Magic Inc., are object-oriented structural analysis programs that use a graphical user interface to quickly input and analyze structural problems. Multiframe 2D (version 2.01) and Multiframe 3D (version 1.51) analyze two dimensional and three dimensional structures. Both programs use the stiffness matrix method of analysis for solving simultaneous equations to determine forces and deflections of simple or complex structures. The programs perform "a first order, linear elastic analysis to determine the forces and deflections."

Input and output for these programs is handled by moving through a series of "windows" and pointing and clicking a mouse. These programs allow a structural model to be created by drawing the structure and selecting members from standard libraries. The program's standard library includes properties for sections found in the *AISC Manual of Steel Construction*. Custom sections or other materials may also be added to the existing library or to a newly created library.

Each program allows a variety of restraints and loading conditions. Member releases options are rigid/rigid, pin/rigid, rigid/pin, and pin/pin. Choices for support restraints include free, pinned, fixed, X-roller, Y-roller, X-roller fixed, Y-roller fixed, and theta fixed. Spring support restraints are also available as vertical, horizontal, and rotational springs. Load types include global and local joint and member loads. Member loads include point loads, point moments, distributed, partially distributed, trapezoidal, thermal, and selfweight loads. All of these options are applied by choosing graphical icons from the appropriate window and assigning them to the corresponding member or joint.

Section Maker (version 1.51) is a graphical program tool that determines the elastic section properties for members and materials that are not included in its standard library. These sections may be simple with only one shape and material, or may be complex sections composed of multiple shapes and materials. The section properties computed by Section Maker may be stored in a "library" that may be used by the Multiframe programs.

System Requirements

Rating: 5.0

These three programs are written for use on any Apple Macintosh computer system. The Macintosh computer must have a minimum of 1 MB RAM and

1.6 megabytes of hard disk space available. The programs will operate with or without a math co-processor. The copies received for the review came on 3-1/2" disks. The review was conducted using an Apple Macintosh IIx computer with 8 MB RAM, 80 MB hard disk, a math co-processor, and System Software 7.0. Analysis and graphics printouts were made using an Apple Laser Writer II printer with Postscript capabilities.

Loading

Rating: 5.0

Installation instructions provided are clear and concise. Anyone who is familiar with the Macintosh computer will find the software easy to install. Those engineers who are not familiar with the ease of an Apple computer will learn quickly how object-oriented computer structuring can simplify this procedure.

Documentation

Rating: 3.5

Each program comes with an instruction manual in an 8-1/2" x 11" spiral-bound format. The documentation is organized, clear, and professional in appearance. Additional example problems and documentation about the programs theory and the implementation of the theory would make the documentation even better.

The documentation for the Multiframe 2D and Multiframe 3D programs are set up in the similar formats.

"Learning Multiframe2D" (3D) leads the user through a series of exercises that show the basics of Multiframe2D (3D). The exercise is a detailed example for a simple structure. The exercise procedure teaches the user how to create a structure, select members and their properties, apply and combine loads, analyze, view diagrams and tables, and print the results.

"Using Multiframe2D" (3D) elaborates on the basic step by step instructions learned in Chapter 1 by explaining additional instructions, options, and techniques that may be needed to create and analyze a structure.

"Multiframe2D Reference" (3D) lists the organizational structure of the program(s). It graphically shows each of the eight "windows" used by the program and provides a summary for each command within the "windows."

"Multiframe2D Analysis" (3D) describes the numerical method of analysis used by the program(s) to analyze structures. It also lists the capabilities and limitations of the program(s).

The documentation for the Section Maker program is divided into the following chapters: Learning Section Maker; Using Section Maker; Section Maker Reference; and Sections Calculation.

Program Functioning

Rating: 2.5

According to Graphic Magic Inc., all three programs are "a structural analysis and design system for the Apple Macintosh range of computers." It appears that the three programs have analysis capabilities only. The programs give the user the ability to prepare their own design calculations by making use of a "calculation sheet" feature. However, the "calculation sheet" feature has no support for IF statements, looping, or Boolean operations, which limits its usefulness.

A set of example problems were devised to test each program's performance and its ability to meet the program's stated function. The example problems were set up so that each would test most aspects of the program's input, loading, analysis, plotting, and printing capabilities.

A series of multi-story portal frames were used to test Multiframe2D and Multiframe3D. Each test example included a variety of member types, restraints, loading conditions, and load combinations. The test for Section Maker included example problems which were comprised of built-up sections using combinations of standard sections and plates. The results of the Multiframe two and three dimensional sample problems were compared with the results of a well known DOS-based problem solver. The results of the Section Maker sample problems were compared with the results of a HTB proprietary program and calculations done by hand. The comparison demonstrated sufficient accuracy in all three programs.

Conclusions

Rating: 2.5

Initially we devised verification problems for both 2D and 3D modules that were somewhat large compared to the thirty (2D) degrees of freedom and ninety (3D) degrees of freedom of the test problems used. The first thing that came to our attention while creating the 2D test problem was that we could easily produce the basic structure, but the assignment of member properties, end releases, and loadings were cumbersome. The programs allow the user to identify and assign the

member properties, end releases, and loadings to the members in four ways: one at a time, sloping members, all horizontal members, or all vertical members. This constraint makes the input or alteration of a large structure unmanageable. We suggest that the random "tagging" of members in a group and the subsequent assignments be allowed to enrich the application of this software.

The user is also restricted by the program's compulsory node numbering. The node and member numbering are something that should be left to the discretion of the engineer for generation purposes and convenience in numbering. The renumbering of the nodes for band-width optimization could be performed internally in each program.

It should be noted that the three software programs do not perform a design or a check of the steel sections. They are strictly analysis programs except for the interactive "calculation sheets" which are ineffective and must be created by the user. This greatly limits their usefulness in most design offices. However, Graphics Magic Inc. has implemented features for the use of third party postprocessors, spreadsheets, and AISC code checking by software developed by DayStar Software of Kansas City, MO.

The speed, agility, and graphical capabilities of Macintosh windows based software are tremendous. The member end conditions, supports, and many other necessary functions are assigned visually as if one was sketching a model of a structure by hand. The ability to see the structure forming on the screen virtually eliminates common errors associated with batch or numerical input software. These errors include, among others, no connectivity of members to nodes, incorrect member end releases, and erroneous support designation.

We believe that this object-oriented user interface is the wave of the future for structural analysis problem solvers and much more practical than the CAD integrated software which has been developed at this time. Any software that reduces the possibility of user error is headed in the right direction.

This software review has been prepared by S. Blake Haley P.E. and J. Patrick Morgan Jr. P.E. Both are structural engineers with HTB, Inc., Oklahoma City, Oklahoma.

We believe that this object-oriented user interface is the wave of the future for structural analysis problem solvers and much more practical than the CAD integrated software which has been developed at this time

Ratings:

5: This is a great program and I'd like to buy a copy.

4: This is a very effective, very useful program.

3: The program performs its stated goals adequately.

2: The program could be useful but needs to be improved.

1: The program is inadequate.

May 5. **Tubular Sections in Building Construction** (co-sponsored by AISC and VCSSFA) breakfast meeting in Raleigh, NC. Will include design criteria, Type 2 Connections, tube-to-tube connections, design guides, practical recommendations and application examples.

May 5. **Structural Computer Expo** (sponsored by Structural Engineers Association of Northern California) in San Francisco. Contact: Mark Middlebrook at (510) 547-0602.

May 6. **Tubular Sections in Building Construction** (co-sponsored by AISC and VCSSFA) breakfast meeting in Wilmington, NC (see May 5 listing).

May 7. **Tubular Sections in Building Construction** (co-sponsored by AISC and VCSSFA) breakfast meeting in Charleston, SC (see May 5 listing).

May 11-12. **Central Fabricators Meeting**, Clarion Hotel, St. Louis. General topic: estimating and sales. Contact: LaVerne

Duckrow, 7227 W. 127th St., Palos Hills, IL 60463 (708) 361-2338.

May 12-13. **Welding Structural Design** two-day seminar, San Francisco (See January 27-28 listing).

May 18-22. **Structural Steel Design** continuing education course, Madison, WI. Topics include recent changes in specifications and LRFD. Contact: Department of Engineering Professional Development, University of Wisconsin—Madison, 43 North Lake St., Madison, WI 53706 (608) 262-2061.

May 18-21. **AASHTO Subcommittee Meeting on Bridges & Structures**, Portland, ME. Annual meeting of the 50 state bridge engineers who comprise the membership of the AASHTO Subcommittee. Contact: Clendon L. Loveall, Asst. Executive Director, Bureau of Planning and Development, Tenn. DOT, James K. Polk Building, Suite 700, 505 Deaderick St., Nashville, TN 37219 (615) 741-2831.


May 18-21. **International Symposium on Earthquake Disaster Prevention**, Mexico City. Contact: National Center for Disaster Prevention, Av. Delfin Madrigal 665, Pedregal de Sto. Domingo, MEXICO D.F. 04360 (52-5) 606-9942.

June 3-5. **6th Annual National Steel Construction Conference**, Las Vegas. More than 45 seminars and meetings covering every aspect of steel design and construction, including: codes and specifications; computerized design; research; project and shop management; inspection and safety; and fabrication and erection procedures. Trade show features more than 100 exhibitors. Contact: David G. Wiley, AISC, One East Wacker Dr., Suite 3100, Chicago, IL 60601-2001 (312) 670-5422.

June 8-11. **Seismic Design of Bridges**, Washington, DC. Course includes seismic design, structural dynamics, seismic loading, design concepts, seismic response analysis, bearings and columns, and retrofitting. Contact: Cliff Hopkins at (202) 994-8521.

June 8-11. **A/E/C Systems computer show**, Dallas. Contact: (800) 451-1196.

A NEW DIMENSION in Structural Steel



**SDS/2 Provides the Third Dimension—
a new way to look at your future.**

SDS/2—Your Single Source Software Solution:

- Engineering, Analysis, Design
- Detailing
- CNC Interface
- Estimating
- Production Control
- DesignLINK

For information about solutions to expand your horizons, call Design Data today.

800-443-0782 402-476-8278

**DESIGN
DATA** 

"First in...Software, Service, Solutions."

People In The News

AISC-member Stupp Bros. Bridge & Iron Co. has donated \$1,000 to the AISC Memorial Fund in the memory of Cornelius F. P. Stueck, a former assistant vice president who worked at the firm for 40 years.

Metric Debate

Dear Editor:

On page 14 of the March Issue ["Metric Gains Momentum"], you say that "it is more convenient to express stress in newtons per square millimeter," and that "Moments are expressed in terms of N-mm." This is erroneous. ASTM Standard E 380 is the authoritative guide for metric (SI) expressions. ASTM E 380 does not permit a composite unit (such as mm) in the denominator. The proper expression is "Pa" for stress and "N-m" for moment. If the resulting number is not between 1 and 1000, prefixes (such as mPa, kPa or MPa) must be used.

Sincerely,
Werner H. Gumpertz
Simpson Gumpertz & Heger, Inc.
Arlington, MA

MSC Response:

As stated in the article, because section properties are expressed in millimeters, AISC opts to follow the International Standards Organization (ISO) *Draft International Standard for Steel Design*, as well as the draft of Eurocode 3, *Design of Steel Structures, Part 1—General Rules and Rules for Buildings*, both of which express stress in newtons per square millimeter and moments in Newtons per millimeter. Incidentally, the British Standard for the *Structural Use of Steelwork in Building* also uses N-mm² and N-mm.

Truss Bridges

Dear Editor:

The recent article by Messrs. Olsson and Bandel ("Upgrading Steel Truss Bridges", March 1992) had some interesting ideas, although the lack of clear drawings and the brevity of the article made it difficult to understand some of the proposed details.

For instance, in the case of using clamped connections to the exist-

ing steel, how do the authors propose to control corrosion between the existing steel and the clamp? As shown in Sketch 3 of the article, the top clamp plate bears evenly against the top of the existing angles; however, in reality, it will probably bear against the toe of the angle, as the clamp bolts are tightened. This creates a crevice for dirt and moisture to accumulate and start corrosion. If the sketch is to scale, these corrosive products will be approximately 3" to 4" from the bolt, which will cause large prying forces on the bolts. Whether the bolts will fail or the plate curls will depend on the thickness of the clamping plate and the pitch of the bolts.

Sincerely,
Ralph D. Watts, P.E.
North Island Engineering Ltd.
Comox, B.C., Canada

Nils Olsson responds:

Figure 3 shows how the bottom flange of the new cantilevers are connected to the existing transverse beams. In order to minimize the connection to the existing girder, the compression flange plate at the bottom is only connected at mid-span to the existing transverse girder and only for unbalanced live loading.

For all symmetrical loading, the new bottom flange is not connected to the existing girder, but the existing girder is guiding the new flange plate to prevent vertical or horizontal buckling. The clamps, therefore, connect only the side lugs, the rivet head spacer plate, a filler plate and a clamp plate; there is no force exerted from the clamp plate to the existing floor beam angles. It is natural that all elements prior to installation shall be properly painted.

FACT:

RAMSTEEL was the highest rated of all Structural Engineering Software on the market today according to the 1992 *Modern Steel Construction Magazine* user software survey.

"RAMSTEEL allowed us to meet a very tight schedule with a smaller, more efficient design team. The savings in man hours quickly paid for the cost of the program."


Nabih Youssef, S.E., President,
Nabih Youssef & Associates, Inc. Los Angeles, CA




INTERGRATED ANALYSIS, DESIGN
AND DRAFTING OF STEEL BUILDINGS

For more information or an in-house
demonstration, call 800-726-7789
FAX 916-895-3544


RAM ANALYSIS
55 Independence Circle, Suite 201
Chico, CA 95926



RAMSTEEL provides user interaction like you've never seen before!



Break into the LRFD competitive edge with full ASD vs. LRFD comparisons at the click of a button.



**AIRPORT
VERHANG**



**Providing the
needed
column-free
space for an
airplane
maintenance
facility required
cantilevering
long-span steel
trusses 282'**

By Jon C. Herrin, P.E.

While it may never be seen by most passengers, American Airline's latest construction project may be its most important.

The 780,000-sq.-ft. hangar/shop building is the centerpiece of American's new maintenance and engineering facility at the new Alliance Airport (AFW) in Fort Worth and is crucial in keeping the airline's fleet in the air. American's 175-acre campus consists of the hangar, eight other major buildings, and a variety of smaller structures totaling 1.7 million sq. ft. Total cost for the base is \$750 million.




The facility functions as American's heavy "C" check base for its fleet of Boeing 757, 767, and Airbus aircraft. The Federal Aviation Administration (FAA) mandatory heavy "C" check is performed after every 5,000 flight hours, about every 12 to 18 months for commercial transport. The "C" check is basically a complete overhaul of the

aircraft, with over 15,000 mechanic man-hours spent on each aircraft. Each aircraft is essentially stripped down to the airframe, with items such as engines, flaps, rudder, landing gear, seats, etc., removed in the hangar and inspected, repaired or rebuilt as required in shops located throughout the base. A normal "C" check takes about 14 days.

Design Requirements

The hangar was required to accommodate seven wide body aircraft simultaneously, arranged wing tip-to-wing tip, with sufficient working clearance around each aircraft. These requirements dictated a high bay floor plate 1,275' long-by-282' deep, with a clear height inside for the vertical stabilizer and bridge cranes of 75'.

Fifty years ago, the DC-3—with an overall length of 65' and a wing-span of 94'—was the workhorse of the American airline industry. Today, it's the DC-10 and MD-11, each 182' long, 59' tall and with a



wingspan of 165'. Fifty years from now, who knows?

No Columns Along 1,275' Opening

Providing a column-free clear opening along the hangar doors would alleviate concerns that fixed objects such as columns along the door opening would hinder future operations. However, accomplishing this meant that no columns would be allowed along one of the 1,275' sides. The challenging design parameters were met by an innovative combination of 282'-long cantilevered steel trusses supported by reinforced and post-tensioned concrete towers along the back wall of the high bay space.

The high bay roof structure is composed of seven bays of essentially identical framing: 165' span trusses, with depths varying from 16' to 24', space 44' on center, supporting long span open web bar joists. These bays of framing are supported on wide flange columns at each end of the 1,275' long building, and by six identical cantilevered box trusses along the interior of the building. The box trusses are suspended from six concrete towers measuring 25'x100' in plan, and rising to a height of more than 160' above the finish floor.

In addition to the customary design loads for the roof structure (structure weight, roofing and insulation, catwalks, plumbing and fire protection, and code required roof live load), it was required to support a 10-ton bridge crane in each bay plus the weight of hanging work docks serving the fuselage and horizontal and vertical stabilizers. The cranes and docks along impose a design load of 540,000 lbs. per bay onto the roof structure.

Project architect was Corgan Associates Architects, Dallas, and structural engineer and prime consultant was L.A. Fuess Partners Engineers, Dallas. General contractor was HCB/Walker Joint Venture Dallas/Ft. Worth.

Structural Details

From a purely structural stand-

point, the lightest, and therefore most economical truss, has maximum depth at point of maximum moment. It was imperative, then, to obtain the maximum depth possible at the face of the concrete towers.

The top of the concrete towers was set at the maximum height allowed by FAA standards with regard to radar and instrument landing guidelines. It was possible to slope the bottom chord of the truss down over the nose of the aircraft and the second floor mezzanine, so that the bottom chord framed into the towers at the fourth floor level, providing a depth of 100' from the point of support measured from the top of the tension strut to the bottom chord of the box section. At that point, the depth between the top and bottom chords is 20', and it varies over its length from 16' deep to 27' deep.

The top chord of the box section is sloped from front to back at a minimum of 1/2" per foot to provide the necessary roof drainage, establishing the box depth and also setting the depth of the 165' span trusses in the orthogonal direction.

All trusses on the project are composed of 14" wide flange sections turned with webs horizontal for connection simplicity. Virtually all 7,770 tons of structural steel on the project, including all truss members, is ASTM A572 Grade 50. The largest individual truss member is a W14x455 located on the box truss bottom chord adjacent to the tower. The box truss tension struts are W36x328.

Tension Struts

Of utmost importance to the design and constructability of the truss was the connection detail at the top of the tension struts. The design force in each tension strut is 2,400 kips, which must be transmitted to the concrete tower at a joint in which three concrete members intersect. The joint contains a total of 76 #11 reinforcing bars converging from three directions, plus eight 3/4" diameter corrugated ducts in the diagonal concrete member housing a total of 96 0.6", 270 ksi post-tensioning strands,

K2084	TRUSS	W14 x 45	32'-2 1/2"
W1	W14 x 45	32'-2 1/2"	4
W2	W14 x 45	32'-2 1/2"	4
W3	W14 x 45	32'-2 1/2"	4

SHOP DETAILS
THE EASY WAY

Beams, Columns, Plans, Elevations, Stairs, Handrail, Grating Layout, Ladders, Bracing, Roof Frames, Floor Frames, Kickers, Hangers, Relieving angles, Roof angles, Pipe racks, Breeching supports, Stack framing, Access platforms, Gussets, Tubes, Trusses, Towers or anything else you can fabricate.

without using a pencil.

If you want to get rid of your pencil we can show you how.

COMPUTER DETAILING CORPORATION
A service company for steel fabricators and detailers
1310 Industrial Blvd.
Southampton, PA 18966
215-355-6003


FREE!! FREE!! FREE!! CONTINUOUS BEAM ANALYSIS PROGRAM

That's right, for just a nominal charge to cover materials and handling (\$19), we will send you our powerful CONTBEAM program. This is our fullblown CONTBEAM, not a watered-down version. How can we possibly afford to do this? It is because we are convinced that once you've tried our software, you will be back for more. You will also receive all required documentation, as well as a catalog for our 100+ programs for concrete, masonry, steel, timber and post-tensioned concrete design, including design and graphics modules for CONTBEAM. Our programs are developed to run on IBM-PC, -XT, -AT, PS2 and most compatibles.

CONTBEAM analyzes continuous beams having up to 20 spans. Girder moments and shears are computed and may include the effects of up to 100 loadings alternate-day live loadings and live load reductions. Deflections are computed at the span tenth points using Newmark's numerical integration method.

Also, you will be sent a free copy of "CONTBEAM/TALK", SAI's fast, easy, and powerful INTERACTIVE software module for CONTBEAM programs. This "add-on" TALK module allows users to greatly speed up input preparation and problem reruns. The CONTBEAM/TALK module is menu-driven, has a spreadsheet format, and many on-screen help features. Also included are a built-in text editor, and error checking.

Graphics software "GCONBEAM", is available for CONTBEAM. GCONBEAM allows engineers to obtain detailed graphical moment, shear, and deflection diagrams for the CONTBEAM analyses.



005

THE MOST PRODUCTIVE STRUCTURAL DESIGN SOFTWARE SINCE 1966

SAI
STRUCTURAL
ANALYSIS, INC.
555 S. Federal Hwy.
Suite 210
Boca Raton, FL 33432
(407) 394-4257

YES, Please send me free CONTBEAM (\$19 to cover materials and handling.)
(Offer valid in the U.S.A. and Canada only, expires July 31, 1992)

NAME _____ COMPANY _____

STREET ADDRESS _____

CITY/STATE/ZIP _____

PHONE _____ MASTERCARD VISA

ACCT. NO. _____ EXP. DATE _____ CHECK ENCLOSED

SIGNATURE _____ DATE _____

WE HELPED CALVARY CHURCH



Calvary Church in Charlotte, North Carolina seats 6,200 people.

WE SAVE MORE THAN SOULS.



Seating 6,200 people, Calvary Church is, in a word, big. Which meant building the Charlotte, North Carolina structure required exceptional stewardship in order to keep costs down. And we were delighted to be part of the solution. Our super long span joists were ideal for constructing the beautiful sanctuary. And they were far more economical than using steel trusses or a rigid frame.

What's more, our joists were simple to erect. Two sections were easily bolted together on the job site to create joists as long as 172'.



Our super long span joists easily bolt together on the job site.


The architect and structural engineer on the project both had previous experience working with Vulcraft, and they had every faith in our performance. They knew they could count on us for on-time delivery, joists that fit, and a solution to any problem that might arise during construction. As a result, they came to us not only for our long span joists, but also for 250,000 square feet of steel roof and floor deck.

We'd like to show you how we can help with your jobs, too, and save more than you might imagine. So contact any of the plants listed below or see Sweet's 05100/VUL and 05300/VUL.

PO Box 637, Brigham City UT 84302 801/734-9433; *PO Box 100520, Florence, SC 29501 803/662-0381; PO Box 169, Fort Payne, AL 35967 205/845-2460; *PO Box 186, Grapeland, TX 75844 409/687-4665; *PO Box 59, Norfolk, NE 68702 402/644-8500; *PO Box 1000, St. Joe, IN 46785 219/337-5411.
*Deck manufacturing locations. Architect/Engineer: Commercial Builders of Kansas Inc.; General Contractor: Metric Constructors; Steel Fabricator: Central Steel Inc.; Steel Erector: Metric Constructors.

VULCRAFT

A Division of Nucor Corporation



plus various other ties and confinement reinforcing.

With careful design and dimensioning of the reinforcing steel and post-tensioning, it was possible to provide for 20 2 1/2"-diameter anchor bolts to support the 2,400 kip tension force. The 12'-long, ASTM A193-B7 bolts bear on a 4"-thick steel bearing plate on the back side of the concrete member.

The design load is transmitted from the W36x328 tension strut to the bolts through a 4 1/2 ton weldment composed primarily of 3"- and 4"-thick plates. All plates in the weldment are fine grained, silicon killed, 50 ksi steel to allow for the required complete penetration groove welds. All welding on the assembly was performed in the shop. A 10"-diameter, 50 ksi steel pin provides the connection between the wide flange strut and weldment.

Correct location of the anchor bolts was assured through the use of a shop welded steel pipe sleeve

Structural Material Sorter Ver. 4.0

A series of programs designed to help steel fabricators manage material.



- Reduces labor — increases accuracy.
- Automatically computes weights, surface areas, bolt counts and lineal totals.
- Quickly sorts lists into proper order.
- Produces optimum length-cutting lists from in-house stock, vendor's stock or the best combination of each.
- Provides shipping lists based on piece-mark sequence.
- Tallies material costs, shop hours and field hours for easy estimating.
- Uses simplified terms so non-tech personnel can operate with ease.
- External Data Interface can import existing computer-based material lists.
- Call today for a FREE demo kit, including the full system's operator's manual!

E.J.E. INDUSTRIES, INC.

COMPUTER SOFTWARE FOR STEEL PROFESSIONALS
287 Dewey Avenue Washington, PA 15301 (800) 321-3955

SAVE TIME AND MONEY CALCULATE CONNECTIONS with CONNECT® version 3.5

Software and Data Base for IBM PCs and Compatibles
Proven, easy to-use, moderate price

DETAILERS, STRUCTURAL ENGINEERS
design, document, check:

- Framed Beam Connections
- Seated Beam Connections
- Eccentric Connections
- Connections in Tension
- Moment Connections
- Hip and Valley Details
- Oblique bracing with Setbacks
- Web Stiffeners
- Triangulation and more.

Print a hard copy of calculations and/or save on disk.

Updated to AISC 9th Ed.

Demo package available.

Write or call today:

Hess Technical Services

2389 Mill Grove Road
Pittsburgh, PA 15241

(412) 831-2010 or (412) 833-7525

00769

assembly that was positioned in the forms and cast within the concrete beam at the peak of the tower. The plates on each end of the embedded assembly were match drilled with the bearing plate and weldment to assure proper fit-up in the field. In addition, varying thicknesses of finger shim plates were used between the weldment and the face of concrete to allow for erection tolerances and elevation adjustment of the truss.

The compression connection to the tower at the bottom chord is accomplished through a similar weldment and 10" pin. The face of the concrete at this location is cast such that the resultant truss force is orthogonal to the concrete. After final adjustment of the truss, the base plate was grouted with high-strength, non-shrink grout.

The cantilevered truss was analyzed and designed with a three dimensional computer model using STAAD-III from Research Engineers and Intergraph's Micasplus.



The inside of American Airline's new maintenance and engineering facility is designed without columns to accommodate even the largest aircraft. The roof structure can support 540,000 lbs. per bay.

WHEN YOU BUY ST. LOUIS, YOU BUY AMERICAN!

- AND YOU GET:
- FULL TRACEABILITY
 - LOT CONTROL
 - CERTIFICATIONS

Registered Head Markings on all structural and machine bolts:



A-325
Type 1



A-325
Type 3



A-307-A



A-449



A-307-B

Products from 1/2" — 3" diameter include:



COUNTERSUNK



SQUARE
MACHINE



BUTTON
HEAD

ST. LOUIS SCREW & BOLT COMPANY

6900 N. Broadway • St. Louis, MO 63147

(314) 389-7500 • 1-800-237-7059 • Fax (314) 389-7510





Great care was taken during the design and erection of the steel members. The erector, Derr Construction Co., lifted the box section in three parts and provided three sets of shoring towers to temporarily support the box sections prior to adding the tension struts.

The 3D analysis was required to accurately model the affect of unbalanced loading on the box section, such as full dock and crane load on one bay and none on the adjacent bay. Calculated deflection at the tip of the cantilever due to all loads is 17"; 7" on this was cambered out during fabrication and erection. Erector was AISC-member Derr Construction Company.

150,000 Bolts

The project required 800,000 drilled bolt holes and 150,000 high-strength bolts. All trusses were field bolted using A325 or A490 bolts of various sizes, in bearing connections. Both halves of each cantilever truss, and all 165' span trusses were required to be completely assembled in the shop to assure proper fit-up in the field. Trusses were shipped knocked-down and re-assembled in the field prior to lifting.

Each cantilevered truss was fully erected and adjusted to the

SITUATION:

Your project needs cost-effective fireproofing, thermal insulation or acoustical control.

SOLUTION:

ISOLATEK'S full line of economical, spray-applied protection products.

At ISOLATEK, we customize solutions for your toughest fire, thermal and sound control problems. Our dependable, UL-tested formulations require minimal manpower and are designed for fast spray applications and easy clean-up.

Ideal for both new and retrofit jobs, ISOLATEK's CAFCO® products have been the right choice for countless major projects across the country. For over 40 years, CAFCO has been protecting commercial, industrial, medical, educational, recreational and other types of facilities.

Whether your situation calls for specialized fireproofing, thermal insulation or acoustical control, ISOLATEK has the solutions to your toughest problems.

For additional information, contact us at **800 631-9600**.

ISOLATEK
INTERNATIONAL

41 Furnace Street, Stanhope, NJ 07874/USA
TEL: 201 347-1200 FAX: 201 347-9170



ECOM SES™ Structural Expert Series

- + Written by Practicing Engineers
- + Over 1,800 Installations
- + 18 Years Experience

2D and 3D Frame Analysis
Steel Beam/Column Design
Composite Steel Design
Concrete Design
Now available on UNIX
for Sun and IBM RS/6000

For a **FREE** DOS Demo set
call 414-365-2100

ECOM Associates, Inc.
8324 N. Steven Rd.
Milwaukee, WI 53223

09770

proper tip elevation prior to beginning erection of the simple trusses in the adjacent bays.

In addition to the final cantilevered configuration, the truss was designed to be supported during erection at a point directly beneath the intersection of the box section and the tension struts. Derr elected to lift the box section in three sections and provided three sets of shoring towers to temporarily support the box sections prior to adding the tension struts.

After all connections were complete, two sets of shoring towers were lowered and the truss was adjusted by jacking at the location described previously. After the necessary shim stack thickness at the upper tension strut connection was achieved, providing the proper tip elevation, the anchor bolts were tightened and the jacking towers removed.

A series of horizontal X-braces at the bottom chord level provides the diaphragm required for stabil-

ity and lateral forces. Composed of field bolted double angles, these elements transfer lateral forces to the concrete towers and vertical steel X-braces located in the end walls.

The shop and office area along the back of the hangar building between concrete towers contains 300,000 sq. ft. of composite steel floors. All framing is with ASTM A572 Grade 50 steel. Design live load for these floors is a hefty 250 psf.

The hangar doors for this project consist of eight independently operated sections, each 75' tall and 159' wide. They are electrically operated, motor driven, and run along crane rails embedded into the floor slab. The telescoping roller guides at the top of each door leaf allow for the vertical deflection of the roof structure and transmit lateral forces to the bottom chord diaphragm framing.

The roofing of the building is a standing seam metal roofing over rigid insulation and a base steel

deck. Specially designed light gauge metal Z purlins nest into the base deck flutes and are screwed directly into the bar joist top chord. The standing seam panels are attached to the top flange of the Z purlins as in a "normal" metal roofing application. The base steel deck, which is a standard 22 gauge roof deck, provided a working platform for the roofing contractor and neat, durable finish ceiling. The standing seam panels were field rolled to lengths required in order to eliminate end laps in the panels. Maximum sheet length is 200'.

Design of the hangar facility began in August 1989, with construction commencing in March 1990. American Airlines began servicing aircraft in the facility in October 1991.


Jon C. Herrin, P.E., is a principal/vice president with L.A. Fuess Partners Inc., a structural engineering firm headquartered in Dallas.

The All New Actual Size 3 1/4 "x 5 1/2 "x 3/8 "

Jobber III

Dimensional Calculator

The Calculator that does it All !



The Indispensable Tool for Everyone Who Works with DIMENSIONS Detailers, Fabricators, Foreman, Crewleaders, Layout Men, Engineers & Architects. The Worlds BEST Feet/Inches/Sixteenths Engineering Calculator that also works in Decimals & Metric (millimeters) with **Instant Conversion at the touch of a button !**


New Features Include:

- * Built-in Trig. Functions That **Automatically** Solve Bevel, Rise, Run & Slope in all Modes. Makes Calculating Beams, Columns, Frames, Stairs, Rails, Braces, Roof Slopes & Circles **Easy**.
- * The only Calculator with the Jobber III patented 0/15 Keyboard that cuts keystrokes by **66 %**. Saving You time & entry errors over "old fashion calculators" & that Means Money to YOU !
- * **4 Memories** that automatically retain your data even when the Jobber III is off.
- * **Everyone** who works with Dimensions needs the Power of the **Jobber III**.

Special Price
\$ 99.95 + \$4.50 S&H

Jobber Instruments
P.O. Box 4112 -C
Sevierville, TN, 37864

Order Toll-Free
1-800-635-1339



Long-Span Performance

Steel trusses clear-spanning 287' create the wide-open space needed for a combined basketball arena/performance center

By Donald W. Hoffmann, P.E.

Although the original design of the Ervin J. Nutter Center—which allowed the architecture to reflect the building's structural design—proved too expensive, the engineers still managed to maintain the desired appearance by incorporating a more conventional—and more economical—steel frame.

The original framing concept for the new athletic and performance center at Wright State University near Dayton, OH, featured a space truss system known as a *Takanaka Truss*. The shape of this system has its top chords in a direction of 45 degrees to its bottom chords and its first diagonal slopes inward and upward to the top chord creating a mansard-type roof shape. The geometry of the Takanaka Truss established the perimeter mansard roof profile and dictated the main column locations. In addition, the entire design of the seating and aisle layout (10,500 seats for basketball; 13,000 for performances) was based on this geometry.

But what started as a wonderful blending of architecture and engineering proved too expensive; when the roof structure was bid, the cost exceeded budget by \$1 million. Fortunately, a redesign using conventional linear trusses and other conventional steel framing allowed the project to come in on budget.

The redesign used four main trusses varying in depth up to 30' and clear spanning 287' across the arena. Sub-trusses spanning 62' and 105' frame between the main trusses. Metal deck and bar joists frame between the sub-trusses.

The center, which opened late in 1990, includes physical education and athletic facilities. Auxiliary gymnasiums and an indoor running track provide recreational facilities for the student body. KZF Incorporated, headquartered in Cincinnati, was the prime architect and engineer. Construction manager was Shook Building Group, Dayton.

Structural Challenges

Since the original Takanaka system established the roof profile

and column locations, KZF engineers had a structural challenge to adapt a conventional system to fit the mansard sloped roof design. In order to maintain the architectural design—a truncated pyramid with clipped corners—the structural engineers designed a perimeter space truss around the edges of the roof to support both gravity and lateral loads with spans of as much as 172'. The perimeter space truss was designed to fit the architectural profile and provided the needed three-dimensional stiffness to stabilize the main roof trusses.

In addition to the roof truss dead load, the design roof live load consisted of snow load and an additional 20 psf for miscellaneous loadings—primarily the lighting, event rigging, sound and catwalk systems. The lateral loads used were based upon a wind speed of 90 mph, exposure "C" and Zone 2 seismic loadings.


Spherical bearings were used to accommodate the truss end rotations and to uniformly distribute the truss reactions. The lateral forces from wind and earthquake are distributed to two columns on the north wall and two columns on the east wall. At these four locations, guided slide bearings transfer the lateral thrust to concrete columns in one direction while allowing the bearing to slide in the other.

The four remaining truss reactions are supported by unguided or free-floating slide bearings, which theoretically transfer no lateral load to the column tops, except for the friction of the slide bearing. The temperature effects on a structure of this size required provisions to accommodate 4" of movement by the slide bearing.

Jumbo Sections

For the truss design, the top and bottom chords used W40 jumbo wide flange sections turned horizontally. The weight ranged from 167 lbs to 531 lbs per linear foot.

Dual gusset plates were connected to the outside face of the flanges to essentially form a through truss, which was used as part of the catwalk system. This



Top photo courtesy of Wright State University; others by Greg Girard.



The mansard-style roof shape reflects the original structural design of the center. When that system proved too expensive, the engineers switched to a more conventional steel system but managed to still keep the aesthetically desirable roof shape. Photo by Greg Girard

chord orientation allowed for two reasonably light diagonal web truss members connecting the top to bottom chords. An additional benefit was a very stiff truss in the plane of the truss, a major benefit during the erection of the truss. Prime steel fabricator on the project was AISC-member Carter Steel & Fabricating Co. and steel erector was AISC-member John Beasley Co.

Pre-Assembled In The Shop

All of the major truss components were shop assembled to avoid the problem of member fit-up when dealing with such large members. A combination of pre-punching and shop drilling of the bolt holes as the components were assembled insured a good fit. The trusses were then partially disassembled, as needed, for shipping.

The main trusses were assembled in thirds on the ground. Each 40- to 60-ton section was then lifted into position. The outer portions were suspended from a guyed "gin

STEEL 2000



THE INTERNATIONAL VERSION

of the industry's hardest working automated steel fabrication management program will be unveiled at the AISC Conference in Las Vegas on June 3. Meet us at booth #401C.


STEEL SOLUTIONS

P.O. Box 1128 • Jackson, MS 39215 • 601-932-2760 • Fax 601-939-9359


RISA-2D

Rapid Interactive Structural Analysis
Two Dimensional

Whether designing multistory buildings



or just checking a single member,



RISA-2D is the best tool for the job.
Give us a call and see for yourself!

For a demo, call: 1 (800) 332-7472
FAX: (714) 863-0244

17900 Sky Park Circle, Suite 106
Irvine, CA 92714

RISA
TECHNOLOGIES

pole" and the center section lifted in place. The sub-trusses, which also act as bracing for the main truss, were then framed into the main trusses. These sub-trusses were not pre-assembled in the shop, but were assembled on the ground and lifted into position.

The perimeter edge space trusses proved to be the most time-consuming design portion of the roof system. Assisted by a computer, analysis of the design was fairly straight-forward, though still time consuming. Analysis was performed using Structural Analysis Inc.' (SAI) "Space" and "Plane" programs.

Detailing the joints presented a unique challenge. A joint with the axis of all members framing to a single concurrent point was physically impossible to construct. Therefore, a few of the members had to be offset from their theoretical alignment and the eccentric forces resolved with the addition of joint stiffeners. More than 400 fab-



The Ervin J. Nutter Center at Wright State University is a combined sports and entertainment center. It seats 10,500 for basketball games and 13,000 for concerts and also includes auxiliary gymnasiums and a running track. Photo by Gordon Morioka.

M-STRUDL®

The Best Selling
Civil/Structural Program Since 1987

ANALYSIS

- 2D/3D Frame / Truss / Plate / Shell
- Static / P-Delta / Dynamic / RSA Analysis
- Capable of 1000's of joints and 100's of load cases
- Moving load generator
- Interactive geometry, deflection, mode shape, plots
- Interactive shear and moment diagram plots
- AISC Library included

DESIGN

- Interactive graphic menu driven design
- Continuous beam, section properties, frequency calculations
- AISC code check and sizing including LFRD
- ACI column, beam, footing, retaining wall design
- Design details can be output to AUTOCAD
- Excellent in report presentations

SATISFACTION GUARANTEED*

*See our brochure for details
Supports DOS/OS2 operation systems


"Ask for a brochure today!"
You'll be glad you did.



P.O. Box 14676
Fremont, CA 94538-4676
415/226-8857
Fax 415/226-7328

ROUND O BEAM BENDER

FOR BEAMS,
CHANNELS,
PIPE & OTHER
SYMMETRICAL
SECTIONS



ROUND O
BEAM BENDER
Model B-5000S
rolling W21" x 147 lb.
beam on X-X axis

Ideal for beams and channel both the "hard way" and the "easy way". Three fully hydraulic models with capacities ranging up to **36" WF beam on X-X axis**, 36" beam and channel the "easy way", 20" pipe, 15" round bar, 13" square bar, 16" x 12" flat bar the "easy way" and 16" x 10" flat bar the "hard way".


Section modulus capacities to 550 in³.

COMEQ, Inc.

Phone: (410) 325-7900

P.O. Box 2193
Balto., MD 21203

Fax: (410) 325-1025

SLUGGER® by Jancy Engineering Co. 
 Manufacturer of Portable Magnetic Drilling Systems

2735 Hickory Grove Road, Davenport, Iowa, USA
 Phone 319-391-1300 FAX 319-391-2323
 Ask for Pat, Steve or Jeff

Call for a
 Demonstration
 Today

Lightweight-Accurate
 Durable-Convenient
 Affordable

Made in
 America's
 Heartland



IOWA



Patented

Available Exclusively Through the Best Stocking Distributors

rication drawings were needed to detail the complex roof system.

Lateral Loads

The transfer of lateral loads from the roof system to the supporting columns and foundations presented the challenge of dealing with 250 kips of lateral load applied to the top of a 6'-diameter cantilevered column 50' above the concourse level. Two stability columns were located on the east end of the arena and extend an additional 35' to the arena floor. The stability for these columns was provided by a diaphragm link to a nearby concrete stair/elevator tower.

However, this bracing arrangement produced unexpected design problems when the effect of a long cantilever and a short back span were analyzed. The "PRYBAR" effect magnified the 250 kip horizontal load at the column top to approximately 800 kips just above the concourse level.

To provide the needed stability a pair of W36x260 beams were encased within the 6' diameter concrete arena columns. Also, a horizontal steel transfer truss cast within a concrete diaphragm slab was used to transfer the loads to the stair/elevator "shear" towers. These towers provided the east/west stability not only for the arena roof but also for the adjacent academic wing and auxiliary gym.

The auxiliary gym is 120' x 240' with a 33'-10" clear height. Long span joist girders span the 120', spaced at 20' centers. The depth of the joist girder varied from 7' at the low end to 9' at the high end. Around the perimeter of the auxiliary gym, a 9'-wide banked running track was suspended from the roof girders.

The academic wing is a 3-story structure with approximately 35,000 sq. ft. per floor. It was framed with conventional composite beam and column construction.

Donald Hoffmann, P.E., is a senior project structural engineer with KZF, Incorporated, a multi-discipline design and consulting firm in Cincinnati.

AUCTION

Major Structural Steel
 Fabricator and Contractor

**RIVERSIDE STEEL
 AND CONSTRUCTION, INC.**

11400 Greenstone Ave.,
 Santa Fe Springs, CALIFORNIA

Sale Date: Wednesday, MAY 6, 10:30 A.M.

Inspection: Monday and Tuesday, May 4 & 5,
 9:00 A.M. to 4:00 P.M. and Day of Sale

MACHINES & EQUIP.: (15) Overhead Dbl. Girder, and Sgl-Leg Gantry & Mono-Rail Cranes, up to 10 Ton Cap... (Over 50) Hoists up to 5 Ton w/ Pend. Cntrl.; Over (150) Welders up to 1000Amp; (10) Portable Gas Welders; Manipulators; Sub-Arc & Stud Welders; **ROJAR** Spar Mill; **HEM & HYDROMECH** Saws; **IRONCRAFTER, BUFFALO & MUBEA** Ironworkers; (6) **WHITNEY** Portable Hyd. C-Frame Punches; Shears; Radial Drill; **HYD. 400 TON CAMBER MACHINE**; Hyd. Press; 150 H.P. I.R. & 75 H.P. **JOY** Air Comp's; (4) Sets Beam-Turning Fixtures; Tank Turning-Rolls; Cut-Off Saws; Dry Rod Ovens; Lg. Qty. Welding Rod, Wire & Supplies; Lg. Qty. Hand Tools Incl.: Enerpac's; Grinders; Track Burners; Torpedo Grinders; Saws; Drills; Reamers; Come-Along's & Chain Binders; Impacts; Threaders; Clamps; Cables; Slings; Spreader Bars; Dunnage; Pneu. Hammers; Chippers; More! **Most-All Contractors Field Tools, Office Mach & Equip.**

ROLLING STOCK: (84) **HYSTER** 30,000 lb Diesel Forklift; (2) (79) **CAT** 20,000 lb Diesel Forklifts; (75) **HYSTER** 18,000 lb. Forklift; **HYSTER** 16,500 lb Forklift; (85) **HYSTER** 8,000 lb. Diesel Forklift; (79) **CAT** 8,000 lb. Forklift; (11) **FORD** Utility & Pick-Up Trucks; (1) Water Truck; (1) Yard-Mule; (4) 40' Box Containers; (17) Flat-Bed Trailers; **OFFICE Trailers**

(3) STRUCTURAL STEEL FABRICATING BUILDINGS TO BE OFFERED INDIVIDUALLY AND/OR AS PKG.: Approx. 85,000 ± Sq. Ft. Total within These Buildings; Plus...Crane & Crain Rails, Electrical and Plumbing! **Phone / FAX For Free Brochure!**



INDUSTRIAL ASSETS INC.

11846 Ventura Blvd., Suite 207, Studio City, CA 91604
 • Phone: 818-508-7034 • FAX: (818) 508-3025

(800)-243-4887 Toll Free Outside CA

DESCON

DESIGNS AND DETAILS
 STEEL CONNECTIONS



FOR A FREE DEMO DISK
 CALL OR WRITE TO

OMNITECH ASSOCIATES

P.O. BOX 7581
 BERKELEY, CA 94707
 (510) 658-8328

02773

CALL FOR PAPERS

1993

National Steel Construction Conference
Orlando Convention Center, Orlando, FL
March 17-19, 1993

Primary Author:

Name _____
(First) (Middle Initial) (Last) (Professional Suffix-Degree)
() AISC Active Member () AISC Associate Member () AISC Professional Member () Non-Member

Position/Title _____

Place of Employment _____

City _____ State _____ Zip _____

Business Phone () _____ Ext. _____ Fax# () _____

Home Address _____

City _____ State _____ Zip _____

Home Phone () _____ *Preferred mailing address () Business () Home

Co-Author(s):

1. Name _____
(First) (Middle Initial) (Last) (Professional Suffix-Degree)

2. Name _____
(First) (Middle Initial) (Last) (Professional Suffix-Degree)

3. Name _____
(First) (Middle Initial) (Last) (Professional Suffix-Degree)

Invitation/Call For Papers

The 1993 National Steel Construction Conference will be held at the Orlando Convention Center, March 17-19, 1993. Participants include structural engineers, fabricators, erectors, educators, and researchers. Potential authors may submit abstracts of papers on design, fabrication and erection of steel structures for buildings and bridges. Topics of interest include:

- Practical application of research;
- Advances in steel bridge design and construction;
- Composite members and frames;
- Buildings designed by LRFD;
- Heavy framing connections;
- Steel-framed high-rise residential buildings;
- Partially restrained connections and frames;
- Economical fabrication and

erection practice;

- Quality assurance and control;
- Case studies of unique projects;
- Computer-aided design and detailing;
- Case studies of unique projects;
- Computer-aided design and detailing;
- Material considerations;
- Fire Protection;
- Coatings and material preparation;
- Structural systems.

Guidelines for Abstract Proposals

Abstracts for papers must be submitted before June 15, 1992. They should be approximately 250 words in length, and submitted on a separate sheet of 8 1/2" x 11" white paper attached to this form.

Authors will be informed of the Organizing Committee's decisions by September 1, 1992. Successful authors must submit their final manuscripts for publication in the 1993 Conference Proceedings by December 15.

Preparation of Paper

Final manuscripts for publication in the official 1993 Conference Proceedings are expected to be approximately 20 pages in length. Copy (including photographs) must be camera-ready. Complete instructions will be forwarded to authors upon acceptance of Abstract Proposals.

Poster Session

Papers not accepted for presentation at the Conference may, at the author's expense, be presented at the Conference Poster Session. Guidelines for the Poster Session will be provided upon request.

Return your abstract with this submission form before June 15, 1992 to:
American Institute of Steel Construction, Inc., One East Wacker Drive, Suite 3100
Chicago, IL 60601-2001 Attention: 1993 NSCC Abstracts
Phone 312/670-5400 Fax: 312/670-5403



Steel Pyramid

A pyramid proved the ideal structure for a rain forest exhibit

By Ali Haris, S.E., Ph.D., and Ian Robertson, P.E., Ph.D.

The latest addition to an education/conference center on Galveston Island along Texas' Gulf Coast is a lush rain forest housed in a steel-and-glass pyramid.

The 142-acre Moody Gardens, a non-profit complex of educational, physical treatment and entertainment attractions, is in its sixth year of a 20-year master plan and already boasts a convention/conference center, an animal contact facility used for both physical therapy and children's education, an equestrian arena used for physical therapy, plus the only white sand beach along the Texas coast.

The new rain forest exhibit, which is currently under construction, is expected to be the complex's most spectacular project to date. It will include displays of a wide variety of tropical flora, exotic fish in fresh water tanks and ponds, a Mayan ruin, a Japanese tea house, a series of waterfalls cascading from a man-made mountain, and a 2D/3D IMAX theater in a companion visitor's center. The entire one-acre exhibit will be housed in a 100'-tall pyramidal glass-and-steel enclosure.

The pyramid shape was selected for its superior structural economy and inherent stiffness under the




120 mph hurricane winds common along the Texas coast. In addition, the pyramid provides sufficient height near the center to accommodate large tropical trees.

Structural engineer Walter P. Moore and Associates, Inc., and architect Morris * Architects, both of Houston, collaborated to effectively blend the efficiency of the pyramidal structure with the stringent functional criteria of the unique exhibit. As the design developed, a third team member, the Houston office of construction manager Gilbane Building Co., provided analyses to confirm the economy and constructability of the structural system.

Analysis And Design

The structural frame consists of steel trusses with welded pipe members and steel tube purlins supporting sloping glass cladding. Pipe sections were used for truss elements and tube sections for purlins to minimize the effective size of all members, thereby allowing the maximum amount of sunlight into the rain forest exhibit. Likewise, welded connections minimized the size of gusset plates, which also reduced shadowing.


To assure a comprehensive analysis, the structure was analyzed



Opposite photo courtesy of Jack Kraft



A center erection tower and four red gin poles supported the ridge trusses during erection. Additionally, the center erection tower supported the apex connection as each quadrant for the pyramid was erected. These supports were removed after all bolted connections were torqued. Pictured on the opposite page is the side truss-to-ridge truss top chord connection. Pipe stubs projecting from ridge trusses simplified connection of side trusses and belt beams. The slip-critical high-strength bolts were torqued prior to final cleaning and painting with a special corrosion resistant white coating. The simplicity of the truss connections helped to speed the erection process. The majority of the 310-ton structure was erected in just 45 days.





with a three-dimensional computer model using the SAP90 program from Computers & Structures, Inc. The following basic load conditions were considered:

- Dead loads including the weight of the steel structure;
- Live loads on the sloping surfaces;
- Wind loads along each orthogonal axis and along the principle diagonal axes;
- A thermal differential of 0 to 140 degree F;
- Lateral bracing forces in the plane of the top chord of the trusses (which are equal to the forces required to provide second order lateral bracing of the chords).

Wind loads from three sources were considered: the 1985 *Standard Building Code* with 140 mph basic wind speed; results of a boundary layer wind tunnel test with 120 mph basic wind speed; and *Building Code for Windstorm Resistant Construction* by the Texas Catastrophe Property Insurance Association. Interestingly, the wind design criteria required by the insurance carrier was the most stringent and hence controlled the majority of the design.

The basic loading conditions generated 35 possible load combinations for analysis. Since the SAP90 post-processor provides only a design check, the engineers developed a customized post-pro-





cessor to retrieve output files from the SAP90 runs and rapidly perform the load combinations. In addition, the post-processor program accomplished three important tasks:

- For each element, it produced a member design to satisfy each load combination;
- For any specific structural steel size specified by the designers, it produced a code design check;
- To develop forces for connection and foundation designs, it produced sets of axial loads, moments, and shears corresponding to load combinations that produced the maximum (or worst) combinations of axial load and moment.

By harnessing the power of the customized post-processor, the designers accurately analyzed the entire structure and designed every element for the 35 load combinations. The result is an efficient and economical structure with a total weight of 310 tons (or 15.5 psf based on the area of the 200' square base). The post-processor also allowed the designers to utilize a range of readily available pipe and tube sizes.

Design Results

The major supporting elements of the superstructure are four primary ridge trusses, each 173' long and 10'-2" deep. The trusses meet at the apex of the pyramid as

shown in Figure 3. The trusses support—and are braced by—26 intersecting side trusses that vary in length from 35' to 106'. The 8'-10" deep side trusses are located at alternate chord panel points along the primary trusses.

Pipe elements ranging from standard 10"-diameter pipes to extra-strong 12"-diameter pipes were specified for the truss top and bottom chords, while 5" diameter pipes in strengths of standard, extra-strong and double extra-strong were used for the diagonal web members. Tube purlins, typically 10" square, span between side truss top chords. The purlin sizes were increased to 12" square to take bracing forces at each of the circumferential bracing belts.

Structural steel fabricator on the project was AISC-member Richmond Steel, while the tubes were supplied by AISC-member Welded Tube Co. of America and the pipes were supplied by Saginaw Pipe Co.

The pyramidal structural system performs efficiently, but with a few peculiarities and special design challenges. With the recent design experience of a major pyramid-shaped roof structure ("The Great American Pyramid, Memphis, TN," see June 1991 *Modern Steel Construction*) as background, the design team was able to anticipate and economically resolve these challenges, the most critical of

YOU'LL BE AMAZED AT WHAT YOU CAN DRAW FROM OUR EXPERIENCE.

CADVisions, in conjunction with Burchfield Detailing, has been a leader in developing CAD solutions for the A/E/C industry since 1989.

Our experience provides you with advanced software and hardware products, service, support and professional training. Our products provide the best CAD solutions for architects, engineers, fabricators and detailers. Our advantages are imperial or metric dimensioning; steel database for AISC, CISC, DIN and BS4 standards; plus much more.

CADVisions is an authorized dealer and training center for Softdesk and is an authorized dealer for AutoCAD®.

- ▲ AdCADD™ Structural Designer Series by Softdesk
 - › The Modeler
 - › Plans & Elevations
 - › Sections & Details
 - › The Steel Detailer
 - ▲ Combined with AutoCAD for a powerful, intuitive solution for A/E/C professionals
- For an experienced vision into structural software technology call on CADVisions today.

2200 North Lamar, Suite 104
Dallas, Texas 75202
214 720-2023, FAX 214 720-0617

CAD VISIONS

IT'S HERE!
A Brand NEW
Publication
For Safe
Construction
Practice in
Steel Floor
and Roof Deck
Installation

STEEL DECK
 INSTITUTE
sdi

SDI MANUAL
 OF CONSTRUCTION
 WITH
 STEEL DECK



**"SDI MANUAL OF
 CONSTRUCTION WITH STEEL DECK"**

is a new and complete guide to safe construction. It covers responsibilities for Design, Specification, Bundling, Loading, Unloading, Hoisting, Placing, Attaching, Placement of Construction Loads. It serves as a safety primer for Contractors, Erectors, Architects, Engineers and Inspectors who are responsible for safe and proper field installation of Steel Deck.

PRACTICAL...
EASY TO READ...
EASY TO FOLLOW...
EASY TO TAKE TO THE JOBSITE...

BRAND NEW - FIRST PRINTING
SDI MANUAL OF CONSTRUCTION
WITH STEEL DECK - No. MC01

Quantity @ \$18.75 each

U.S. Currency Total

Out of Continental U.S. Add 15%

Call SDI for Special Shipping such as
 Express Mail, Air Mail, etc. -additional

TOTAL ENCLOSED

NAME

ADDRESS

CITY

STATE ZIP

ALLOW 3 TO 4 WEEKS FOR DELIVERY



Shown above is the start of the glazing mullion installation at the base of the pyramid.

which are discussed below.

Connection Design

To simplify erection, all field connections were designed with slip-critical bolts in oversized or slotted holes. The typical connection detail at the joint where the side trusses intersect the ridge trusses is shown in Figures 2 and 4.

To streamline mating of the pieces, a pipe stub with circular end plate and two projecting perpendicular gusset plates was shop-welded to the top chord of the ridge truss chord at each joint. The horizontal gusset plate was split in a dovetail to accept a similar set of interlocking gussets on the side truss. The top and bottom connections on each truss were slipped into position simultaneously.

The connections were designed to resist large simultaneous axial loads, bi-axial bending, and shear.

Thermal Behavior

The key structural elements in the pyramid system are the four primary ridge trusses, which are predominantly loaded in axial compression. Each of the four ridge trusses is braced at alternate panel points by smaller side trusses and horizontal tube members acting as belts around the structure (see Figure 1). The horizontal belt mem-

bers are subject to significant axial loads, both in tension and compression.

Near the base of the pyramid, where the belt members are longest and subject to the highest end constraint, the stresses due to temperature extremes are significant. To resolve this concern, the first line of belts above the ground were detailed with releases at one end of each member to allow axial slip movement. To compensate for the loss of lateral stiffness that these slip connections created, a series of 3/4" rod X-braces was added in the plane of the sloping wall (see Figure 1).

Settlement Sensitivity

Any pyramidal structure is inherently sensitive to differential settlement of the supports. Even relatively modest settlement of one truss support may reduce that truss' axial load significantly and increase the loads at the adjacent trusses. The resulting redistribution of forces can overstress other elements. In response, a very stiff system of deep pile foundations was utilized on the Rain Forest Pyramid to limit the maximum expected differential settlements to less than 0.25".

Field connections between the trusses, as well as for purlin-to-truss connections, were detailed

STEEL DECK INSTITUTE

P.O. Box 9506 Canton, Ohio 44711 (216) 493-7886



Pipes and tubes were used to minimize the size of the steel members and therefore maximize the amount of light streaming through the glass walls of the Rain Forest Pyramid at Moody Gardens on Galveston Island, TX.

with high-strength A325 bolts. The purlin-to-truss connections in particular were detailed to minimize joint size, which both simplified erection and reduces sunlight shading.

Construction Issues

Differing support locations and lateral bracing of individual members during erection make adequate erection analysis important for any long-span roof structure. Because the pyramid is so efficient—and hence individual member sizes are relatively small—erection concerns are particularly important. As a result, the designers fully analyzed the structure for each phase of construction with construction loads and temporary erection towers in place. In addition, the erection scheme was fully developed and described on the contract drawings.

The steel erector, Peterson Brothers Steel Erection, Co., followed the specified erection scheme and sequence very closely. A guyed erection tower was placed at the center of the structure to support the top of the ridge trusses. Four secondary gin poles were placed near the mid-span of each of the ridge trusses. Since the ridge trusses were designed as predominantly axially-loaded members, a temporary support near mid-span was necessary to prevent flexural overstresses and reduce deflections due to self-weight prior to completion of all erection and the resultant efficient pyramid behavior.

Several pre-erection meetings were held between the structural engineer, fabricator and construction manager to work out all aspects of steel fabrication, detailing and erection. As a result of the careful planning and detailing of this structure, the erection progressed very smoothly, requiring only 1½ months to install all trusses and the majority of the purlins. Completion of the slip critical bolted connections continued for another month before the erection towers were removed, and deflection at the apex of the pyramid was even less than the ½" expected.

After erection, the structural members and connections were cleaned and painted white with a high quality exterior coating system from DeVoe Coating Co. to prevent corrosion and improve light reflection.

The project is scheduled for completion in Spring, 1993. It successfully blends the economy of structural steel with the efficiency of the pyramid shape to create a graceful structure. Welded steel pipe trusses and tube purlins satisfy all of the architectural and structural requirements, including resisting hurricane winds and minimizing shading.

Ali A.K. Haris, S.E., Ph.D., is a vice president and Ian Robertson, P.E., Ph.D., is an associate with Walter P. Moore and Associates, Inc., a leading structural and civil engineering firm headquartered in Houston. ■

Joist in Time!

The new SJI 1992 catalogue for steel joists and joist girders is here.



It's bigger and better than ever before, making it even easier to specify and use steel joists and joist girders.

All 1992 revisions are listed in front so changes can be reviewed quickly and easily. And the section on fire-resistive assemblies has been expanded and completely revised. It now lists criteria for using K-Series Joists in an assembly and includes a simple, five-step procedure for selecting the proper and most economical joist. In addition, the catalogue lists over 70 floor and roof assemblies, with specific UL designations. You'll find specs for the welding of Longspan Joists, Deep Longspan Joists, Joist Girders and much, much more.

Order yours today. It's Joist what you needed.

1992 EDITION!

Standard Specifications, Load Tables and Weight Tables for Steel Joists and Joist Girders. \$10.00 per copy.

Number of copies: _____

VIDEO SEMINAR AVAILABLE.



This 28-minute learning tool shows how to specify the right steel joist for each job, quickly and correctly. \$34.95 charge includes all shipping.

Managing Director
Steel Joist Institute
Division A-1
1205 48th Avenue North
Myrtle Beach, SC 29577



Total enclosed _____
Payment includes first class postage and handling and must accompany order.

Name _____

Firm _____

Address _____

City _____

State _____ Zip _____



Spray-Applied Fireproofing

Blaze-Shield II is the latest offering in Isolatek International's line of spray-applied fireproofing. The pneumatically-applied product offers quick-and-easy on-site application with a minimal amount of water, which translates into a fast drying time. Plus, this latest introduction features a higher density and greater bond and compression strengths than earlier products. The fireproofing material adapts to any contour and can be applied to hard-to-reach places without the need for scaffolding. Required thickness for a four hour rating on floor/ceilings, beams, bar joists, columns and roof/ceiling constructions can be reached in just one application pass.

For more information, contact: Isolatek International, 41 Furnace St., Stanhope, NJ 07874 (201) 347-1200; FAX (201) 347-9170.

Cementitious Fireproofing

Monokote cementitious fireproofing from Grace Construction Products is ideal for interior and exterior structural steel. The product is spray-applied but bonds tenaciously—even in 2,000 degree F. fires. A wide range of formulations are available for specific applications—interior; heavy traffic and high humidity; high impact; acoustical plaster; and over polystyrene and urethane foam for freezers and cold rooms.

Contact: Becky DeWitt, Grace Construction Products, 62 Whittemore Ave., Cambridge, MA 02140 (617) 876-1400.

Architectural Fireproofing

A new low-density, cementitious fireproofing material, Pyrolite 1, has been introduced to the architectural market by the Fireproofing Division of Carbolite Company. The spray-applied material is ideal for a wide variety of applications, including office buildings, parking garages, abatement respray, airport terminals, pharmaceutical plants, shopping centers and warehouses. The material is 80% lighter than concrete, which reduces structural loading while still providing up to four hours of rated fire protection on columns and beams and two hours on deck assemblies. The single-package product is mixed with water on the job site and is asbestos-free and chloride-free.

For more information, contact: Mitch Braun, Marketing Services Manager, Carbolite Co., 350 Hanley Industrial Court, St. Louis, MO 63144 (314) 644-1100; FAX (314) 644-4617.

Joint Sealant

Pensil 300 Firestop Joint Sealant from GE Silicones is a one-part, neutral-cure sealant for joints that have high movement and require fire ratings in accordance with UL 1479 and ASTM E814. The system is designed to help limit the spread of flame, smoke, toxic fumes and water during fires.

Contact: GE Silicones, Inquiry Handling Service—PR#CONST-06-91, P.O. Box 330, Poestenkill, NY 12140.

Intumescent Coatings

A wide range of fireproofing materials are available from Textron Specialty Materials. The Chartek family of intumescent epoxy fireproofing materials are easily applied and offer long-lasting corrosion protection as well as fire protection. Chartek 59 was the first fireproofing coating material in the industry to achieve UL listing

for exterior use. Coroc II Panels are designed as an alternative to concrete for steel protection on industrial applications and are specially rated for rapid temperature rises.

For more information, contact: Lisa Seidel, Sales & Marketing Coordinator, Fire Protection Systems, Textron Specialty Materials, 2 Industrial Ave., Lowell, MA 01851 (508) 452-8961; (508) 454-5619.

STEMFIRE

STEMFIRE determines safe and economical fire protection for steel beams, columns, and trusses. STEMFIRE is based on rational procedures developed by AISI which extend the published UL fire resistive designs to other possible rolled structural shapes and common protection material requirements. For a required fire rating, STEMFIRE determines the minimum spray-on thickness for various rolled shapes as well as the ceiling membrane or envelope protection for trusses. This methodology is recognized by UL and has been adopted by the three national model building codes in the USA.

The software database contains all pertinent steel shapes and many listed UL Fire Resistance Directory construction details and fire ratings. In this manner, user search time is minimized and the design and checking of steel fire protection is optimized. Hence, STEMFIRE is easy to use with little input effort to quickly produce specific design recommendations. Two 5 1/4" disks containing executable software bearing AISC copyright and a users manual with instructions and sample problems are included with purchase.

Available on 5 1/4" disk only. \$96.00

AISC also offers the following programs:

CONXPRT - Shear and moment connection design software

AISC Database - Part 1 of the AISC Manual of Steel Construction in electronic database form

AISC for AutoCAD - Part 1 of the AISC Manual of Steel Construction for AutoCAD

WEBOPEN - Software to design beams with web openings

Call AISC Software, (312) 670-2400

09777

Custom-Designed Steel Joists from Canam Steel Play Supporting Role in Unique Structures.

Pyramid Arena uses steel joists in structural frame.

Recreating the ancient design of the Pyramids is a monumental engineering and construction feat. The architecture of the new Pyramid Arena in Memphis, Tenn., called for new materials and methods.

Canam Steel was the joist manufacturer willing and able to tackle a difficult and specialized project.

Bar joists were utilized on the sloped sidewalls as the supporting element for the exterior skin system. Since the bar joists were an integral part of the horizontal bracing design, there were unusual requirements for the joist design, including the joist bridging.

The Pyramid Arena is an awe-inspiring tribute to teamwork and modern technology. Canam Steel is proud to have served the builders and fabricators of this new wonder of Western civilization.



PYRAMID ARENA
Consulting Engineer: Walter P. Moore & Associates; General Contractor: Huber, Hunt & Nichols, Inc.; Steel Fabricator: Havens Steel; Erector: Barnhart Construction Co.



WICHITA CITATION SERVICE CENTER
Engineers/Architects: Rossi, McCreery & Associates, Inc.; General Contractor: Martin K. Eby Construction Co., Inc.; Steel Fabricator: PKM Steel Services, Inc.; Erector: Foster Erection

215 ft. long joists produced for Cessna Aircraft.

The Cessna Aircraft Company's new Citation Service Center in Wichita, Kan., is off to a flying start with some of the longest joists ever produced by any joist company.

"Pushing the envelope" at over 9 feet deep and 215 feet long, these double pitched deep-longspans were shipped and erected in halves using perfect-fit bolted splices. For this project, nearly 800 tons of standard K-Series, LH-Series and DLH-Series joists were required.

Canam Steel's engineering and production capabilities allow us to handle a wide array of requirements. Whether your project is large or small, straight forward or special, we are a joist company who consistently performs.

So, review the past, then look to the future. You'll discover why Canam is the joist supplier of choice.



canam steel
corporation

Open Web Joists-Longspan Joists-Deep Longspan Joists-Trusses-Girders

Plants: Lafayette, IN (317) 477-7764-Washington, MO (314) 239-6716-Point of Rocks, MD (301) 874-5141

Sales Offices: Bolingbrook, IL (708) 759-7800-Parma, OH (216) 888-4922-Memphis, TN (901) 763-0266-Flint, MI (313) 230-8090-Delano, MN (612) 972-6135-Needham Heights, MA (617) 444-5504-Towson, MD (301) 494-1400-Findley Lake, NY (716) 769-7121-Virginia Beach, VA (804) 479-1828-Chambersburg, PA (717) 263-7432-Centerville, VA (703) 803-9371

For
ENGINEERS

A/E/C SYSTEMS® '92

The world's largest computer and management show
for the design and construction industry
Conference June 8-11 ■ Exhibit June 9-11 ■ Dallas, Texas USA

Create better projects, maximize productivity, and sharpen your management effectiveness.

See, touch and compare the hottest hardware, software, peripherals and supplies for every application at the annual event where design and construction professionals make their best computer connections.

A/E/C SYSTEMS '92 is *the* technology connection for today's computer-sophisticated architects, engineers, contractors, facilities managers, GIS professionals, and others in the design and construction industry. The comprehensive exposition is actually a host of related exhibits of interest to the entire project team, happening simultaneously.

In application areas, special-interest users can zero in on pro-

ducts primarily for design, construction, computer-assisted specifying, facilities management, reprographics, or GIS, while neighborhoods sponsored by Autodesk and Intergraph display linkable systems from many developers in a one-stop shopping environment.

Each exhibit stands alone, but all relate closely, and attendees have full crossover privileges to every area of the show. If you want to see it, it will be at A/E/C SYSTEMS '92.

Connect with the best computer minds at conferences that teach you how to find better solutions to clients' problems ... design & build quality facilities at lower cost ... operate the built environment more efficiently.

Looking at the latest technology is good, but learning how to use it for maximum benefit to your firm and your clients is even better. That's what the 1992 conference program is all about.

More than 100 sessions ranging in length from 60 minutes to 3 days are scheduled between June 8 and 11 including:

- Managing Your Engineering CADD System
- Managing CADD/CAE in the Multi-disciplined, Multi-officed Firm
- Computer-integrated Design: The Real Payoff

Our conferences don't waste your time with circuit lecturers or vendor pitches. Get it straight from fellow users at A/E/C SYSTEMS '92 ... where design and construction professionals make the best computer connections.

A/E/C SYSTEMS '92

Phone 1-800-451-1196
or 1-203-666-6097

or fax this form to
1-203-666-4782

or mail this form to
A/E/C SYSTEMS '92
PO Box 310318
Newington, CT 06131-0318

Phone, fax, or write for complete information...fast!
Print or type clearly—or just tape your business card below.

E5

Name _____

Title _____

Company Name _____

Mailing Address _____

City, State, ZIP Code _____

Connect me with A/E/C SYSTEMS '92! Send the following right away: 32-page conference catalog

09778

6th Annual National Steel Construction Conference

June 3-5

Developments in
Painting Structural Steel

More than 100
Exhibitors

Practical Solutions
for Connection Problems

Integrating Design,
Detailing and Production
Systems

O'Hare's New
International
Terminal

Short Span Steel Bridges

High-Rise Steel
Frames

Designing Heat
Straightening Repairs

Economical Welded
Structures

Repairing
and Retrofitting
Buildings and Bridges

Designing with
Tube Steel

1992 T.R. Higgins Lecture

Solving the Steel
Parking Deck
Dilemma

Exhibitor Workshops

Building Code
Updates

Improving your shop safety

45 seminars & workshops

And much, much, more!!!




EXHIBIT BOOTHS STILL AVAILABLE

For more information contact: David Wiley,
American Institute of Steel Construction, Inc.,
One East Wacker Dr., Suite 3100, Chicago, IL 60601-2001;
Phone 312/670-5422; FAX 312/670-5403

L S
VEGAS

STATE OF THE ART

INTEGRATED ANALYSIS AND DESIGN
SOFTWARE FOR STRUCTURAL &
EARTHQUAKE ENGINEERING

Developed by Edward L. Wilson
& Ashraf Habibullah



For further information:

Computers & Structures Inc.
1995 University Avenue
Berkeley, California 94704

TEL: 510/845-2177
FAX: 510/845-4096

ETABS is a registered trademark of CSI.
SAP90 & SAFE are trademarks of CSI.