


MODERN STEEL CONSTRUCTION

October 1994


\$3.00



The
work of
Eli
Cohen



In the past it was
necessary to show
special loadings,
such as this
example, on the
structural
drawings and call
for a special (SP)



maximum moment = 243 k. inch
maximum shear = 3588 lbs.

joist. Now, tables for new KCS joists can be used to find a joist with sufficient moment and shear values. The new KCS joists have constant moment and shear strengths -- in the case of the illustrated example a 16KCS2 joist is found to resist a moment of 349 inch kips and a shear of 4000 pounds. By specifying this joist it is no longer necessary to call for a SP joist or show the diagram.

In addition to the tables on the new K Series KCS joists the new SJI specification contains other important revisions:


1. New bridging requirements for K, LH, and DLH joists.
2. Metric load tables.
3. Revised joist girder bearing seat depths.

The latest SJI information is now available.



NICHOLAS J. BOURAS, INC.
Executive Offices, Engineering and Sales
475 Springfield Ave., Summit, NJ 07902-0662
(908) 277-1617


Please circle # 33



ARBED *Tailor-Made* *Beams speed repairs of* *nation's oldest steel bridge.*

Gateway Western Railway's bridge at
 Glasgow, MO. after the flood of July 1993.

60 days after award; thanks to 140 tons of
 ARBED W44 x 335 Tailor-Made Beams.



Constr. Mgr.: Design Nine, Inc. St. Louis, MO.
 Photography : Dale Graham, Fayette, MO.

Fabricator : Phoenix Steel, Inc., Eau Claire, WI.
 Erector : St. Louis Bridge Co., Arnold, MO.

Consulting Engineers: Modjeski & Masters, New Orleans, LA.

Steel supplier: 140 tons of ARBED W44x16x335 rolled WTM (Tailor-Made) beams in ASTM A572/Gr50,
 from the TradeARBED stock in Blytheville, AR.

When you need Big Beams, Service and Quality; The name is **ARBED**.

WTM (Tailor-Made) rolled beams are available in 24" through 44" and from 129 lbs/ft through 798 lbs/ft; in ASTM A36, A572, A709 with most sections available in ARBED's new **HISTAR®** Grade 65 (ASTM A913). Sectional properties are available on a free floppy disc (Lotus 1-2-3, Quattro Pro and ASCII versions for IBM, Excel for Macintosh) and the complete ARBED database is ready to use in the design softwares GTSTRUDL, ETABS, SAP90 and STAAD-III.

HISTAR® is a registered trade-mark of ARBED

**For complete information, availability, literature and floppy disc,
 contact one of our TradeARBED offices at the following locations:**


- 825 Third Ave., New York, NY 10022. (212) 486-9890, Fax (212) 355-2159.
- 60 E. Sir Francis Drake Blvd., Suite 202, Larkspur, CA 94939 (415) 925-0100, Fax (415) 461-1624 / 8257.
- 390 Brant Street, Suite 300, Burlington, Ontario, Canada L7R 4J4. (905) 634-1400, Fax (905) 634-3536.

Please circle # 35

MODERN STEEL CONSTRUCTION

Volume 34, Number 10

October 1994



Eli Cohen is Chicago's foremost practitioner of structural engineering today. It's hard to walk along any downtown street in Chicago without seeing one of his numerous projects.

Modern Steel Construction (Volume 34, Number 10). ISSN 0026-8445. Published monthly by the American Institute of Steel Construction, Inc., (AISC), One East Wacker Dr., Suite 3100, Chicago, IL 60601-2001.

Advertising office: The Ramage Group, O'Hare Lake Office Plaza, 2400 E. Devon Ave., Des Plaines, IL 60018 (708) 699-6049.

Subscription price:
Within the U.S.—single issues \$3;
3 years \$85.
Outside the U.S.—single issues \$5;
1 year \$36; 3 years \$100.

Postmaster: Please send address changes to Modern Steel Construction, One East Wacker Dr., Suite 3100, Chicago, IL 60601-2001.

Second class postage paid at Chicago, IL and at additional mailing offices.

FEATURES


- 22 DESIGNING BUILDINGS THAT WORK**
Developers and architects appreciate Eli Cohen's ability to design economical—and functional—buildings
- 32 THE LRFD (R)EVOLUTION**
In addition to providing more uniform reliability, analysis shows LRFD can save an average of 5% of total steel tonnage on mid- and high-rise buildings
- 1994 T.R. Higgins Lecture*
- 36 COMPOSITE FRAME CONSTRUCTION**
In high-rise building design, the synergism between steel and concrete allows for rapid construction at a lower cost

DEPARTMENTS

- | | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 6 EDITORIAL | 18 STEEL NEWS <ul style="list-style-type: none">•Two New LRFD Textbooks•Quick Steel Survey•Geerhard Haaijer•Upcoming Events |
| 9 STEEL INTERCHANGE <ul style="list-style-type: none">•Creating Composite Action By Adding Studs•Weep Holes And Tubular Columns•Erecting Steel Beams On A Brick Wall•Deflection Limits For Crane Runway Systems | 48 COMPUTER PRODUCT PERIPHERALS |
| | 50 STEEL MARKETPLACE |
| | 50 AD INDEX |
| 13 STEEL COUNSEL <ul style="list-style-type: none">•Avoiding Professional Liability Traps | |

It's tomorrow ...

in Computerized Structural Engineering



Experience STAAD - III

"Concurrent Engineering" on DOS/Windows/Unix/NT

Welcome to tomorrow in Computerized Structural Engineering. The latest release of STAAD-III, based on the principles of "Concurrent Engineering", is redefining the way you engineer your structure. Whether you are on DOS, WINDOW, UNIX, or NT, STAAD-III is guaranteed to enhance the performance and productivity to a whole new level.

STAAD-III, from Research Engineers, is an acknowledged world leader in structural software. State-of-the-art Static/Dynamic/Nonlinear analysis, innovative finite element techniques, comprehensive Steel/Concrete/Timber design, powerful graphics and seamless CAD integration have always been our forte. Our deep rooted R & D base, spread over four continents, and our association with the world's leading institutions, have resulted in a solid technological foundation for STAAD-III.

Today's STAAD-III, brings you the latest in modern Computer Aided Engineering. Based on the principles of "concurrent engineering", it unifies leading-edge graphics and visualization techniques with proven and time tested analysis/design. A live and unified associative data base provides seamless integration across all mission critical applications, from concept design and analysis to detail design, simulation and visualizations. Today's STAAD-III - a productivity concept for tomorrow.

With over 10,000 installations, more than 30,000 engineers worldwide rely on STAAD-III for the state-of-the-art in technology.

Experience tomorrow today - experience STAAD-III



Research Engineers, Inc.

22700 Savi Ranch Pkwy., Yorba Linda, CA 92687

Tel: (714) 974-2500 Fax: (714) 974-4771 Toll Free: (800) FOR-RESE

• USA • UK • GERMANY • FRANCE • CANADA • JAPAN • KOREA • NORWAY • TAIWAN • INDIA

Please circle # 34

Editorial Staff

Scott Melnick,
Editor and Publisher
Patrick M. Newman, P.E.
Senior Technical Advisor
Charlie Carter,
Senior Technical Advisor
Jacques Cattani,
Technical Advisor

Editorial Offices

Modern Steel Construction
One East Wacker Dr.,
Suite 3100
Chicago, IL 60601-2001
(312) 670-5407
Fax 312/670-5403

Advertising Sales

The Ramage Group
O'Hare Lake Office Plaza
2400 E. Devon Ave.
Des Plaines, IL 60018
(708) 699-6049
Fax 708/699-6031

AISC Officers

Frank B. Wylie, III,
Chairman
Robert E. Owen,
First Vice Chairman
H. Louis Gurthet,
Second Vice Chairman
Robert D. Freeland,
Treasurer
Neil W. Zundel,
President
David Ratterman,
Secretary &
General Counsel
Geerhard Haaijer,
Vice President,
Technology & Research
Morris Caminer,
Vice President,
Finance/Administration

GEERHARD HAAIJER

Tragedy recently befell the steel industry—and the entire structural engineering community—with the loss of Geerhard (Jerry) Haaijer. For the past 11 years, Jerry was AISC's Vice President of Technology and Research and a driving force in many of the progressive design changes occurring in the fabricated structural steel industry.

Before that, he spent 27 years with U.S. Steel's Research Laboratory, including 17 as chief of the Design Technology Division. He also served an adjunct professor at Carnegie-Mellon University in Pittsburgh. His many papers included such topics as autostress bridge design, plastic design theory, and hybrid girder design.

While Jerry will be remembered and honored for his many professional accomplishments, he will also be missed for his remarkable personality. Like a favorite uncle, he would illustrate a point with a story. And like a great teacher, he could take even the most complicated subjects and explain them so clearly that even the poorest student understood. Often, when I had problems understanding one topic or another that I was writing about, I found myself in Jerry's office. Sometimes just a few words would suffice. But more often, he'd put pen to paper and draw me a clear and concise answer. In the five-and-a-half years I was privileged to have known and worked with Jerry, I came to respect not only his brilliance, but also his ability to remain unflappable despite the turmoil around him. Even more impressively, he was able to extend that calmness to others. No one was better at diffusing a tense meeting or situation.

He was also remarkable for how much effort he was willing to make to help others no matter how busy he was with his own work. If a few of us were discussing something at lunch, it was not unusual for Jerry to drop by my office a couple of days later with a copy of a paper he had dug out of his huge files that he thought might be helpful. And many in the industry will be forever grateful for his mentoring skills. Jerry's legacy won't just be his own accomplishments, but also the accomplishments of his many students and others to whom he gave a professional boost.

A memorial scholarship fund has been established in Jerry's name at Lehigh University. Contributions can be sent to: The Geerhard Haaijer Memorial Scholarship Fund, Lehigh University, 207 Memorial Dr. West, Bethlehem, PA 18010. **SM**

How to get from here



Estimating Module



Engineering, Analysis
and Design Module



Detailing Module



Production Control
Module



CNC Interface
Module

to here.



Design Data's SDS/2 Steel Fabrication System.

SDS/2 gives you the flexibility to integrate all aspects of your business with one software system. That concept is called Information Management. Each module by itself will save you time and money and by combining products to implement Information Management you receive more than twice the benefit in savings and productivity. So whether you need one SDS/2 software module or all these tools working together, Design Data can provide the most productive system for you.

For more information about SDS/2, information management in the steel industry or future product demonstrations call **800-443-0782**.

Please circle # 32

**DESIGN
DATA** 

"First in...software, solutions, service"
402-476-8278 or 1-800-443-0782

© 1992 Design Data Corporation

LRFD ON CD.



LRFD on CD is more than just the entire two-volume, 2,000-page LRFD Manual of Steel Construction, 2nd Edition, on a compact disk.

This electronic manual makes extensive use of the latest hypertext technology to automatically link related sections of the manual together. Click on "connections" in one part of the manual and quickly and easily find other sections dealing with that same topic. Or click on any of the more than one thousand items that are electronically cross-referenced throughout the manual. The Manual includes a 45-page introduction to LRFD electronically linked to the Specification and Commentary.

The CD also includes:

- Complete copies of every issue of Engineering Journal published in 1992 & 1993
- Nearly 100 drawings (.dxf files) taken right from the manual that can be quickly copied to your AutoCAD or other CAD program

And best of all, LRFD on CD follows the exact format, page-by-page, as the Manual. If you're looking at nominal strength parameters on page 6-115 of the Manual, the identical page is reproduced on the CD.

LRFD on CD is available for \$1,000 (or \$750 for AISC members).

To order or for more information:

Phone: 312-670-2400 or Information Fax Line: 800-644-2400


STEEL INTERCHANGE

Steel Interchange is an open forum for *Modern Steel Construction* readers to exchange useful and practical professional ideas and information on all phases of steel building and bridge construction. Opinions and suggestions are welcome on any subject covered in this magazine. If you have a question or problem that your fellow readers might help you to solve, please forward it to *Modern Steel Construction*. At the same time, feel free to respond to any of the questions that you have read here. Please send them to:

Steel Interchange
Modern Steel Construction
One East Wacker Dr., Suite 3100
Chicago, IL 60601-2001

The following responses from previous Steel Interchange columns have been received:

Can an existing steel beam and concrete slab be made to work together in composite action by adding studs to the steel through cored holes? Are there any special considerations?



M_D = Dead Load Moment

M_L = Live Load Moment

Net Moment = $M_D + D_L - T \times e$

For Crack Control, $M_D \leq T \times e$

It is presumed that the intent here is to enhance the capacity of an existing beam. One option that does not involve composite action is presented in the figure.

A steel cable can be installed to create negative moment in the center of the beam to counteract the positive moment from the gravity loads. The tension in the cable can be developed to counteract the dead load moment. Needless to say, $T \times e$ should not exceed M_D since that may render the concrete

Answers and/or questions should be typewritten and double-spaced. Submittals that have been prepared by word-processing are appreciated on computer diskette (either as a Wordperfect file or in ASCII format).

The opinions expressed in *Steel Interchange* do not necessarily represent an official position of the American Institute of Steel Construction, Inc. and have not been reviewed. It is recognized that the design of structures is within the scope and expertise of a competent licensed structural engineer, architect or other licensed professional for the application of principals to a particular structure.

Information on ordering AISC publications mentioned in this article can be obtained by calling AISC at 312/670-2400 ext. 433.

slab susceptible to cracking.
Vijay P. Khasat, P.E.

In a structure that has tubular columns, should weep holes be added at the bottom of the columns in order to drain any water in the column?

Tubular columns which are exposed to the weather, or to temperature change which can cause interior condensation, should have weep holes even if the columns are capped. Water can also enter a column through the ends of slots which are not totally covered by washer.

The consequences of water entering a tubular column are that the column may freeze and burst, or may be subject to hidden corrosion.

If, however, a column is protected from the elements and is not subject to drastic changes of temperature, or an overly humid environment, weep holes may not be necessary. Some engineering judgement is required.

David T. Ricker, P.E.
Payson, AZ

When erecting steel beams on a brick wall, could the non-shrink grout be omitted under a proper bearing plate, if the surface of the brick is smooth, clean of any and all debris and leveled?

In practice, we do not believe the omission of grout under a potentially rough bearing surface (or even a smooth surface) is wise since: (a) unanticipated or unaccounted for torsional strain and translation can result if the bearing surface plane is not normal to the loading plane; (b) the bearing surface and bearing plate (or flange) will have zones of excessive stress if the loading not uniform; (c) a failure can result in one or more of the mechanisms involved in the transfer of load from one member to another since the model calcu-

STEEL INTERCHANGE

lations might not match the real loading and boundary conditions. These considerations are amplified when the base surface is non-uniform as in the case of masonry construction (brick or c.m.u.). Without the use of a grouted leveling bed, the edge of the base will also be loaded which can result in a premature shear/tension failure at the edge (popping of the corner). As such, we set back the grouted leveling bed and the bearing plate $\frac{1}{2}$ inch to minimize this potential failure mode. We specify shrinkage-compensating (the term, "non-shrink grout" is a misnomer) grout in the 5 to 10 ksi ultimate compression strength range as determined by ASTM C1019 depending on the bearing stresses with a minimum thickness of $\frac{1}{2}$ inch.

Stephen K. Crockett, P.E.

David M. Berg Associates, Inc.
Needham, MA

Serviceability is a particular concern for crane systems in industrial buildings but is not clearly covered in the standard code literature. What are deflection limits for crane runway systems?

The following national publications deal expressly with the design concerns of all types of hoisting equipment. Serviceability and deflection limits are treated in great detail in these documents:

- American National Standards Institute B30.XX series of standards.
- Crane Manufacturers Association of America Specifications 70 and 71.

Joe S. Garcia, P.E.
Santa Fe, NM

New Questions

Listed below are questions that we would like the readers to answer or discuss.

If you have an answer or suggestion please send it to the Steel Interchange Editor, Modern Steel Construction, One East Wacker Dr., Suite 3100, Chicago, IL 60601-2001.

Questions and responses will be printed in future editions of Steel Interchange. Also, if you have a question or problem that readers might help solve, send these to the Steel Interchange Editor.

The AISC Manual indicates that design strengths tabulated for clevises and turn-

buckles are calculated using $\phi = 0.3$ in LRFD (or a factor of safety of 5 in ASD). The Manual indicates that this conservative reduction is used because these devices are most often used for temporary rigging which may be subjected to dynamic and impact loading. When these devices are used in permanent applications and not subject to these considerations, e.g., as part of the permanent bracing system, is it justified to use a ϕ of 0.5 in LRFD (or a factor of safety of 3 in ASD)?

What is the most efficient way to enlarge an existing footing, when new loading conditions are applied?

Jake Roth
Roth Metal Works, Inc.
Brooklyn, NY

The bending resistance for square and rectangular sections is doubled when bent about the edge instead of the neutral axis. When is it appropriate to use bending across the edge of the section?

Don A. Finney
Mason & Hanger - Silas Mason Co., Inc.
Amarillo, TX

In addition to the requirement of Section B5, the laterally unsupported length L_b of a box member is based on the ratio M_1 / M_2 . What value of M_1 / M_2 should be used in the case of a simply supported beam, where $M_1 / M_2 = 0/0$, which is mathematically undefined? Note that similar situations occur in the equations for bending coefficients C_b and C_m in the bending and combined axial and bending equations, except that statements are made in the text that cover the case of a simply supported beam.

George R. Lang, Jr., P.E.
Mobil Producing Nigeria, Ultd.
Morgan City, LA

In what instances, if any, and under what criteria can the attachment of grating with mechanical fasteners be used to provide lateral bracing to the compression flange of the members supporting the grating in applications such as walkways and catwalks?

Curt E. Mauler
Wilson & Co.
Wichita, KS

Join The Wasser Revolution!

Stop using 2-part epoxies, 2-part urethanes and inorganic zincs. After 40 years, it's time to move to a coating system that's far better. Wasser has revolutionized the industry. **Join Us!**

BRIDGES AND LEAD OVERCOAT



ASTORIA BRIDGE, OREGON COAST - Hundreds of bridge projects in environments like Oregon's coast, prove Wasser outperforms all other coatings.

WATER AND WASTEWATER



NORTH POLE ALASKA - Painting continues on these sludge beds, while standing in snow. Wasser outperforms epoxy coatings on these demanding projects.

1. Industry's **BEST Corrosion Resistance**
2. **Single Component.**
3. **No Application Restrictions for Humidity, Dewpoint or Temperature (20°F)**
4. **World's Largest Producer of Single Component Moisture Cure Urethanes.**
5. **North America's Largest Manufacturer of Micaceous Iron Oxide Coatings.**

UTILITIES, DAMS AND LOCKS



PRIEST RAPIDS DAM, COLUMBIA RIVER - Wasser has been chosen for their superior performance by agencies throughout the world.

PULP AND PAPER



CHIP CRANE, ROSEBURG LUMBER - Wasser Coatings allow perfect results in outdoor winter painting or indoor painting on paper machinery, for virtually every paper company. Imagine, immersion after only minutes, and superior performance.

WASSER

HIGH-TECH COATINGS

FOR FREE VIDEOS

Call 800-MC-PAYNT

For Information About Wasser
Circle Reader Response #50

Wasser, the Leader of the Coating Revolution!

Wasser Coatings Aren't Just Better...They're A Lot Better Look What Experts Are Saying....

"Wasser's system outperformed every high performance coating system even when applied on poorly prepared surfaces. It has solved our state's bridge painting problems."

• **State Highway Report**

"This is Alaska paint. It would be crazy to use anything else but Wasser in this environment."

• **Alaska Coating Inspector**

"Our tank painting project was delayed for months because of the humidity. With Wasser, we finished in three days."


• **Hawaiian Contractor**

"We can't say enough about the MC-Tar. It saved our tail on our clarifier tanks. We would still be painting with the epoxy."

• **Paper Mill Engineer**

"We are very pleased with Wasser for lead overcoating. Everyone is calling it 'steel on steel'. Wasser solved our overcoat problems."

• **Highway Official**



TACOMA NARROWS BRIDGE, Washington's largest bridge. Wasser's coatings are being used on a five year contract to overcoat the old lead coating. Every controlled test shows Wasser's coatings best for lead overcoating and full painting. Over 400 bridge projects make Wasser the industry leader.

"We used the ice as scaffolding in 22' tide and painted down to within four inches of low tide. Four years later, the coating is still perfect on these pilings."

• **Alaska Contractor**

"We coated the interior areas in 99% humidity and the performance is perfect after five years. We'll never use anything else."

• **Army Corps Locks**

"If it wasn't for Wasser, we would still be out there trying to get that darn inorganic zinc to work."

• **Bridge Engineer**

"Wasser is the answer to all our field painting problems. We'll never use epoxy again."

• **Waste Water Engineer**

"Wasser beat every other coating in our tests, and contractors love them."

• **Paper Mill Engineer**

WASSER
HIGH • TECH COATINGS

Call 800-MC-PAYNT

The Best Coatings in the Industry are also the Easiest to Apply!

CIRCLE #50 ON SERVICE CARD

World Leader in
Single-Component,
Moisture-Cure
Urethane

We designed our mill with the same convenience in mind.

When you're in the market for steel, and you need it fast, you know there's nothing convenient about waiting for a rolling schedule. Maybe it's time you switched from a rolling mill to a stocking mill: Chaparral.

Our \$50-million on-site steel inventory is one of the largest in the world. It's so large, in fact, that we can fill over 80% of our steel orders from stock — in two weeks or less. Special orders? Fast track jobs? We'll process those within

72 hours. Even if your order changes, we'll work with you to fill it as quickly as possible.

So what are you waiting for? Next time you're shopping for steel, call Chaparral. You'll always get the right steel...right away.



**CHAPARRAL
STEEL**

Toll Free (800) 527-7979 U.S. and Canada • Local (214) 775-8241
Fax (214) 775-6120 • 300 Ward Road, Midlothian, Texas 76065-9651

Accurate Steel Costs

Bay Sizes from
20 x 20 ft to 40 x
40 ft in 5 ft incre-
ments

Preliminary Composite Beam Design Data *****
2" MT. DW. + 3" WNC; LRFD; BOCA; LL = 80 PSF *****
Date: 06/08/93 @ 08:54 PM *****

Beam: 20' X 20' Bay - 20' Beam - LRFD
Span = 20.0 Ft.

Beam Location: (X)Center ()Edge
Rib Orientation: (X)Perpendicular ()Parallel

LOADING DATA:

	DL	SDL	SLI	SL	TL	AREA	WRED
Area (sqft) (w=10.0 ft)	56.00	30.00	80.00				
w (k/ft)	.56	.30	.80	.80	1.10	1.66	

al Shear (Kips)	5.60	3.00	8.00	8.00	11.00	16.60	
al Moment (ft-k)	28.00	15.00	40.00	40.00	55.00	83.00	

LRFD Factored Loads

al Shear (Kips)	6.72	4.80	12.80	12.80	17.60	24.32	
al Moment (ft-k)	33.60	24.00	64.00	64.00	88.00	121.60	

DESIGN ALTERNATIVES:

Shape	Studs (in)	Shear	Camb	Fy	k	Com	Max Perform.	Ratio	<< Defl (in) >>			<<< Cost (\$) >>>		
									DL	SL	TL	Std	Std	Camb
W12X19	8	.00	50	25	.94	TL Defl	.53	.41	.94	66	12	0	78	
W12X16	16	.00	36	99	.97	TL Defl	.67	.30	.97	54	24	0	78	
W12X16	18	.00	36	100	.97	TL Defl	.67	.30	.97	54	27	0	81	
W12X19	12	.00	36	62	.94	TL Mom	.53	.30	.84	64	18	0	82	
W14X22	6	.00	36	25	.97	TL Mom	.35	.29	.64	75	9	0	84	
W12X16	20	.00	50	89	.99	TL Defl	.67	.31	.99	56	30	0	86	
W12X22	8	.00	36	36	.96	TL Mom	.45	.31	.76	75	12	0	87	
W12X22	8	.00	50	25	.80	TL Defl	.45	.35	.80	77	12	0	89	
W14X22	8	.00	50	25	.70	TL Mom	.35	.29	.64	77	12	0	89	
W16X26	0	.00	50	0	.73	TL Mom	.23	.45	.68	91	0	0	91	
W12X19	12	.00	0	0	.84	TL Defl	.28	.56	.84	92				
W12X19	12	.00	100	0	.97					97				
W12X19	12	.00	54	0	.98					94				
W12X19	12	.00	100	0	.82					79				
W12X19	12	.00	38	0	.98					98				
W12X19	12	.00	25	0	.88					64				
W12X19	12	.00	35	0	.76					44				
W12X19	12	.00	25	0	.81					53				
W12X19	12	.00	0	0	.95					71	102	0	103	
W12X19	12	.00	0	0	.92					82	88	15	103	

Fully docu-
mented with
live load
reductions

20
designs
with num-
ber of
studs,
inches of
camber
and steel
grade for
each case

Dead, live
and total
load
deflection
conve-
niently
displayed

Designs in
order of least
relative cost

Increased competition for projects is forcing engineers to more carefully consider the differences in constructed costs between steel and concrete structures. Furthermore, today's low cost steel bay designs result from the optimum balance of steel costs, shear stud costs and cambering costs. Thus the least steel-weight design may no longer be the least cost design.

To help engineers make accurate cost analyses, AISC Marketing has introduced a new design tool that is based upon today's cost information for steel and composite bay designs. The **Parametric Bay Studies** program is a database that provides relative cost information on more than 2,400 composite beam and girder designs on one IBM-compatible 3.5-inch diskette. The **Parametric Bay Studies** program allows the design engineer to quickly analyze a wide range of bay alternatives based on bay size, composite and non-composite construction, AISC specification (LRFD or ASD), model codes (BOCA, UBC, SBC), and deck profiles to determine the least cost configuration.

After design parameters are selected, the program provides the designer with 20 design alternatives from which to choose the most cost effective framing. This is an invaluable tool for quickly and accurately estimating the cost of a steel-framed bay early in the design stage.

Only \$50

To order or for more information:

Phone: 312-670-2400

Information Fax Line: 800-644-2400

American Institute of Steel Construction
One East Wacker Drive, Suite 3100



Please circle # 5

This bi-monthly column deals with legal matters of interest to designers, fabricators and contractors. We solicit your comments, concerns, suggestions and questions, both as to individual issues and subjects that you would like to see treated in this column. Some of the issues that we plan on covering in the future include: contract provisions; OSHA standards; employment law; alternative dispute resolution; and dealing with the EPA. Comments should be sent to: Modern Steel Construction, One East Wacker Dr., Suite 3100, Chicago, IL 60601-2001.

WHAT IS THE LIMIT OF PROFESSIONAL LIABILITY for design professionals? Traditionally, the courts have held that professional engineers have a duty to exercise that degree of care normally exercised by design professionals under like or similar circumstances.

Of course, that's a pretty nebulous standard—Who gets to decide what's a "normal" standard of care? Today, though, the issue has been further muddled. Now lawyers are arguing not just *what* duty is owed, but also *to whom* the duty is owed.

Earlier this century, courts ruled that design professionals did not owe a duty of care to an individual unless the design professional had a direct contractual relationship with that individual. Thus, if the roof of a theater collapsed, the design engineer was not liable to those patrons injured or their heirs because there was no legal contractual relationship between the patrons and the design professionals. However, today the law is different. A designer is responsible to a third party if the designer's negligence caused either injury or property damage to that person—regardless of whether there is any contractual relationship between the designer and the third party.

But what about where an individual doesn't suffer injury or property loss due to negligence by a design professional, but instead suffers an economic loss either through a delay or the need for extra work? Or, just as commonly, one design professional suffers economic loss due to the negligence of another design professional working on the same

project? In neither case is there normally a contractual relationship between the two parties.

Third party suits over economic loss are attractive because each group has a contractual relationship with the project's developer, but neither wants to sue the developer and risk souring a future relationship. These suits also are attractive when one group is contractually limited. Under these circumstances, can a potential plaintiff essentially disregard the written contract and sue a party with whom it has no contract?

Unfortunately, this question is still being hotly debated. During the past decade, the highest courts in about two dozen states have considered the question, and the answers differ from state to state. **About half have adopted the so-called "economic loss" rule**, which finds its origin in the law of products liability. Under the economic loss rule, a design professional is not responsible for purely economic loss caused to a third party by his or her negligence if there is no contract between the third party and the design professional and there has been no personal injury or property damage.

The remaining states, however, have rendered an opposite opinion, holding that licensed professionals are responsible for all damage, economic or otherwise, arising from their negligence.

Further complicating the issue, not all states have considered the issue, and even in those that have, the law is not necessarily clear. For example, Ohio recently has apparently reversed itself, initially adopting the economic loss rule, then later issuing a contrary decision rescinding the economic loss rule. South Carolina, on the other hand, has issued a series of decisions which say that a first-time homeowner has a right to sue a designer hired by the home's developer for purely economic loss caused by design defects. However, there is some question as to whether that rule also applies to a battle-hardened subcontractor on an industrial project—an issue our office is currently appealing to that

AVOIDING PROFESSIONAL LIABILITY TRAPS



David B. Ratterman, Esq., is Secretary and General Counsel for AISC. His firm, Goldberg & Simpson, P.S.C., in Louisville, KY, concentrates in the area of construction law.

EVENTUALLY,
DESIGN
PROFESSIONALS
WILL BE
RESPONSIBLE
FOR ALL LOSSES,
ECONOMIC AND
OTHERWISE,
RESULTING
FROM BREACH
OF THE
PROFESSIONAL
LEVEL OF CARE

state's supreme court.

To add even more fuel to the fire, Maine recently issued a thought-provoking (to say the least) expansion of the law in this area when it held that a design professional who attended a preliminary meeting between an owner and a financial institution at which a construction loan was being negotiated was liable to the financial institution for not advising it that the owner's budget was insufficient to build the project. Which raises an interesting follow-up question: Under that same standard, would a design professional owe the same duty to construction contractors who don't receive final payment from an insolvent owner?

Fortunately, it is unlikely that many states will adopt a standard requiring design professionals to be the watchdog of an owner's financial solvency.

However, I do believe that, ultimately, most jurisdictions will reject the economic loss rule and eventually design professionals will be responsible for all losses, economic and otherwise, resulting from breach of the professional level of care. The law does not move rapidly, though, and such a nationwide evolution may take a generation or longer.

In the meantime, what can designers and contractors do to protect themselves?

- **First**, design professionals should be certain that their contracts clearly define the scope of their work on each particular job and that project documents clearly establish that no contractual relationship (or third party beneficiary relationship) is being established, or should be implied, between the design professional and anyone other than the party directly engaging the design professional. Any contract language that would limit the measure of damages recoverable by a contractor should apply to both the design professional and the owner.

- **Second** (and this is easier said than done), design professionals should

not accept jobs where the project owner is not providing sufficient time or remuneration to properly discharge his or her professional responsibilities.

Contractors should not accept contracts or submit competitive bids on projects where the design documents are clearly deficient. If, after a project is underway, an owner changes the ground rules under which the design professional is to perform and those changes are detrimental to the project, then the design professional should either resign the commission or be certain that the record is clear as to the owner's action. The design professional should be remunerated for the impact of these changing ground rules and, in extreme cases, should attempt to have the owner agree to hold him or her harmless from any difficulties which may arise.

- **Third**, communication is the best preventive medicine to avoid litigation. In recent years "partnering" (a new term for the old-fashioned idea of teamwork) has gained great favor on construction projects and is *heralded by many in the insurance industry as being the single most effective way to avoid litigation on today's complex construction projects.*

- **Fourth**, where litigation appears inevitable, engineers and contractors should utilize the contract chain-of-command in attempting to resolve disputes of this nature. You can be almost certain that insurance carriers will raise the economic loss rule in every instance where a third party negligence suit is brought, even in those jurisdictions where the economic loss rule appears to have been abolished. And, of course, when litigation seems inevitable, design professionals should seek the advice of counsel and the consent of insurance carriers before entering into any agreement to settle a dispute on a construction project where issues related to professional liability have been raised.

As the saying goes, an ounce of prevention is worth a pound of cure.

00262

Affordable Design Power.

PC Compatibility.

SIMON Systems



For more than 20 years, many state DOTs and consultants have utilized U.S. Steel's SIMON mainframe program for the design of straight steel plate-girder bridges. Now, the American Institute of Steel Construction is offering this powerful program on a PC platform.

SIMON designs I-shaped and multiple single-cell box-shaped girders, with up to 12 continuous spans. SIMON produces complete designs in accordance with the latest AASHTO Standard Specification for Highway Bridges. This enhanced and updated version of SIMON has undergone extensive verification by several state DOTs and consultants.

SIMON is easy to use because the engineer follows the same logic and process as when designing a bridge manually. The entire system runs in MS-DOS and occupies less than 1 MB of hard-disk space.

Output from the SIMON program includes:

- Dead-load and maximum and minimum live-load moments and shears for variable-axle H or HS truck loading or for variable-wheel loading with up to 20 axles.
- An optimum design of the girder elements based on control parameters selected by the user.
- Performance ratios computed for each limit state at the critical cross sections of the girder along with a complete printout of all AASHTO specification checks.
- A complete bill of materials including locations, yield strengths, weights, lengths, widths and thicknesses of all webs, flanges and stiffeners.

Licensing of SIMON Systems for use on a personal computer is available for an annual subscription fee of \$300. During the subscription period, AISC will furnish program updates and enhancements along with telephone support on the use of the software at no additional charge. To order or for more information: Phone: 312-670-2400, Fax: 312-670-5403.



Setting Standards for over 70 Years

Please circle # 6



00263

THIS IS GOING TO BE THE MOST POPULAR CONSTRUCTION SIGHT IN AMERICA.

Nucor-Yamato Steel is reshaping the way America sees construction. With an expanded mill that can supply

more structural steel than any mill in the Western Hemisphere.

THE BIGGEST MILL And not only more steel, but a broader product line with beams up to 40 inches deep. Perhaps best of all, we are a low cost producer. It all adds up to just one thing: talk to Nucor-Yamato before you decide to build your next project.

AVAILABILITY With 1.6 million tons behind us, nothing can stop our availability and on-time delivery by rail or truck or barge on a wide range of products. In fact, we can offer high strength steel at little or no more cost than standard ASTM A36 beams.

QUALITY Nucor-Yamato is a state-

of-the-art mill, including electric arc and ladle metallurgy furnaces, continuous beam blank casting and high performance

rolling mills designed to produce stock and other lengths for all our customers. All our steel is low carbon and fine grain with superior toughness and surface quality that offers both weldability and improved corrosion resistance.

LOW COST PRODUCER Perhaps best of all, it's produced cost effectively for some of the most competitive prices you'll ever see. And if you're in the construction business these days, that's a sight for sore eyes.

Contact Nucor-Yamato Steel early in your next project at 800/289-6977, FAX 501/763-9107; or write to us at PO Box 1228, Blytheville, Arkansas, 72316.

Structural shapes from W6 X 15 to W40 X 397
Standard sections including C15 X 33.9-50, MC 12 X 31-50, MC 13 X 31.8-50 and MC 18 X 42.7-58
H-Piling ranging from HP 8 X 36 to HP 14 X 117
Grades include ABS Grades A, B, AH32, AH36; ASTM A36; ASTM A572 Grade 50; ASTM A588 ("weathering steel"); ASTM A709 (AASHTO M270 equivalents); as well as CSA 40.21 Grade 44W

NUCOR-YAMATO STEEL COMPANY

Two New LRFD TEXTBOOKS

SEGUI LRFD TEXTBOOK OUT IN RECORD TIME

By Robert F. Lorenz, P.E.

MODERN ADVANCES IN PUBLISHING TECHNOLOGY are catching up to the speed of television. The same month that AISC introduced its new manual on Load and Resistance Factor Design (LRFD), a textbook on the new Specification landed on my desk. That textbook, *LRFD Steel Design*, is authored by William T. Segui, a faculty member in the Civil Engineering Department at Memphis State University and author of *Fundamentals of Structural Steel Design*, a textbook on Allowable Stress Design methods.

Segui's latest book contains a lucid text and well-explained example problems that should help the understanding of LRFD, which many perceive as a complex subject. The layout is generous and flowing, and is conducive to enlightened reading, even by students.

The heart of the book, though, is the set of problems following each chapter. This text has more than 300 problems for solution; 48 on eccentric connections alone. Answers to more than half these exercises are listed at the end of the book.

After two rather short introductory chapters, the next five chapters cover tension, compression, bending, beam-columns, and simple connections. The author suggests this much for a basic undergraduate course. Advanced topics are found in Chapter 8 (eccentric connections), Chapter 9 (composite construction) and Chapter 10 (plate girders). Plastic design and ASD are subjects of brief and concise appendices.

Each technical chapter has a dozen or so example problems that are truly updated and con-

tain quite detailed explanations. Subtle changes to the Specification, such as the new C_b formula or the upper bound on shape factor are clearly delineated in these examples. If you're a practicing structural engineer who has heard enough LRFD theory and needs a deep resource of worked-out design examples, this book is for you.

For those steel design educators who want to jump start their courses with a text that has

already incorporated the new 1993 AISC LRFD Specification and the 1994 LRFD Manual of Steel Construction, this textbook may be just the thing.

More information on LRFD Steel Design can be obtained from PWS Publishing Co., 20 Park Plaza, Boston, MA 02116; fax: 617/338-6134.

Robert F. Lorenz, P.E., is the AISC Director of Education and Training.

GESCHWINDNER AND COMPANY INTRODUCE LRFD TO ASD LOYALISTS

WHILE EXPERIENCED DESIGN PROFESSIONALS HAVE A WIDE VARIETY OF DETAILED TEXTBOOKS from which to choose, many of these are too complex for students and novice engineers. However, a new textbook, *Load and Resistance Factor Design of Steel Structures*, seems to have been written with the student or novice engineer in mind. Consequently, it provides a firm basis for understanding and continued learning in steel design.

The greatest strength of this textbook is that its topics are covered in a manner that is well organized, completely understandable, and straightforward. In all cases, the authors review the underlying theory, provide practical examples, discuss design considerations and offers real-world applications. Furthermore, the book first presents basic principles and simplified cases, and then builds up to more complex discussions. Above all, the text is loaded with references to other sources of supplementary information—an indis-

pensable benefit for those readers interested in more detailed discussions and/or the pioneering source of certain information.

Like most current textbooks, *LRFD of Steel Structures* is based upon the 1986 LRFD Specification and the 1986 LRFD Manual. However, the solutions manual is expected to summarize the effects of the subtle and substantive changes made in the 1993 LRFD Specification and the 1994 LRFD Manual.

The first three chapters of this textbook provide a thorough discussion of the LRFD method, including the underlying philosophy and principles of LRFD, a discussion of load and resistance factors, and loads and load combinations. In addition, the text provides an excellent discussion of the structural reliability benefit LRFD offers and promotes an understanding of how LRFD grew out of ASD.


The fourth chapter covers materials for steel structures: properties and characteristics of steel; steel grades; and bolt, weld

CONTINUED ON PAGE 20

Why should I use the new 2nd Edition LRFD Manual of Steel Construction?

Here are a dozen good reasons:

1. LRFD is **THE** AISC recommended method of structural steel design!
2. Since LRFD directly accounts for the most variable aspect of steel design—loads—it offers the most uniform reliability of any steel design method.
3. LRFD increases an engineer's international competitiveness—almost every other industrialized country has adopted limit state design.
4. In most structures, LRFD is more economical.
5. The 2nd Edition Manual combines and updates four previous AISC publications into a single two-volume set. It also includes the AISC Seismic Provisions. And, NEHRP's, SBCCI's and BOCA's seismic provisions are based on LRFD.
6. It will be easier to directly compare LRFD Steel Designs with concrete designs because the next ACI 318 Specification is expected to incorporate the ASCE 7 load factors as an alternative.
7. The 2nd Edition is a complete improvement over any previous AISC Manual—ASD or LRFD. It offers tremendously expanded coverage of connections and factored uniform load tables, as well as coverage of frame stability and leaning columns, floor deflections and vibrations, and single angle struts.
8. The 2nd Edition includes a 45-page introduction, Essentials of LRFD, that makes it easy for engineers to upgrade to LRFD.
9. Extensive editorial changes make this the easiest-to-use Manual in AISC's history.
10. All design problems are complete solutions — not just sample calculations for a few limit states.
11. The 2nd Edition incorporates all of the latest steel research, including Astaneh's shear tab work and Thornton's Uniform Force Method for bracing connections and new approach to tee connection design.
12. As professionals, it is incumbent upon engineers to utilize the best, most advanced design method available—LRFD.



**Two-volume set only \$132
(\$99 for AISC members)**

To order or for more information, phone the American Institute of Steel Construction at 312/670-2400 or fax an order to 312/670-5403 (include your VISA or Mastercard number plus expiration date).



Setting Standards For Over 70 years

QUICK STEEL SURVEY

DURING THE PAST FEW YEARS, AISC has produced a series of design guides on such subjects as: Industrial Buildings; Load & Resistance Factor Design of W-shapes Encased in Concrete; Low- and Medium-Rise Steel Buildings; Extended End-Plate Moment Connections; Serviceability Design Considerations for Low-Rise Buildings; Design of Steel and Composite Beams with Web Openings; and Column Base Plates. On what other subjects should AISC consider producing design guides or aids (circle the appropriate numbers on the reader response card near the back of this magazine; you may circle as many as you would be interested in):

- 100.Commercial
.....Buildings
- 101.Office Buildings
- 102.Parking Structures
- 103.Residential
.....Buildings

- 104.Medical Facilities
- 105.Economical
.....Building Details
- 106.Economical Bridge
.....Details
- 107.Practical LRFD
.....Primer
- 108.Metrication
- 109.Short-Span Steel
.....Bridges
- 110.Floor Vibration
.....Criteria
- 111.Stub Girders
- 112.Semi-Rigid (PR)
.....Frames
- 113.Seismic Design
- 114.Eccentrically
.....Braced Frames
- 115.Architecturally
.....Exposed Structural
.....Steel
- 116.Connecting Non-
.....Structural
.....Components to
.....Steel Systems
- 117.Connecting Steel
.....and Concrete
.....Systems
- 118.Connections for
.....Steel Pipe and
.....Structural Tubing

GESCHWINDNER, CONT.

electrode and shear stud steels. Chapters 5 through 8 cover tension members, columns, bending members and plate girders. Chapter 9 examines beam-columns and frame behavior including second-order effects, interaction, braced and unbraced frames, fully restrained frames (with leaning columns), partially restrained frames and bracing design. Chapters 10 and 11 cover composite construction and connections.

The authors are eminently qualified. Louis F. Geschwindner, Ph.D., P.E., is a professor of architectural engineering at Pennsylvania State University. Robert O. Disque, P.E., is a

consultant with Besier Gible Norden Consulting Engineers, Inc., and the former Director of Building Design Technology with AISC. Reidar Bjorhovde, Dr. Ing., Ph.D., P.E., is a professor of civil engineering at the University of Pittsburgh.

This textbook provides an excellent resource for students. Additionally, the discussion of the LRFD method and strong coverage of applied LRFD design examples would be of great benefit to the novice engineer or the experienced engineer unfamiliar with LRFD.

Charles J. Carter is Staff Engineer—Structures with AISC and a former student of Louis Geschwindner at Penn State.

Geerhard Haaijer

(1929-1994)

GEERHARD HAAIJER, PROMINENT STRUCTURAL ENGINEER AND VICE-PRESIDENT OF TECHNOLOGY AND RESEARCH AT THE AMERICAN INSTITUTE OF STEEL CONSTRUCTION (AISC) has passed away at the age of 65. A native of the Netherlands, Dr. Haaijer received his professional degree in civil engineering in 1952 at the Technical University, Delft, the Netherlands, and his doctorate in civil engineering in 1956 from Lehigh University, Bethlehem, PA.

During his 11 years as Vice President of AISC, Dr. Haaijer was actively involved as a leader in the steel industry both nationally and internationally. He published numerous professional papers and served actively in many professional organizations in civil engineering; the American Society of Civil Engineers, the Structural Stability Research Council, the Research Council on Structural Connections, the American Welding Society, the European Convention for Construction Steelwork, the International Association for Bridge and Structural Engineering, and the Royal (Netherlands) Institute of Engineers.

Before joining AISC in 1983, Dr. Haaijer was employed by United States Steel Corporation's Research Laboratory for 27 years, including 17 as chief of the Design Technology Division. During his tenure, he expanded this division from three engineers to an effective research group of 55. Additionally, he served as adjunct professor in the Department of Civil Engineering at Carnegie-Mellon University in Pittsburgh, teaching courses in structural engi-

neering and mathematics.

His background in research includes the areas of plastic design, development of hybrid girders, new fire-protection methods, cold-formed steel framing for residential structures, finite element analysis and autostress design of steel bridges.

The Geerhard Haaijer Memorial Scholarship Fund has been established at Lehigh University. Contributions can be sent to Lehigh University, 207 Memorial Drive West, Bethlehem, PA 18010.

UPCOMING EVENTS

AISC MARKETING'S POPULAR FOUR-PART SEMINAR SERIES, "Innovative Practices In Structural Steel," is quickly winding down with only 13 more seminars scheduled. The lecture includes information on the new LRFD Manual of Steel Construction, including such topics as the stability of unbraced frames, web crippling equations, and slip critical joints at factored loads.

The seminar also includes a session on state-of-the-art design software, the latest NEHRP Seismic Regulations, and a review of semi-rigid composite connections.

The seven-hour seminar costs \$90 (\$75 for AISC members), including dinner and a variety of handouts. The lecture has a CEU value of 0.4. For more information, call 312/670-5400.

Seminar Dates & Locations

Edison, NJ	Oct. 4
Philadelphia	Oct. 6
Detroit	Oct. 11
Indianapolis	Oct. 13
Memphis	Oct. 18
Phoenix	Oct. 20
Cleveland	Oct. 25
Columbus, OH	Oct. 26

Cincinnati	Oct. 27
Miami	Nov. 1
Orlando	Nov. 3
Portland, OR	Nov. 15
Las Vegas	Nov. 17

THIS YEAR'S T.R. HIGGINS AWARD LECTURES on composite design are currently underway. Lawrence G. Griffis, senior vice president of Walter P. Moore and Associates in Houston, is scheduled to give two lectures in November (for a condensed version of his lecture, see pages 36-47 of this issue). He'll be in Austin, TX, on Oct. 14 at the Annual Convention of the Structural Engineers Association of Texas and in Atlanta on Nov. 15.

For information on the Austin lecture, contact AISC Marketing regional engineer Jim Anders at 214/369-0664.

For information on the Atlanta lecture, contact AISC Marketing regional engineer Dave Magee at 404/642-9707.

SSPC's 1994 INTERNATIONAL CONFERENCE AND EXHIBITION on paintings and coatings for structural steel will be held Nov. 11-17 in Atlanta. The technical program includes 12 seminars and 17 tutorials. For more information, contact: SSPC, 4516 Henry St., Suite 301, Pittsburgh, PA 15213-3728 or call 412/687-1113.

THE STEEL STRUCTURES RESEARCH COUNCIL IS ACCEPTING PAPERS for its "Stability Problems Related to Aging, Damaged & Deteriorated Structures" conference to be held March 28-29 1995 in Kansas City. One-page abstracts on solutions to stability problems in buildings, bridges, offshore structures or lifeline structures should be submitted by Oct. 15 1994 to: SSRC, Fritz Engineering Laboratory, 13 E. Packer Ave., Lehigh University, Bethlehem, PA 18015.

NEW SPECS AND LOAD TABLES FOR STEEL JOISTS AND GIRDERS

Fortieth Edition
Standard Specifications
Load Tables and Weight
Table for Steel Joists and
Joist Girders.

Metric and U.S. Customary Units

40TH EDITION INCLUDES METRIC AND STANDARD UNITS

- Includes specs and load table on the all-new KCS Joist, an extension of the K-Series Joist. KCS Joists are useful in designing for concentrated loads and other non-uniform loads.
- Covers new K and LH Series erection stability requirements derived from over two years of study and field research by the Institute.
- Fire resistance portion has been updated and revised.
- Also included is a one-page method for converting load tables for LRFD design.

ORDER TODAY!

Just \$20.00 per copy in the U.S. and its possessions (payment includes first class postage and handling and must accompany order)

\$30.00 (U.S. currency) for international shipments

Number of Copies _____

Total enclosed _____

Name _____

Firm _____

Address _____

City _____

State _____ Zip _____

Send to:
Managing Director
Steel Joist Institute
Modern Steel Const. Div. A-1
1205 48th Avenue North
Myrtle Beach, SC 29577





Eli Cohen's design for 10 South LaSalle St. was the first Chicago structure to preserve a significant portion of the facade of the building it replaced. The first four stories of the new 37-story office tower feature the granite and terracotta facade of a 16-story office building designed by Holabird and Roche in 1911. The preservation involved keeping the first bay of the old steel-framed structure intact, a solution that helped win Cohen the 1987 Most Innovative Structure Award from SEAOL.



DESIGNING BUILDINGS THAT WORK

Developers
and architects
appreciate Eli
Cohen's ability
to design
economical—and
functional—
buildings

By Cindi Crane

CHICAGO'S LEADING STRUCTURAL ENGINEER DOESN'T WORK FOR ITS BIGGEST FIRM or its most publicized. In his approach to structural engineering, he prefers simpler solutions to cutting edge design, diplomacy to obstinacy, and reliability above all else. His structural solutions are "not too exotic," as several of his colleagues put it. But Eli Cohen wouldn't have it any other way.

With almost 40 years of structural engineering experience, the 67-year-old principal of Thornton-Tomasetti/Cohen-Barreto-Marchetti structural engineers (TT/CBM) is as much a fixture in Chicago as the many celebrated buildings he has designed. Cohen is admired and appreciated by developers, architects and contractors for his deftness as a team player, and for consistently offering functional, economical structural solutions. His clients read like a player roster for a building Dream Team—clients such as the American Medical Association, Leo Burnett advertising agency, Miglin-Beitler, and John Buck. Cohen loves his work, and his affections accent the Chicago skyline with impressive edifices that, like him, were built to last.


"He's a fabulous engineer," says Charles Thornton, P.E., of Thornton-Tomasetti structural engineers in New York, which merged with CBM last year.

"Anybody that could be responsible for the number of major projects in Chicago that a relatively small firm has accomplished is unbelievable. When you walk around town with him, he says, 'I did that one, I did that one, I did this one, I did that one.' I mean, there isn't much he hasn't touched in Chicago."

Although CBM's work spans from cooling towers to high rises, it is most noted as a pioneer in the use of composite construction in Chicago. CBM has engineered a number of these type of systems for such renowned architects as Helmut Jahn, Harry Weese, Dirk Lohan, Philip Johnson & John Burgee, Kenzo Tange, Patrick Shaw, Cesar Pelli, Ricardo Bofill and Kevin Roche. "It's challenging working with their ideas," Cohen says. "They're very creative people."

However, Cohen has a well deserved reputation of pleasing both architects and developers. Paul Beitler of Miglin-Beitler, one of Chicago's largest developers, practically sings Cohen's praises. "It's easy to take something complicated and keep it complicated. It's an art to take something complicated and make it simple. Eli has done that," he says. Cohen keeps the leasing objective paramount and is a master at satisfying developers' immediate as well as long-term needs. "Eli works very hard to think about the future," Beitler says. "He allows maximum flexibility in terms of floor loading and the way in which the beams are designed so we can have multiple floor penetrations, and it gives people the maximum flexibility for laying out their space in the building."

Bill Moody, a principal with Chicago-based developer John Buck, agrees: "Eli's buildings are economical enough that they can lease because they can be financially competitive." In fact, the majority of Cohen's buildings in Chicago are currently more than 80% leased—despite Chicago's continuing abundance of office space.



While the exterior of 190 South LaSalle St. gets most of the attention, the interior, with its clean rectangular shape and excellent window placement, is a key leasing point. Every floor features 9-ft. ceilings and can be easily divided into 10-, 15- and 20-ft.-wide offices.

Managing the balancing act between architecture and engineering is perhaps Cohen's greatest skill. "He walks the tightrope" of satisfying all of the involved parties, according to long-time friend and admirer Bill Liddy, a regional engineer with AISC Marketing, Inc. In uniting the two disciplines, Cohen recognizes that the most important component of any structure is the human element. "Anybody can design a column and a beam, but it's a team that puts it together and works together," Cohen says. "You have to put all the brains together to come up with the best solution."

Many times, Cohen's best solution is a composite structure, which involves numerous erection and trade coordination headaches. The principals at CBM "are masters at composite buildings," says Robert P. DeScenza, P.E., Thornton-Tomasetti's transplant from New

York who will eventually take over the TT/CBM Chicago office. "[Cohen] knows the whole process, and he stays involved from start to end," he notes. Developers and architects alike credit Cohen's deep involvement in projects—from his practical designs to his timely solutions—with the success of his many structures. "Eli is wonderful at being available and being responsive to recognizing that time is money, particularly in the field," Moody says. "He was always able to come up with a solution, an answer, input on constructibility issues—whatever was required—very, very quickly."

ALWAYS AN ENGINEER

RAISED IN ISRAEL, COHEN ALWAYS KNEW what he wanted to be when he grew up. "Somehow I always liked putting things together," he reflects. "I knew I wanted to be in the field of archi-

tectural engineering." One of Cohen's greatest inspirations was Thomas Edison ("he was a very creative person who had a vision, practical concepts of how to solve problems and come up with new ideas"). Later, Cohen would be encouraged by the innovations of his good friend Fazlur Khan.

After coming to the U.S. to earn his civil engineering degree from the University of Illinois, Cohen began his career in 1955 with the Illinois Division of Highways. "I liked it, but I preferred buildings," he says tactfully. Within a year, he joined Paul Rogers and Associates in Chicago as chief engineer. In 1965, the firm became an associated partnership as Rogers-Cohen-Barreto-Marchertas, Inc. When Rogers stepped down in 1969, his name was dropped from the letterhead and Cohen became president and principal of CBM, Inc.

STRUCTURAL ANALYSIS SOFTWARE

developed by COMPU-TEC ENGINEERING

BEAMS AND FRAMES \$149.00
Interactively performs analyses of continuous beams and selected 2-D frames quickly and accurately. Convenient to use instead of larger, general purpose programs.

FRAME3D (Version 3.0) \$295.00
Performs structural analyses of space frame structures (2000 nodes maximum) for a variety of loading and support conditions. Element library includes beam, truss and spring elements. Model, deformed shape, shear and bending moment plot files are generated.

FRPLOT \$99.00
Transforms data files generated by **FRAME3D** into plots of 3-D structural models or deformed shapes. These plots may be viewed on a computer monitor or printed.

BMPLLOT \$99.00
Produces load, displacement, shear and bending moment plots for beam elements and load cases selected by the **FRAME3D** user. These plots may be viewed on a computer monitor or printed in color or black and white.

FRAME3D (Version 4.0) \$395.00
Includes all of the features of **FRAME3D** (Version 3.0) plus tension only elements for diagonal bracing, piping elements for piping analysis, curved beam elements and a library of AISC section properties.

SHORE \$195.00
Performs stress analyses of shells of revolution (pressure vessels, etc.) and axisymmetric solids using the finite element method.

FEM3D \$495.00
Performs finite element stress analyses of 2-D and 3-D structures for thermal and mechanical loading conditions. Element library includes plate bending elements, planar isoparametric elements and solid elements. Includes all of the features of **FRAME3D** (Version 4.0). Model, distorted shape and stress contour plot files are generated.

FEHEAT \$195.00
Calculates the temperature distribution in flat plates and 3-D solid structures using the finite element method.

PLOTIT \$149.00
Provides model, distortion and color contour plots for **FEM3D** and **FEHEAT** analysis programs. Plots may be viewed on a monitor or printed.

BASEPLATE \$149.00
Calculates bolt loads and the maximum stress in flexible, rectangular baseplates. Bolts (preloaded) and loads may be placed anywhere on the plate. Prying action is included using a nonlinear finite element approach.

FLATPLATE \$149.00
Calculates displacements and stresses in flat (rectangular or circular) plates with concentrated or distributed loads. Plates may rest on an elastic subgrade and edges may be free, simply supported, fixed or spring supported.

The user's manual for each program contains theoretical background, descriptions of input and output, and examples. Plotting programs support HP Laser Jet and Desk Jet printers.

For more information,
please contact:

COMPU-TEC ENGINEERING, INC.

16100 Chesterfield Parkway, Suite 246 • Chesterfield, MO 63017

(314) 532-4062 • FAX: (314) 536-2154

Please circle # 85

Since 1969, the firm, now numbering 16 employees, had undergone little change in personnel—until last September. The small, respected Chicago partnership merged with the much larger Thornton-Tomasetti Engineers of New York.

There were a number of reasons for the merger, which was widely hailed by many in the industry. Almost 20 years of collaboration between the two firms had resulted in a great familiarity between the principals. But more importantly, CBM got out from under 40 years of liability, while Thornton-Tomasetti secured a better hold in the midwest. "All the partners at CBM are about the same age—we're just about to retire," explained Tony Marchertas, who is one year the junior of his longtime friend and partner, Cohen. "We felt it was a good opportunity for the people who are going to stay on to have good continuity.

Thornton says Lev Zetlin, the founding father of what is now Thornton-Tomasetti, once explained to him the gravity of liability. "It's very, very hard to start a successful engineering company, but it's even harder to stop one," Zetlin said. "The deal between Thornton-Tomasetti and CBM didn't involve a lot of money, Thornton says. CBM's payoff is in the form of freedom from future liability concerns.

For both companies, there is a comfort level in knowing that they each conduct their business with the same philosophy. Unlike some structural engineering firms, neither CBM or Thornton-Tomasetti hire and fire staff as projects commence and finish. "We've tried to maintain the staff through good times and bad," Marchertas says. "We used to, for example, turn jobs down if we saw that we couldn't handle them with our people, because we would hate to hire people and


then lay them off. But we found that Thornton-Tomasetti's philosophy was very similar to ours" on that front. Adds Thornton: "We as people and we as two companies were completely compatible."

Over the last four decades, CBM has completed a diverse array of structures—including office towers, hotels, hospitals, retirement housing, schools, manufacturing plants, warehouses, and specialty structures. However, it is the high-rise office towers that garner the most attention. CBM can claim credit for such prestigious addresses in as 35 and 77 W. Wacker Dr., 181 Madison St., 10 and 190 S. LaSalle St., all in Chicago, and 801 Grand Ave. in Des Moines. Most rise more than 40 stories, and several utilize composite design. The edifices have been acclaimed for their functionalism and have been rewarded with

Continued on page 28

Introducing...

RISA-3D



For the last 5 years our **RISA-2D** program has been setting the standard for 2 dimensional structural analysis and design. **RISA-2D** is, in fact, rated higher than most of the 3 dimensional programs currently available! See the Jan., '94 issue of Modern Steel Construction.

We are pleased to announce that **RISA-2D** has finally been surpassed!

Introducing **RISA-3D**, the new standard for structural analysis and design software. Statics, dynamics, P-Delta effects, steel design and many other features are incorporated into this powerful new program. **RISA-3D** provides a fast, intuitive problem solving environment absolutely unmatched by any other program.

Give **RISA-3D** a try and see for yourself!

RISA
TECHNOLOGIES

26212 Dimension Dr.
Suite 200
Lake Forest, CA 92630
Voice: 800-332-7472
FAX: 714-951-5848



Setting the
Standard,
Again.

Call or FAX us
for a free demo!

Please circle # 40

WE CATER OVE GET-TOGETHERS



*Herman Miles Trucking Inc., El Paso, Texas, 8,500 sq. ft.;
Architect: Joe M. James, AIA; Structural Engineer: Pedro Herrera; General
Contractor: Balboa Enterprises, Inc.; Steel Fabricator: Area Iron & Steel*

R 1,000 SMALL EVERY MONTH.

As the country's largest supplier of steel joists, joist girders and steel deck, we've pulled off some pretty big productions in our time. But that's actually a small part of what we do.

Day in and day out, the average Vulcraft project is relatively small, about



Independence Point Office Park, Charlotte, North Carolina, 17,000 sq. ft.; Architect/Engineer: Overcash/Demmitt; General Contractor: D. A. Davis Construction Co.; Steel Fabricator: Steelfab, Inc.; Steel Erector: Dixon Industries

15,000 square feet. And we take on more than 30 such projects a day; that's more than 1,000 each month, more than 12,000 a year. In short, small projects are a very big part of our business.

As such, we treat each and every one of them to the same quality products, service and expertise that we'd offer on a million square foot project. That's something smaller

joist suppliers just can't do.

Extremely efficient manufacturing means that Vulcraft is uniquely able to respond to the tightest delivery schedules.



Station KMSP-TV, Eden Prairie, Minnesota, 36,000 sq. ft.; Architect: Korsunsky Krank Erickson; Consulting Engineer: Nelson-Rudie & Associates; General Contractor: Kraus-Anderson Construction Co.; Steel Fabricator: Central Minnesota Fabricating; Steel Erector: Amerect, Inc.

We have the experience and the personnel to solve design problems that might otherwise stand in your way.

And with six joist plants across the country, Vulcraft is incredibly convenient.

All of which means shorter lead times and cheaper freight for you.

So the next time you've got a little something in the works, give us a call, or consult Sweet's 05100/VUL and 05300/VUL. Because no one else brings such vast experience and superior resources to the party.




Tony Ingolia Salami & Cheese Co., Sacramento, California, 25,000 sq. ft.; Architect/Engineer: Edward A. Bonelli & Associates; General Contractor: Holdener Construction Co.

VULCRAFT

A Division of Nucor Corporation

PO Box 637, Brigham City, UT 84302, 801/734-9433; PO Box 100520, Florence, SC 29501, 803/662-0381; PO Box 169, Fort Payne, AL 35967, 205/845-2460; PO Box 186, Grapeland, TX 75844, 409/687-4665; PO Box 59, Norfolk, NE 68702, 402/644-8500; PO Box 1000, St. Joe, IN 46785, 219/337-5411.

Version 5.3



A service company for Steel Fabricators and Detailers

80 Second Street Pike - Suite 10
Southampton, PA 18966

215-355-6003
Fax 215-355-6210

NEW

OCP An Optimal Cutting Program
for linear nesting (multiling) to
optimize cutting lists for maximum savings -
current stock, warehouse, or both.
Introductory price \$ 169.00

in the Western Hemisphere
CAPACITIES TYPE A-36 STEEL

10" x 10" x 1" Angle Iron Leg Out and Leg In
 9" Solid Round Bar
 8" Solid Square Bar
 4" x 14" Flat Bar on Flat (the easy way)
 2 1/2" x 12" Flat Bar on Edge (the hard way)
 16" Pipe and Tubing (square, round and rectangular)
 36" Beams and Channels
 12" Tees Stern In and Stern Out

CHICAGO METAL
ROLLED PRODUCTS COMPANY

3715 South Rockwell, Chicago, Illinois 60632

FOR INQUIRIES & ORDERS
CALL **312-523-5757**
FAX 312-650-1439

Big Bend

Please circle # 66

COMPOSITE DESIGN

COMPOSITE DESIGNS COMBINE THE ADVANTAGES of steel and concrete. "You get the best of both worlds," notes Beitler. However, while composite construction can be quite efficient, it also can be very complicated, since the concrete core is going up at the same time as the steel superstructure. Cohen's ability to coordinate the steel and concrete contractors has proven a benefit on many projects.

The structure at 181 W. Madison St. in Chicago, which won the 1991 Best Structure Award from the Structural Engineers Association of Illinois (SEAOI), is an exemplary example of a composite design. Developed by Miglin-Beitler, designed by Cesar Pelli in his Chicago debut in collaboration with the local firm Pat Shaw & Associates, and engineered by Cohen, this 50-story, 1.1 million-sq.-ft. structure was completed four months early and came in 5% under budget at \$225 million, according to Beitler. And even more impressively, it was 40% leased upon completion and more than 97% leased today—despite Chicago's sluggish market.

A pointed tower with multiple setbacks and a distinctive crown, Beitler gives Cohen much of the credit for the building's success. "Eli's very efficient design enabled us to build 181 W. Madison in record time. Eli, being a pragmatist, being a very savvy team player, being flexible, was able to put that together."

The building utilized some of the foundation of a previous structure. Approximately 25% of the caissons were pre-existing and transfer grade beams between the new and existing caissons were used to take the towers wind and gravity loads. The foundation wall on the east side of the building required



To help the developer's leasing efforts, the 50-story 181 W. Madison St. building was built in near-record time. The composite building won the 1991 Best Structure Award from SEAOL.

underpinning, since it shares a common wall with its neighbor, 10 S. LaSalle St., another CBM project.

The column-free interior space provided 43-ft. spans for maximum user flexibility. The many setbacks at the top of the building required all the perimeter columns to be transferred several times. In addition, the columns on either side of the loading dock at ground level also were transferred to increase clearance for trucks. Even with these complications, total steel

weight was less than 12 lbs. per sq. ft.

At the base of the building on the north side is a four-story loggia that leads to the five-story lobby with a vaulted, coffered ceiling. A bridge extends across the alley to the south to connect 181 West Madison to the Northern Trust Building.

"Eli was very helpful in the process of checking the shop drawings," says Shaw. "He always put in all his effort, and he took the time to do it right."

Another award-winning CBM composite structure is 77 W. Wacker Dr. in Chicago, which was completed in June 1992. There, the local geological deposits made the project especially challenging. Cohen drove a concrete shaft through a thick layer of relatively soft clay and delivered the building loads to hardpan about 70 ft. below the ground surface. As a result, even though the 50-story (665-ft.), 1.04 million-sq.-ft. building has a light steel frame, it is able to sustain lateral wind forces of as much as 2,000 kips.

The building features 45-ft. column-free spans and a facade free of cross beams. The foundation utilizes composite floor decking throughout. The building also features a magnificent five-story entrance lobby, offering a completely unobstructed 45-ft.-high space.

Architect Ricardo Bofill, working for DeStefano & Partners, teamed with Cohen on the project. Major tenants include R.R. Donnelley & Sons and the building's developer, The Prime Group. The SEAOL also took notice; it awarded the building its 1992 Best Structure Award.

The structure was 92% leased upon completion. "Eli is a big part of why the building was so attractive to tenants," says Jim Runnion of The Prime Group. "The floors were very efficient for them to use."

At another Chicago site, 190 S. LaSalle St., Cohen designed an efficient composite structure for renowned architects Philip



THE CADVANTAGE DETAILING SYSTEM WON'T DRIVE YOU INSANE.

CadVantage Structural performs all calculations, matches connections and figures member clearances automatically. The program prepares advance material lists (and applies M.O. #s), applies AISC weld symbols, writes bills of materials, creates title blocks, checks for logical input and more. It's easy - and your job productivity and profits will never get the ax.

CadVantage®

619 South Cedar Street • Studio A
Charlotte, North Carolina 28202

704-344-9644

MAX WEISS

STEEL SHAPING SPECIALISTS



UNUSUAL SHAPES AREN'T UNUSUAL AT MAX WEISS.

ROLLING &
FORMING
BLACKSMITHING
WELDING &
MACHINING
INDUSTRIAL AND
CONTRACTORS
SUPPLIES



IRREGULAR CURVES,
VERTICAL OFFSETS,
ELLIPTICAL SHAPES,
CIRCLES, OR
SEGMENTS
WITH OR WITHOUT
TANGENTS

If it's structural steel that needs to be bent, for major architectural projects or for unique applications, chances are, Max Weiss bends it. If you have a question or problem in bending, call, FAX or write Dept. M93 for a solution. **TAKE IT TO THE MAX.**



MAX WEISS CO., INC.
8625 W. Bradley Road
Milwaukee, WI 53224 USA
Telephone: 414-355-8220
MAX FAX 414-355-4698

Johnson and John Burgee that saved developer John Buck about \$1 million in time and construction costs.

The 900,000-sq.-ft., 40-story (575-ft.-high) pink granite tower features a 55-ft.-high lobby with a gold leaf barrel-vaulted ceiling and mosaic marble floor. This emphasis on ornamental features put additional budget pressures on the structural design. Cohen's steel and concrete solution retained the existing base-ment of the previous building, eliminating the need for sheet piling and bracing at the busy, congested site. "Eli strove to make the detailing [in the designs] simple so that it could be executed correctly and quickly in the field," says Bill Moody of the John Buck Company, which was able to put the \$1 million in structural savings into architectural features.

Concrete pouring commenced in June 1985 and was completed in March 1986. The steel erection started in August 1985 and was topped out in just eight months—a then record for a building of that size. Featuring 41-ft. clear spans, 190 S. LaSalle was only 27% preleased (including tenant Mayer Brown & Platt, the largest law firm in Chicago), but occupancy reached 88% by the end of 1988, despite difficult market conditions.

At 10 S. LaSalle St. in Chicago, Toronto architect Moriyama & Teshima (in a joint venture with Chicago-based Holabird & Root) wanted to preserve and incorporate the former Otis Building's 55-ft. elaborately sculptured terra cotta cladding. However, the facade could not be economically saved if the structure was taken down or the cladding moved and rebuilt. Cohen came up with a solution that earned the SEA01 1987 Most Innovative Design Award.

After tests confirmed the integrity of the original rock caissons, they were utilized to support transfer girders for the new exterior steel columns, located two ft. inside the tower.



77 W. Wacker won an SEA01 award in 1992.

The existing exterior steel frame, one bay deep, was left in place for the first five floors to support the original wall and cladding—which also saved considerable time and money in building foundations and subgrade construction. Starting with the fifth floor, the new tower provides 40 ft. of unobstructed office space around the central concrete core.

FUTURE PLANS

ELI COHEN'S REPUTATION IS AS SOLIDLY GROUNDED IN HIS RELIABILITY and practicality as his buildings are in the hard rock of Chicago. Asked what lessons he's learned over the years, he answers: "You have to spend more time in the conceptual design because with the first 10% of your time, you can save 25% of the cost of the building."

Aside from engineering highly successful buildings, Cohen is actively involved in his professional community. "He's a very congenial, very gregarious person," says John Zils, a leading structural engineer at Skidmore, Owings & Merrill. "And he's willing to share his knowledge with other professionals." Several years ago, Cohen served as presi-

dent of SEAIO and is currently on its board of directors. He also is an active member of several prominent committees and professional associations, including the Chicago Committee on High-Rise Buildings, the (Chicago) Mayor's Advisory Commission on Building Code Amendments, ASCE and AISC. This has been a good year for honors for Cohen. Earlier this year he won the Parmer Award from SEAIO, which is awarded to an individual whose career has been acknowledged by his peers an example of excellence in the field of structural engineering. And in October, he received an AISC Special Citation, which recognizes individuals who have made a lasting contribution to the structural steel industry.

Cohen also enjoys teaching. For six years he taught the structural portion of the refresher course for the architectural registration exam. He also has appeared numerous times as a guest lecturer on college campuses, including at Northwestern University, the University of Illinois at Chicago and Iowa State University in Ames. These contributions were recognized by the University of Illinois at Champaign-Urbana when it extended to him its 1990 Distinguished Alumni Award in Civil Engineering and invited him to join the Board of Directors of the Alumni Assoc.

What's next for Eli Cohen? He says he's not ready to retire. "I've cut my hours back from 60 to 40 per week, that's all," Cohen muses. "One of these days I'll write a book. We work for so many different architects all over the country, all over the world. I'll write a book: 'My Experience with the World's Leading Architects.'"

And if one of those architects wants to write a book on "My Experience with the World's Greatest Engineers," Cohen is sure to be included.

Cindi Crane is a freelance writer formerly based in Evanston, IL.

CALL TODAY FOR YOUR FREE DEMO KIT!

STRUCTURAL MATERIAL MANAGER 5.0

SMM 5.0 gives fabricators and detailers the fastest, most accurate material list manager available. No more time-consuming manual calculations!

The software's speed and efficiency delivers an easy-to-use system that's second to none. Call today for a FREE, no-obligation demo disk with all modules and the complete system's user's guide.

Let SMM 5.0 turn your next material list into hands-off experience!



- Main Module computes weights, surface areas, bolt counts & lineal totals
- Length-Nesting module produces optimal cut lists from in-house stock, vendor stock or the best combination of both
- Plate-Nesting Module draws the best layout for cutting plates from stock sheets
- Estimating Module tallies material costs, shop hours & field hours
- Production-Control Module prints shipping lists, loading tickets & job status reports

E.J.E. INDUSTRIES, INC.

287 Dewey Avenue, Washington, PA 15301

1-800-321-3955 or 412-228-8841

HANDS-OFF EXPERIENCE.

Please circle # 46


BEAM BENDERS

From
ROUND

**FOR BEAMS,
CHANNELS,
PIPE & OTHER
SYMMETRICAL
SECTIONS**

Ideal for beams and channel both the "hard way" and the "easy way".

Capacities ranging up to
44" WF beam on X-X axis.



Section modulus capacities over 1000 in³.

COMEQ, Inc.

Phone: (410) 325-7900

P.O. Box 2193


Balto., MD 21203

Fax: (410) 325-1025

Please circle # 68

THE LRFD (R)EVOLUTION

In addition to providing more uniform reliability, analysis shows LRFD can save an average of 5% of total steel tonnage on mid- and high-rise projects



Aine Brazil, P.E., and Thomas Scarangelo, P.E. are senior associates with Thornton-Tomasetti Engineers in New York City.

LIKE PAUL REVERE'S FAMOUS RIDE, the release of the First Edition of the Load and Resistance Factor Design (LRFD) Manual of Steel Construction in 1986 was expected to signal a revolution. Many in the engineering community braced themselves for a remarkable change in the way steel structures would be designed. And given that engineers were already comfortable with the strength design method through ACI 318, the changes should have been painless. Indeed, many leading engineers believed that the new LRFD Manual would, in just a short time, relegate allowable stress design to the dusty shelf of the reference library along with the Three Moment Equation and the Williot-Mohr Method.

Unfortunately, it hasn't quite happened that way.

The intent of the new specification was to simplify the design of structures, provide uniform reliability for the various loading conditions that a steel structure would experience in its lifetime, and improve overall economy—all laudable goals. So why then, more than eight years after the introduction of LRFD, is the engineering community still struggling with the schizophrenic approach to steel design?

A portion of the blame can be placed on human nature: People resist change and are slow to adapt to change. A look at the history of the ACI strength approach reveals that it took 15 years (from 1956 until 1971) for the working stress method to be relegated to an "alternate method." And it wasn't until

1977 that the working stress was placed in an appendix, signaling the widespread acceptance of and preference for the strength method by the engineering community.

Human nature and historical parallels, however, are not the whole story. Many other elements have contributed to the slow acceptance of LRFD by the engineering design community—miscommunication, bad timing, technological advances, and the confusion caused by LRFD's different load factors.

Miscommunication has been a serious problem. When AISC released the 9th Edition of the ASD Manual of Steel Construction, it sent a signal to many engineers that the ASD approach was not being phased out. The updating of the 8th Edition to include the latest research reinforced many engineers' justification for not "retooling."

Poor timing and the growth of computer technology also had a negative influence on the adoption of LRFD. When the ACI strength approach was introduced, computer routines were in the infancy. However, when the LRFD Specification was introduced, most offices had already invested considerable time and money in either in-house and/or off-the-shelf steel design programs. The problem was even worse on the fabrication side. Many engineers employed by steel fabricators had codified their connection design approach through the use of proprietary programs that incorporated the working stress design. And since LRFD offered little or no savings—and in some

AND THE FUTURE IS NOW


cases actually increased connection requirements—there was little incentive to switch. LRFD arrived just when design engineers were beginning to reap the benefits in savings of time and money from working stress programs—programs with which they had grown comfortable and confident in their day-to-day design process and use.

Another perceived obstacle to the widespread acceptance of LRFD is the different load factors between ACI 318 and the LRFD Specification. Regardless of their basis in solid research, the LRFD load factors have been met with confusion and skepticism by both engineers and code authorities. Further, the difference between the ACI 318 and LRFD Specifications have negated the benefit of consistent and easily translatable design forces from concrete to steel (and vice versa) in a strength design approach to a given structure.

While these problems continue to slow the transition to LRFD design, the good news is that these problems are being overcome. The LRFD Manual has been adopted by most local governing agencies as an alternate to ASD. Acceptance of LRFD is now the rule, rather than the exception.

In one of the most promising trends towards acceptance of LRFD as the preferred design standard, academia has wholeheartedly embraced it. Almost universally, engineering colleges and universities teach LRFD in their steel design course. In many cases, LRFD is the exclusive steel design method taught to undergraduates. As these students graduate and enter the workforce, their experience with—and knowledge of—LRFD will ease the transition to LRFD-based designs in offices around the country.

Another factor that bodes well for the eventual universal adoption of LRFD is the widespread recognition of LRFD for seismic design in codes throughout the country. Most seismic source



420 Fifth Ave. (left), a 30-story steel-framed office building designed in 1988, was one of the first buildings in New York City to utilize LRFD.



The Allied Junction / Secaucus Transfer Station (above) includes four 20- to 40-story office towers. The use of LRFD results in savings in steel weight in the gravity controlled columns, the baseplates and the 30-ft. span composite steel girders.



Utilizing LRFD for 546 Fifth Ave. in New York City resulted in a reduction of approximately 15% of total steel tonnage for the building's columns.

documents have adopted (or will soon adopt) the strength design approach, since the nature of seismic design requires quantifying and enhancing the ratio of ultimate strength to elastic strength or ductility of structures. The basic need to understand the behavior of systems and elements in their ultimate state of deformation makes the LRFD approach the logical choice when designing for seismic forces.

CASE STUDIES

Back in 1991, Thornton-Tomasetti Engineers evaluated the impact of having utilized LRFD in the design of two New York City mid-rise

buildings. The first was 420 Fifth Ave., a 30-story steel-framed office building. Designed in 1988, it was one of the first buildings in New York City to utilize LRFD. Also studied was 546 Fifth Ave., a 150-ft.-by-100-ft.-by-50-ft.-wide L-shaped, 23-story office building. The building is comprised of 170,000 sq. ft., with floor plates that step back every few levels and vary from 10,000 sq. ft. at the lower levels to 6,000 sq. ft. at the uppermost floor. *

In what has proven to be the case for most typical mid-rise office buildings, these designs illustrated that utilizing LRFD results in significant economies while, at the same time, providing a more uniform level of reliability.

The use of LRFD-based design for these two buildings resulted in savings for gravity columns and base plates since the New York City building code, like most building codes, recognizes significant live load reductions for columns supporting multiple stories. This, in turn, leads to favorable dead load to live load ratios. Savings for columns were approximately 15% of the total column tonnage, with an additional 25% savings in base plate tonnage.

Given the ability of steel to span long distances, and thereby resulting in girders with large tributary areas, live load reduction again is a factor for girders and especially for transfer girder design. A reduction of approxi-

mately 10% in transfer girder weights resulted from the use of an LRFD design.

Also, although most of the lateral load resisting system elements were governed by drift control, utilizing LRFD for lateral load resisting systems provided benefits, albeit minimally.

However, while the use of the LRFD Specification for the typical office floor construction (30 ft. to 45 ft. bay sizes) results in economies when the design is based only upon strength considerations, deflections, vibrations and other service related criteria tend to minimize or eliminate any savings in typical floor beam design.

Overall, the incorporation of LRFD in the design of these two buildings resulted in a savings in total steel tonnage of between 4.2% and 4.4% when compared to an equivalent ASD design.

LRFD TODAY

Thornton-Tomasetti, which now routinely uses LRFD, has a number of projects currently underway.

Representative of our larger commercial high-rise projects is the Allied Junction/Secaucus Transfer Station, a mixed-use commercial development above a rail transfer station located in the Hackensack Meadowlands, NJ. The complex of 3.6 million sq. ft., currently under design, will consist of four 20- to 40-story office towers, a 600-room hotel, retail concourse, and a 4,400-car parking garage. The structural system for the office buildings and basic station concourse will be steel framed. Floor framing with a typical bay size of 45-ft.-by-30-ft. will consist of composite beam construction with concrete slab-on-metal deck. Lateral load resistance will primarily be provided by braced cores with outriggers. Exterior moment frames will be used to supplement the cores.

In the office building structures, the use of LRFD is effecting savings in steel weight in the gravity controlled columns, the

baseplates and the 30-ft. span composite steel girders. However, the design of the 45-ft. span floor beams in the office areas will be controlled by vibration considerations. In addition, design of both the columns and braces in the lateral system will be controlled by drift limitations and will not yield savings in steel weight.

The introduction of composite design guidelines and design aids has simplified the design effort required when incorporating composite columns in a building system. For the Secaucus Transfer Station, utilizing this feature of the LRFD manual helped satisfy specific requirements driven by the platform design constraints: high headroom in the track area mandates floor-to-floor heights of up to 25 ft., with some columns unbraced for 45-ft., and the overall finished column dimensions are limited to 36 in. in diameter. The design solution utilizes concrete-encased steel columns to satisfy strength, stiffness, fireproofing and finish requirements. The provisions in the LRFD Specification greatly simplified the implementation of these components in the design, resulting in efficient column sections and minimizing design effort.

Overall evaluation of current high-rise projects shows that LRFD continues to yield average savings of 5% of the total steel tonnage.

RENOVATION ACTIVITY


In the current market economy, Thornton-Tomasetti Engineers has seen a marked increase in renovation and the expansion of existing buildings. With these types of projects, LRFD is an indispensable tool in maximizing the existing structure's capacity and minimizing the extent and cost of the design.

The Phase III renovation and vertical expansion of the Roosevelt Field Shopping Mall in Garden City, NY, is representative of this type of project. Built

in 1955 as an open air mall of approximately 650,000 sq. ft., the two-story steel frame construction is currently undergoing a major expansion, which will double the retail space in the area under renovation. A significant portion of this expansion will result from the addition of a new retail floor at the level of the existing roof.

In this project, the vertical expansion resulted in the evaluation and reinforcing of existing columns for the additional loads of the added retail level. Floor construction in the existing mall was very heavy, since the original mall was an open-air design. The resultant high dead load to live load ratios of between 1.0 and 2.5 led to a significant advantage of LRFD over ASD. Three basic categories of column treatment were developed for this project using LRFD. First, the existing columns were investigated to determine if the increased capacity under the LRFD Specification provided sufficient additional load-carrying capacity. If reinforcing was required, one of the following two methods was implemented: When space constraints were a factor, the existing W8 column sections were reinforced by cover-plating to form a box section; otherwise, the columns were made composite by encasement in concrete. Load transfer through the column-to-floor joints was critical and use of LRFD eliminated the need for intricate "watch-making" type field work.

Since the retail spaces of the mall continue in full operation during the expansion, it was imperative to minimize the



The use of LRFD for the Roosevelt Field Shopping Mall expansion reduced the impact of construction on stores operations.

extent and complexity of the structural reinforcing. By using LRFD in evaluating the capacity of the existing columns and in developing the reinforcing details, it was possible to reduce the impact of the construction work on the retail spaces.

Owners and developers of existing buildings continue to look for ways to expand and modify their properties in an effort to retain their existing tenants and to attract new tenants. The use of the LRFD method is a tool that engineers can use to effectively cut the costs of major structural renovations.

CONCLUSION

Although adoption of LRFD by the engineering community has been slow, we are confident that recognition of the advantages of this approach will continue to erode resistance and promote its acceptance as the preferred design approach. This evolutionary process is far from complete. But as its utilization on more and more projects continues to confirm LRFD's advantages of uniform reliability, consistency and improved economy, extinction of the ASD method is only a matter of time.



By Lawrence G. Griffis, P.E.

ALTHOUGH MANY MODERN STUDENTS AND PRACTITIONERS OF STRUCTURAL ENGINEERING tend to think that composite construction is a product of recent design and construction

bridge and a building were constructed. The bridge was the Rock Rapids Bridge in Rock Rapids, IA. After submitting calculations to verify his composite design, a Viennese engineer

named Joseph Melan obtained a patent for bending I-beams to the curvature of an arch and then casting them in concrete. The composite building constructed the same year was the Methodist Building in Pittsburgh, which was built using concrete-encased steel floor beams. In 1897, a fire in a nearby building spread to the Methodist Building.

While the contents were destroyed, the frame was not—demonstrating one of the advantages of composite frame construction.

As additional buildings and

bridges were constructed using steel wrapped in concrete toward the end of the nineteenth century, a need for research testing arose to better understand the behavior. A set of systematic tests for composite columns was begun at Columbia University's Civil Engineering Laboratories in 1908. This was followed by tests of composite beams in the Dominion Bridge Company's fabrication shop in Canada by Professor H.M. McKay of McGill University in 1922-24.

An early record of composite construction appearing in a U.S. building code is found in the 1930 New York City Building Code, which allowed extreme fiber stresses of 138 MPa (20 ksi) rather than the 124 MPa (18 ksi) value traditionally allowed for noncomposite beams.

Shear connectors also were recognized in this early composite construction as an effective means to enhance the natural bond between steel and concrete. In 1903, Julius Kahn received a U.S. patent on composite beams where shear tabs in the beam flanges were bent upward to project into the slab. Different types of shear connectors have been proposed over the ensuing 90 years, including some types still documented in AISC's Manual of Steel Construction.

In 1954, welded headed metal studs were first tested at the



Figure 1: The Methodist Building in Pittsburgh was an early example of composite construction.

practice, it actually began just prior to the start of the twentieth century.

In the U.S., some early uses of composite construction appeared in the year 1894 when both a





Figure 2 (left): Fazlur Kahn's 1970 Control Data Building used composite construction.

Figure 3 (above): Composite Frame Construction Sequence. The floor number refers to the number of levels above which concrete has encased the erection columns.

University of Illinois. At the completion of the tests, in 1956, a formula for the design capacity of these connectors was published. The welded headed metal stud has now become the dominant method of transferring shear between steel and concrete. The first bridge to use these connectors was the Bad River Bridge in Pierre, SD, which was built in 1956. Also in 1956, IBM's Education Building in Poughkeepsie, NY, became one of the first buildings to use headed stud connectors. The second floor was formed with a 38 mm-deep, 0.6 mm-thick composite deck, using wires welded to the top flutes of the deck to achieve composite action between the metal deck and the hardened concrete.

The widespread use of composite metal decks began to flourish in the 1950s in building construction. The metal deck acted as a form for the wet concrete, thus reducing concrete

formwork costs. The deck was shaped in such a manner as to ensure composite action so that it could serve as the positive one-way reinforcement for the final hardened concrete slab.

Composite action was first achieved through the use of wires welded to the deck. The standard today, however, is through embossments manufactured into the deck. One of the first modern buildings using this technique of construction was the Federal Court House in Brooklyn, NY, which was designed in 1960. The composite metal deck and welded headed stud have gained such widespread popularity in modern building construction that it has become virtually the only floor system for steel and composite frame buildings during the past 25 years.

The first tall building boom occurred in the U.S. in the 1920s and 1930s when high-rise structures such as the Empire State

Building and the Chrysler Building were constructed. Many of these early vintage steel frames utilized the protection that the concrete afforded the frame when it was cast around it for resistance against fire and corrosion. Not until the 1960s with the advent of modern composite frame construction have engineers actively sought rational methods to take advantage of the stiffening and strengthening effects of reinforcing bars and concrete on the capacity of the embedded steel frame. The late Fazlur Kahn, in his early discussion of structural systems for tall buildings, first proposed the concept of a composite frame system in the Control Data Building in Houston in 1970. Since that time, composite frame construction has been utilized on many high-rise buildings all over the world and its usage, with a composite column as the key element, is well documented in the work of the Council on Tall

FLOORVIB

an expert system for FLOOR VIBRATION ANALYSIS

Developed by

Thomas M. Murray, Ph.D., PE
Souhail Elhouar, Ph.D.

- Far exceeds the capability of all other floor vibration software.
- Choose from six tolerance criteria including one for rhythmic activities.
- Beam, joist or built-up member framing.
- Complete user's manual with examples and tutorial.
- PC-Based. On line expert advice.

To order send P.O., check, or credit card information for \$250 + \$10 S&H to:

Structural Engineers, Inc.
537 Wisteria Drive
Radford, VA 24141
Fax 703-639-0713
Voice 703-731-3330

Please circle # 78

DAST™

Structural Analysis/Design Software

Analysis: Sophisticated 2D/3D Static analysis including P-Delta, Seismic, Dynamic analysis with Time History, Response Spectra and more.

Design: Steel and concrete design using American and many international codes and tables.

Features: Integrated Menu System, interactive input generator, Built-in editor, true AutoCAD® compatibility, advanced graphics, plots of original and displaced structures, axial, bending moment/shear force diagrams, Stress Contours, display of Local axes.

Documentation/ Support: Industry's most comprehensive user's manual, free lifetime technical support.

Output Devices: Extensive printer and plotter support, HPGL, Postscript file generation. Conforms to stringent nuclear regulatory requirements. Virtually unlimited problem size. Complete packages starting from \$495. No copy protection in USA/Canada. AutoCAD is a registered trademark of Autodesk, Inc.

Inside the U.S. call toll free 1-800-322-1487



Das Consulting, Inc.
A Commitment to Excellence

865 Turnpike Street, North Andover, MA 01845 USA
TEL 508-794-1487 FAX 508-685-7230

Please circle # 82




Figure 4 (above): Composite Column & Wall Shapes.



Figure 5 (left): The Bank of China in Hong Kong.

Buildings and numerous other publications.

WHY COMPOSITE?

Composite frame construction is a marriage of steel and concrete. As in any successful marriage, each partner must contribute to its success. Structural steel provides high strength, longspan capability, light weight, and quick speed of construction. Concrete provides economy in carrying large vertical loads, stiffness fire resistance and damping. In high-rise building design, this synergism is particularly beneficial because composite frame construction has allowed for rapid construction by spreading construction activity over many floors, allowing work to proceed faster and more economically.

Furthermore, the moldability of concrete has allowed structural steel erection shapes to be

Modern Steel Construction / October 1994 / 39



Figure 6: Moffitt Hospital in San Francisco

embedded at strategic locations within variable and complex composite column and wall shapes (see Figure 4). This unique and important feature

problems. Because of the use of steel and composite vertical carrying elements in the same building, designers must be cognizant of differential column and

accommodates the free form architectural designs common in tall buildings today, while at the same time greatly simplifying connections of beam, column and brace elements.

However, composite frame construction has not been without its

wall shortening that can lead to problems in floor levelness. Erection constraints are sometimes forced on the contractor when he is required to erect the steel frame within a predetermined number of floors behind which concreting of the composite elements is taking place.

There can be constructibility problems at complex joints where structural steel, reinforcing steel and concrete must all fit together. The contractor and engineer must work as a team to ensure stability in the erection frame until final concreting takes place. Also, until recently, there has been no widespread building code acceptance of this form of construction, hampering its use particularly in seismic zones.

And finally, a general lack of research has contributed to many engineers' reluctance to embrace the concept of composite frame construction.

WHEN YOU BUY ST. LOUIS, YOU BUY AMERICAN!

AND YOU GET: • FULL TRACEABILITY
• LOT CONTROL
• CERTIFICATIONS

Registered Head Markings on all structural and machine bolts:



A-325
Type 1



A-325
Type 3



A-307-A



A-449



A-307-B

Products from 1/2"–3" diameter include:



COUNTERSUNK



SQUARE
MACHINE



BUTTON
HEAD

ST. LOUIS SCREW & BOLT COMPANY

6900 N. Broadway • St. Louis, MO 63147

(314) 389-7500 • 1-800-237-7059 • Fax (314) 389-7510



ECONOMIC CONSIDERATIONS

The economy of composite frame construction in practical cases of high-rise building design is often made apparent in the value engineering phase.

The general contractor will oftentimes figure the total cost of concrete, reinforcing steel, forms and steel frame. This total frame cost is then divided by the building square footage and the erected structural steel price to determine "equivalent" structural steel unit weight. When compared to the unit weight of an all-steel building, it is not uncommon to see a 10% to 20% reduction in steel weight with composite construction.

Part of this economy can be attributed to the fact that composite vertical load carrying elements typically realize an 11-fold cost advantage (steel/composite cost approximately equal to 11.0) when comparing strength and an eight-fold advantage when com-

paring axial stiffness. Perception to motion, as measured by building acceleration of the top most occupied floor, oftentimes controls the design of lateral load resisting frames in tall, slender buildings. Crosswind acceleration is oftentimes the most predominant component of acceleration and its relationship to the building properties can be defined by the following proportionality:

Cross Wind Acceleration:

$$\alpha \frac{(\text{Wind Velocity})^{3.54} \times (\text{Period})^{1.54}}{(\text{Damping})^{0.5} \times \text{Mass}}$$

Because of the inherent advantages of composite frames over all-steel frames as shown above, it is not uncommon for composite building accelerations to be as little as 50% of all-steel building accelerations. When building motion controls the

design in tall buildings, as it often does, there is a very powerful incentive for engineers to use composite frames. Indeed, in looking at most of the super-tall buildings being considered around the world today, it can readily be said that "When engineers build tall, they build with composite."

Perhaps the most spectacular example of composite frame construction that exists today can be found in the Bank of China Building in Hong Kong (see Figure 5). Designed by architect I.M. Pei and engineered by Leslie Robertson, this sleek and graceful tower exhibits all the attributes of composite frame construction. Its five composite columns form a megastructure of concrete filled steel tubes that together provide the lateral load resisting frame in one of the windiest cities in the world—all for a mere 23 psf of structural steel.

STRUCTURAL SOFTWARE CO.

offers a full line of computer programs specifically for the steel fabrication industry. Wouldn't you like to realize the benefits that our existing 400 customers have been enjoying over the past 10 years?

SSC's integrated family of computer programs includes:



STRUCTURAL SOFTWARE CO.

SOFTWARE FOR THE STEEL INDUSTRY
P.O. Box 19220, Roanoke, VA 24019
(703)362-9118

Estimating
Production Control
Inventory
Purchase Orders
Combining
Automated Beam & Column Detailing

**New Automated
Drawing Log**

Tracks drawings,
revisions, and
transmittals

Only \$299⁰⁰

Ask for a free
demo disk

(800)776-9118 Call for a FREE demo disk!

GRINDER SOFTWARE COMPANY

MATERIAL ESTIMATING FOR STEEL FABRICATORS

- ✓ Accomplish in 3 hours time what used to take 8 hours with pencil and paper.
- ✓ Keep material waste to the absolute minimum using our unique length optimizing process.
- ✓ Produces 12 precise, easy to read reports for use by the shop and office.
- ✓ Handles ferrous and non-ferrous metals, fasteners, hardware, misc. items and assembled units. Also tracks shop and field labor.
- ✓ Interfaces with the SteelCad™ International detailing software.
- ✓ A "Competitive Upgrade" is available.
- ✓ "Test Drive" our fully functional demo for 30 days and start saving today.

1774 Rose Valley Road
P.O. Box 431
Kelso, WA 98626

Tel 800 677-4474
Fax 206 577-4474

COMPUTER SOFTWARE FOR SUCCESSFUL STEEL FABRICATORS

Please circle # 83

For the BEST in Bridge
Software...

DESCUS-PLUS

Design of Curved Girder Bridges

NEW FEATURES:

- ☐ Live Load Distribution - Automatic (Longitudinal & Transverse)
- ☐ Mesh Generation - Automatic
- ☐ Rating - Auto Rating Factors
- ☐ Influence Line Output (From Influence Surfaces)
- ☐ Metric Conversion
- ☐ Uses AASHTO 15th Edition
- ☐ Lease or License
- ☐ Timesharing

Free Trial...
FULL Program!

MERLIN DASH

Design & Analysis of
Steel Girder Bridges

- ☐ AASHTO - Uses New 15th Ed.
- ☐ FHWA - Endorsed and Used by
- ☐ DOT's - Used by 35 States
- ☐ Design - Cost Optimized
- ☐ Friendly - Menu-Driven Input
- ☐ Graphics Display of Output
- ☐ Output Report Selection
- ☐ Quality and Performance

TRAP

Truss Rating and
Analysis Program

- ☐ Continuous to 6-spans
- ☐ Prestressed Trusses
- ☐ Cable Members
- ☐ Design & Rehab.
- ☐ AASHTO and LL Vehicles to 20 Axles
- ☐ Auto. computation Inv.
- ☐ Operating & Posting Load

Available Exclusively Thru:

OPTI-MATE, INC.

P.O. Box 9097, Dept A, Bethlehem, PA 18018
(610) 867-4077

Please circle # 53

42 / Modern Steel Construction / October 1994



Figure 7:
Renovation
of a high-rise
building
frame

RENOVATION/STRENGTHENING

While composite construction in the U.S. has flourished in the area of new construction for high-rise buildings, its use has also grown in the area of retrofitting of existing structures. Recent experience has shown that various combinations of steel and composite elements—whether steel angle bracing, composite columns (concrete filled tubes or concrete encased rolled shapes), steel plate composite shear walls or concrete encased steel beams—are ideal for bringing older structures in conformance with modern building codes.

It is very likely that this usage of composite frame structures will expand in the future. All three model building codes in the U.S. now require seismic design. There is a move to standardization of seismic requirements by incorporation of NEHRP seismic provisions in the model codes as well as in the new ASCE 7 document. As seismic awareness spreads eastward from California and seismic design is required by national and local codes, can it be very long before the federal government and thus the private sector requires (demands) seismic safety in building design?

Composite shear walls have been used in California in hospital design. The Moffitt Hospital

in San Francisco, designed by J.J. Degenkolb Associates, is an 18-story building that utilized steel plate shear walls wrapped in concrete (see Figure 6). Although the steel plate shear walls were used in this hospital as part of the original construction, the application is well suited to retrofit. In this case, the steel plates were designed to carry all the lateral loads and the concrete was used for fire resistance. The 1994 NEHRP provisions will permit designing this type of frame as a composite system. Composite shear walls can be an excellent method for retrofitting older structures because of the high-strength, high-ductility, and the limited space requirement within existing cavities and inherent fire resistance.

High-rise buildings, designed for older wind code provisions, can be upgraded by wrapping existing steel columns in reinforced concrete and welding headed stud shear connectors to the columns. Additional wind bracing can be added between the new composite columns to strengthen the lateral load resisting system in order to bring it under compliance with modern wind codes (see Figure 7).

Research has been completed at the University of Texas at Austin under the direction of

MODERN STEEL CONSTRUCTION

Reader Service Card

Please type or print only

name _____

company name _____

address _____

city _____ state _____ zip code _____

() ()

business telephone _____ fax number _____

For free information on advertisers and other companies mentioned in this issue, circle the appropriate number below:

1	2	3	4	5	6	7	8	9	10	11	12
13	14	15	16	17	18	19	20	21	22	23	24
25	26	27	28	29	30	31	32	33	34	35	36
37	38	39	40	41	42	43	44	45	46	47	48
49	50	51	52	53	54	55	56	57	58	59	60
61	62	63	64	65	66	67	68	69	70	71	72
73	74	75	76	77	78	79	80	81	82	83	84
85	86	87	88	89	90	91	92	93	94	95	96
97	98	99	100	101	102	103	104	105	106	107	108
109	110	111	112	113	114	115	116	117	118	119	120
121	122	123	124	125	126	127	128	129	130	131	132

☐ Check this box to renew or start a **FREE*** subscription to *Modern Steel Construction* *This offer good only for practicing professionals within the U.S.

signature _____

1. Type of work

Please circle **all** that apply

- a. Bridges
- b. Office Buildings
- c. Hospitals
- d. Retail
- e. Industrial
- f. Schools
- g. Multifamily
- h. Institutional
- i. Low-Rise
- j. High-Rise

2. Your position

Please circle **ONLY** one

- a. Owner/President
- b. Chief Engineer/Chief Architect/Department Head
- c. Staff Engineer/Staff Architect/Construction Manager
- d. Other

3. Type of business

Please circle **ONLY** one

- a. Structural engineer
- b. Civil engineer
- c. Structural steel fabricator
- d. Other fabricator
- e. Educator/library
- f. Architect
- g. Building owner/developer
- h. Steel mill
- i. Erector
- j. Steel product manufacturer
- k. GC/CM
- l. Student
- m. Other

4. Reason for Inquiry

Please circle **ONLY** one

- a. Information file
- b. Immediate or Future Purchase

OCTOBER

Use these cards to request information from manufacturers and other companies mentioned in this issue. Simply circle the numbers referenced in the advertisement or article, fill out the rest of the information requested on the card, and either mail it to: Modern Steel Construction, Creative Data Center, 650 South Clark St., Chicago, IL 60605-9960 or fax it to: **312/922-3165.**

Please type or print only

name _____

company name _____

address _____

city _____ state _____ zip code _____

() ()

business telephone _____ fax number _____

For free information on advertisers and other companies mentioned in this issue, circle the appropriate number below:

1	2	3	4	5	6	7	8	9	10	11	12
13	14	15	16	17	18	19	20	21	22	23	24
25	26	27	28	29	30	31	32	33	34	35	36
37	38	39	40	41	42	43	44	45	46	47	48
49	50	51	52	53	54	55	56	57	58	59	60
61	62	63	64	65	66	67	68	69	70	71	72
73	74	75	76	77	78	79	80	81	82	83	84
85	86	87	88	89	90	91	92	93	94	95	96
97	98	99	100	101	102	103	104	105	106	107	108
109	110	111	112	113	114	115	116	117	118	119	120
121	122	123	124	125	126	127	128	129	130	131	132

☐ Check this box to renew or start a **FREE*** subscription to *Modern Steel Construction* *This offer good only for practicing professionals within the U.S.

signature _____

1. Type of work

Please circle **all** that apply

- a. Bridges
- b. Office Buildings
- c. Hospitals
- d. Retail
- e. Industrial
- f. Schools
- g. Multifamily
- h. Institutional
- i. Low-Rise
- j. High-Rise

2. Your position

Please circle **ONLY** one

- a. Owner/President
- b. Chief Engineer/Chief Architect/Department Head
- c. Staff Engineer/Staff Architect/Construction Manager
- d. Other

3. Type of business

Please circle **ONLY** one

- a. Structural engineer
- b. Civil engineer
- c. Structural steel fabricator
- d. Other fabricator
- e. Educator/library
- f. Architect
- g. Building owner/developer
- h. Steel mill
- i. Erector
- j. Steel product manufacturer
- k. GC/CM
- l. Student
- m. Other

4. Reason for Inquiry

Please circle **ONLY** one

- a. Information file
- b. Immediate or Future Purchase

OCTOBER

**BUSINESS REPLY MAIL**

FIRST CLASS MAIL PERMIT NO. 12522 CHICAGO, IL

POSTAGE WILL BE PAID BY ADDRESSEE

**MODERN STEEL
CONSTRUCTION**c/o CREATIVE DATA SERVICES
650 S CLARK ST
CHICAGO, IL 60605-9960NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

Use these cards to request information from manufacturers and other companies mentioned in this issue. Simply circle the numbers referenced in the advertisement or article, fill out the rest of the information requested on the card, and either mail it to: Modern Steel Construction, Creative Data Center, 650 South Clark St., Chicago, IL 60605-9960 or fax it to: **312/922-3165**.

**BUSINESS REPLY MAIL**

FIRST CLASS MAIL PERMIT NO. 12522 CHICAGO, IL

POSTAGE WILL BE PAID BY ADDRESSEE

**MODERN STEEL
CONSTRUCTION**c/o CREATIVE DATA SERVICES
650 S CLARK ST
CHICAGO, IL 60605-9960NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES**MODERN STEEL
CONSTRUCTION**
Reader Service Card




Figure 8: ATLSS connector / semi-rigid composite joint detail

James Jirsa and Michael Englehardt to strengthen non-ductile reinforced concrete frames with a steel bracing system. This work involved the jacketing of concrete columns with steel plates and developing existing bottom reinforcing bars through the beam column joint with through bolts. This reinforcing provides a means for retrofitting existing concrete buildings with steel to form a composite frame.

COMPOSITE JOINTS

Clearly, the lack of experimental research required to develop accurate strength models for the transfer of forces between steel and concrete at composite frame joints in one obstacle that has deterred the use of composite frame construction. However, recent research in this area should help change this situation.

Research on the design and behavior of composite moment frame joints by Gregory G. Deierlein, first at the University of Texas at Austin and now at Cornell University, has provided new insight for engineers using composite frame construction. Bahram Shahrooz at the University of Cincinnati has performed experimental research on coupling of concrete shear walls with steel coupling beams. This research should aid practicing

COMPUTER DETAILING

Ask Those Who've
Been There



1-800-456-7875

Please circle # 84


A Quick Quiz For Structural Engineers

The more a computer program costs, the better it is. TRUE FALSE

A program that solves complex, difficult problems must be complex and difficult to use. TRUE FALSE

Structural engineering software can never be fun to use. TRUE FALSE

If you answered *TRUE* to any of the above, or you would like to know more about a truly innovative software program, call us!



RISA-2D

Your complete solution for
frames, trusses, beams,
shear walls and much more!



26212 Dimension Drive, Suite 200
Lake Forest, CA 92630
1-800-332-7472

Please circle # 40

Modern Steel Construction / October 1994 / 43

IT'S HERE!

A Brand NEW Publication For Safe Construction Practice in Steel Floor and Roof Deck Installation



"SDI MANUAL OF CONSTRUCTION WITH STEEL DECK"

is a new and complete guide to safe construction. It covers responsibilities for Design, Specification, Bundling, Loading, Unloading, Hoisting, Placing, Attaching, Placement of Construction Loads. It serves as a safety primer for Contractors, Erectors, Architects, Engineers and Inspectors who are responsible for safe and proper field installation of Steel Deck.

**PRACTICAL...
EASY TO READ...
EASY TO FOLLOW...
EASY TO TAKE TO THE JOBSITE...**

BRAND NEW—FIRST PRINTING SDI MANUAL OF CONSTRUCTION WITH STEEL DECK—No. MC01

Quantity @ \$18.75 each

U.S. Currency Total

Out of Continental U.S. Add 15%

Call SDI for Special Shipping such as
Express Mail, Air Mail, etc.—additional

TOTAL ENCLOSED

NAME

ADDRESS

CITY

STATE ZIP

ALLOW 3 TO 4 WEEKS FOR DELIVERY

STEEL DECK INSTITUTE

P.O. Box 9506 Canton, Ohio 44711 (216) 493-7886

1992 Structural Steel Volume All Building Types




Figure 9: Steel in construction

engineers in designing for this practical condition under both wind and seismic loads.

Motivated by the use of large scale thin walled circular composite columns in high-rise buildings in Seattle, Atorod Azizinamini has performed experimental research and developed design criteria for the use of steel wide flange beams moment connected through large diameter steel pipes filled with high-strength concrete. Research at Lehigh University under James M. Rickles has provided new insight on the behavior of high-strength concrete encased steel H shapes under seismic loads. Other research at Lehigh includes the development of the ATLSS Connector (see December 1993 MSC). One version of this connection is applicable to semi-rigid moment connections as shown in Figure 8.

This and other research expected to come out of the Phase 5 U.S./Japan Cooperative Research Program discussed later in this article should provide needed information to enhance the usage of composite frame construction in the years ahead.

CODES/SPECIFICATIONS/ LITERATURE

The 1994 edition of the NEHRP (National Earthquake Hazard Reduction Program) "Recommended Provisions for

the Development of Seismic Regulations for New Buildings" has completed final balloting and will be published soon.

For the first time ever, this important document, prepared by the Building Seismic Safety Council, will contain a new chapter devoted

strictly to composite elements structural systems and connections.

This chapter is clearly a milestone in the evolution of composite frame structures. For the first time guidelines will be available to the practicing engineer to utilize composite frame construction. This new chapter is particularly important because the NEHRP provisions serve as a resource document to the model building codes. It is hoped that this widespread coverage will encourage the use of composite construction and serve as a catalyst for new research in this area.

There have been other important developments as well. The ASCE Committee on Composite Construction has been very active in preparing design guidelines in the field of composite construction. Included are the following:

- Guidelines for Design of Joints Between Steel Beams and Reinforced Concrete Columns
- Specification for Composite Joists and Trusses
- Guidelines for Design of Composite Semi-Rigid Connections

These documents will soon be available to the profession.

AISC has published another

in its series of design guides—this one dealing with composite columns. Entitled "Load and Resistance Factor Design of W-Shapes Encased in Concrete," it is based on the new AISC LRFD provisions for composite columns. It contains much practical information, including construction details, and design tables. An accompanying computer program also is available.

Other publications also are available. A comprehensive new text entitled "Constructional Steel Design—An International Guide," edited by Patrick Dowling, John Harding and Reidar Bjorhovde and published by Elsevier Applied Science contains several chapters on the subject of composite construction. A recently published text describing European practice as defined in the new Eurocode 4 is entitled "Designers Guide to Eurocode 4" by R.P. Johnson and D. Anderson, published by Thomas Telford Services Ltd. is now available.

Two recent international conferences, sponsored by the Engineering Foundation, have been held recently. Proceedings from both the Henniker, NH, conference in 1987 and the Potosi, MO, conference in 1992 are available from ASCE. A third international conference is planned.

RESEARCH

Some of the recent research on composite joints and columns was briefly described earlier. Other important work has been done or is now ongoing. Most readers are aware of the pioneering work done by Roberto Leon (see March MSC). Subash Goel has recently tested steel joist encased in plain and fiber reinforced concrete. This work could offer a practical composite system applicable not only to new construction but also to retrofit existing structures.

Perhaps the most significant work in the field of composite construction is yet to come. The U.S.-Japan Cooperative

WHITEFAB INC.

BIRMINGHAM
ALABAMA

IN ADDITION TO ANGLE, RAIL, PIPE, CHANNEL, AND BEAM ROLLING CAPABILITIES, WE ROLL TUBES, CHANNELS, AND BEAMS THE HARD WAY.

Phone (205)791-2011 FAX (205)791-0500

Please circle # 55


► RAMSBEAM ◀

Guaranteed to be the BEST beam program ever or your money back! RAMSBEAM, a single steel/steel composite beam program utilizing a Windows graphical interface. Features: ASD or LRFD; vibration analysis; checks existing framing or optimizes new. Allows for depth restrictions, cantilever beams; partial or full composite and unbraced frame conditions; includes SI/Metric units.

Special Limited Time Offer \$150

Ram Analysis

5315 Avenida Encinas, Suite 220
Carlsbad, CA 92008
Tel. 800-726-7789 • Fax. 619-431-5214





FREE
DEMO!

Please circle # 81

DESCON

DESIGNS AND DETAILS
STEEL CONNECTIONS



FOR A FREE DEMO DISK
CALL OR WRITE TO




OMNITECH ASSOCIATES

P.O. BOX 7581
BERKELEY, CA 94707
(510) 658-8328

Please circle # 52



Figures 10 & 11 (left): Fujita System from Japan
Figure 12 (top right): Shimizu System from Japan
Figure 13 (middle right): Kajima System from Japan
Figure 14 (bottom right): Taisei System from Japan



Research Program is now about to enter Phase 5. This phase deals with Composite and Hybrid Structures and promises to provide insight into the behavior of composite elements, systems, and connections. The focus of this research effort will be in the following areas:

1. New materials, elements and systems
2. Concrete filled steel tube (CFT) systems
3. Reinforced concrete (RC)/steel reinforced concrete (SRC) systems
4. Reinforced concrete (RC)/steel reinforced concrete (SRC) wall systems

Research in these four areas will include the following topics:

1. Material and component studies
2. Subassemblages
3. Complete structure
4. Analytical studies
5. Design studies

A common theme structure for the joint research effort in the

two countries will be used to facilitate comparisons between various system types identified for research and to derive structural elements and subassemblages for detailed studies. Component and subassemblage studies will probably precede testing work on full systems. Physical research specimens will be not less than one-half full size. It is envisioned that five years will be needed to fulfill the major objectives of this research program.

LOW-RISE CONSTRUCTION

In comparing U.S. and Japanese practice in composite construction, it is interesting to see the difference in focus, emphasis and thrust of research and applications. In the U.S., the emphasis has been on high-rise construction where composite construction has allowed economy of materials, speed of construction, and maximum utilization of labor trades. Applications

have been mostly in non-seismic zones where wind loads have controlled the design. In Japan, however, composite construction has expanded because of the perceived advantages it has in high seismic zones where the increase in stiffness, ductility and fire resistance is important. Also, most of the Japanese applications are in low-rise and mid-rise construction.

Perhaps, however, the U.S. can learn from the Japanese experience in low-rise construction. It is interesting to examine the usage of structural steel in U.S. building construction (see Figure 9). AISC Marketing, Inc. reports that for calendar year 1992, more than 60% of the steel volume is contained in one-story buildings, nearly 90% in buildings less than or equal to four stories, and less than 2% in high-rise buildings over 20 stories. This leads to a significant conclusion for the future of composite frame construction: "The glamour is in high-rise, but the volume is in low-rise."

Perhaps, however, the U.S. can also learn from the Japanese experience in high seismic zones. In Japan, the numerous large construction companies are well equipped and funded for research in structural components and systems. As a result, numerous proprietary components and systems have been developed. Systems with long-span steel beams connecting to concrete filled steel tubes or to steel reinforced concrete columns or walls are very common in Japan. Clever connection details have been developed to make these systems practical (Figures 10 through 14). These systems are designed according to structural standards published by the Architectural Institute of Japan and the Building Research Institute of Japan. However, many of the new components and systems developed are not covered by the existing standards and so the composite research on the Japanese side is motivated to develop new stan-

dards.

The challenge for U.S. designers, builders and researchers is clear. We must develop new composite frame systems for low-rise construction, suitable also for seismic zones. New composite materials, elements, systems and connections will likely take advantage of the ductility, toughness and redundancy that are inherent in steel and concrete composites. As we look back on our experience in the U.S. with high-rise composite construction, the road to successful applications is evident. First, we must develop new low-rise systems, starting in non-seismic zones. Here, as in the high-rise arena, designers and builders should collaborate on the development of practical, economical systems. Then, we need the researchers to conduct physical and analytical tests to enhance our understanding of the behavior of such systems and to refine the simplified theories used in the early development. Subsequently, with the experience of practical applications in low and moderate seismic zones and a newly refined design theory, we are in a position to apply these systems to high seismic zones. And lastly, we must codify the practice.

Although this may seem a somewhat backwards approach, it is borne out of necessity and certainly worked well for U.S. high-rise development. This procedure will allow new composite systems to successfully compete with existing steel, composite and concrete systems in the marketplace.

Lawrence G. Griffiths, P.E., is senior vice president of structural engineering with Walter P. Moore and Associates in Houston. The author wishes to acknowledge the assistance of Ivan Viest, who furnished much of the early history of composite construction usage in the U.S., Isao Nishiyama of the Building Research Institute in Tsukuba, Japan, and the researchers named in the article.



Mound Architectural

Fabricators of Quality Railing and other Decorative Metal Products

Pricing available for standard products.

NO CHARGE FOR QUOTATIONS on most custom projects.

Standard picket rail from \$17.00 a lineal foot.

940 Holman Ave., Monroe, OH 45050

513-422-0584 513-422-5184 (FAX)




Please circle # 97

ROBOT V6

THE FINEST IN STRUCTURAL ANALYSIS AND DESIGN SOFTWARE

**HIGHEST
RATING
4.5**
IN
1994
STRUCTURAL
ENGINEERING
SOFTWARE
SURVEY
MODERN STEEL
CONSTRUCTION
JANUARY '94



- very easy to learn and use, become a productive user in just one day
- extremely fast, shortens the concept through design cycle
- most powerful on PC platform - 3D FEM, buckling, nonlinear, P-delta, dynamic, 3D moving loads, parametric structures, phase constructions, US and foreign codes
- buy the power you need, starts from \$495 version - 150 node/3D plus plate elements
- easy payment plans for 1500 and 32500 node versions
- no risk, 30 day money back guarantee

See for yourself. Have fun. Any questions? Call us. **1-800-60-ROBOT**

metrossoft

332 Paterson Ave
E. Rutherford, NJ 07073

DEMO AVAILABLE (WORKING VERSION OF PROGRAM AND PRE-RECORDED EXAMPLES)
OVER 1200 USERS WORLDWIDE. FOR MORE INFORMATION CALL 201-438-4915 OR FAX TO 201-438-7058



UK • Germany • Italy • Belgium • Spain • Portugal • France • Brazil • Luxembourg • Poland • Jordan • Morocco

©1994 Metrossoft, Inc. All brand and product names are trademarks or registered trademarks of their respective holders. Copyrighted Textbook Only. Metrossoft makes no warranties with respect to this product.

Please circle # 51

COMPUTER PERIPHERALS

Product: Color Scanner**Company:** ANAtch**Address:** 10499 Bradford Road
Littleton, CO 80127**Telephone:** 800/533-0165**Fax:** 303/973-7092**Info:** This new scanner offers single-pass, large format, color scans at 100 dpi to 400 dpi. Scanner interface software provides the ability to classify color or gray tones and is available for Windows, Windows NT or UNIX Motif operating environments. Output formats include: TIFF 24 bit RGB, TIFF 8 bit Palette Uncompressed, TIFF 8 bit Palette PackBits, RGB 24 bit Uncompressed, T27 Compressed RGB, COT Continuous Tone, CRL Color Run Length, and T29 Compressed Color. Operating platforms include: Intergraph RISC and Intel-based workstations; IBM RS/6000; Sun SPARCStations; HP Series 700; Data General AviiON; and other major UNIX workstations.**Circle no:** 87**Product:** Plotter Supplies**Company:** Dataprint**Address:** 700 South Claremont St., Ste. 205
San Mateo, CA 94402**Telephone:** 800/227-6191**Info:** The free Dataprint catalog offers a complete in-stock selection of brand name drafting and plotter/CAD supplies at discounts of up to 60%—with same day shipment. This 72-page catalog features drafting equipment, media, ink jet, electrostatic and pen plotter supplies, furniture, books and calculators.**Circle no:** 88**Product:** Plotters**Company:** Galtech**Address:** 5320 Derry Ave., Ste. H
Agoura Hills, CA 91301**Telephone:** 800/688-4496**Fax:** 818/707-0587**Info:** Two types of plotter systems were recently unveiled by this company. The Marksman GF-1060 plotter is a D-A flatbed pen plotter with DC linear motion for vector sorting. The GC-1060 offers full color, 10 pen plotting. For larger E-size plotting, the company offers the PlotPal GC-1090 with digital "closed-loop" feedback control system and high speed pen motion. Its plotting speed is in excess of 42

in./sec. and will support media sizes for ANSI E-A or ISO A0-A4. Both plotter types support HP-GL/2 graphics language emulation software and buffer expansion sizes from 1 MB to 4 MB. Prices start at \$2,495 for the Marksman and \$2,995 for the PlotPal.

Circle no: 89**Product:** Full-Size Scanners**Company:** IDEAL Scanners & Systems**Address:** 11810 Parklawn Dr.
Rockville, MD 20852**Telephone:** 301/468-0123**Fax:** 301/230-0813**Info:** Four new SCSI interfaced scanners feature a Digital Signal Processor for better image capture. The large document scanners are available in from 300 dpi to 1000 dpi and start at \$9,900. Scans can be made in 40 different raster formats and software is available for PC-compatible and Macintosh computers, as well as a variety of workstations including SUN and Silicon Graphics.**Circle no:** 90**Product:** E-Size Plotter**Company:** JDL**Address:** 4770 Calle Quetzal
Camarillo, CA 93012**Telephone:** 800/899-8709**Fax:** 805/389-6993**Info:** A free cost-of-ownership analysis is offered along with a video demo of this company's E-size, 400 dpi laser-quality plotter. According to the manufacturer, the JDL 4000E plotter has a five-year cost of ownership significantly less than its competitors. The plotter can use plain paper, vellums, and films. Plots are cut to exact size (B through E), virtually eliminating media waste and plot trimming.**Circle no:** 91**Product:** Combined Plotter & Scanner**Company:** Precision Laser Plotting**Address:** 3260 N. Hayden Road, Ste. 104
Scottsdale, AZ 85251**Telephone:** 602/949-7568**Fax:** 602/949-7321**Info:** Wide-format document storage and retrieval, top-speed plotting, plain-paper copying, electronic collation, enlargements and reductions can all be accomplished automatically with just one output device controlled by the plotWorks Total-Reprographics

System. The new PC-based system can produce original plots or complete multiple-document sets at a rate of 400 D-size plots per hour on the Xerox-8845 engineering printer/plotter, while with the Indigo-536XL, collated sets are produced at a rate of 1,200 D-size plots per hour.

Circle no: 92

Product: Color Ink Jet Plotter

Company: Summagraphics
Address: 8500 Cameron Road
Austin, TX 78754

Telephone: 512/835-0900

Fax: 512/835-1916

Info: Two new low-cost, wide format color ink jet plotters for CAD applications have been recently introduced. The plotters feature a refillable and interchangeable tri-color and monochrome cartridge system and produce vivid and crisp D- and E-size drawings with up to 32 levels of gray supports and user-definable line densities. The plotters are both raster and vector compatible and ship with 4 MB of stan-

dard memory expandable up to 32 MB. Prices range from \$2,799 to \$4,499.

Circle no: 93

Product: Wide Format Scanner

Company: WideCom Group
Address: 55 City Centre Dr., Ste. 500
Mississauga, Ontario L5B 1M3
CANADA

Telephone: 905/566-0180

Fax: 905/566-0181

Info: The SLC-36 offers a scanning speed of 8.5 ft./min. for a price under \$30,000. An E size (36x44) scan from start to TIFF G4 compression on disk takes less than 32 seconds for fine mode files and 16 seconds for standard mode files. The scanner offers true 400x200 dpi scan resolution and simple one step operation. An optional internal high-speed modem allows fax transmission to both standard fax machines and through the WIDefax network. Also available is optional raster to vector conversion.

Circle no: 94

Get your detailers in shape(s)!

Save time doing detail drawings and have AISC shapes drawn at your command.

AISC for AutoCAD will draw the end, elevation, and plan views of W, S, M, and HP shapes, American Standard Channels (C), Miscellaneous Channels (MC), Structural Tees cut from W, M, and S shapes (WT, MT, ST), Single and Double Angles, Structural Tubing, and Pipe. Shapes are drawn to full scale corresponding to data published in Part 1 of the AISC Manuals of Steel Construction. US or Metric units may be selected.


AISC for AutoCAD Version 2.0 runs in AutoCAD Release 12 only, Version 1.0 runs in AutoCAD Release 10 and 11. **\$120.00**

To order or for more information:

Phone: 312-670-2400

Information Fax Line: 800-644-2400

American Institute of Steel Construction
One East Wacker Drive, Suite 3100
Chicago, Illinois 60601-2001



AISC for AutoCAD

AutoCAD is a registered trademark in the US Patent and Trademark Office by Autodesk, Inc.
AISC for AutoCAD is copyrighted in the US Copyright Office by Bridgefarmer & Associates, Inc.

Please circle # 1

Help Wanted

Aggressive, expanding structural steel fabricator in the midwest is seeking an experience Chief Draftsman. Department has 12 to 14 detailers. Must be a take charge individual with total control over department and outside detailers. Great assistant on board. CAD experience a plus. Send resume with salary history and requirements to:

**President, Doing Steel, Inc., 2125 North Golden,
Springfield, MO 65803**

**WE PROVIDE
CADD STRUCTURAL STEEL
DESIGN/DETAILING**
for Engineers, Fabricators and Contractors
JOHNSON TECHNICAL SERVICES
A Division of Johnson Technologies
2905 Saint Paul St., Suite 4B
Baltimore, MD 21218
(410) 243-3269/FAX (410) 243-1963

Computerized Structural Steel Detailing

Experienced Staff including licensed Professional Engineers with many years of detailing experience. 30 years of service to steel fabricators and contractors.

R.A. GRESS & ASSOCIATES
176 Planebrook Road, Frazier, PA 19355
(610) 644-3250
FAX (610) 889-4836

HEWLETT-PACKARD Computers/Peripherals

A complete line of used and refurbished HP Equipment to fill all your computer needs. Laser printers, scanners, disk drives, plotters (Draftpro, Draftmaster & Designjet), PC's and 9000 series workstations are available for immediate delivery. Call our toll free number for additional information and pricing.

Ted Dasher & Associates
4117 2nd Avenue South
Birmingham, AL 35222
800-638-4833 fax (205) 591-1108

Images—3D

2D-3D Structural/Finite Element Analysis

Easy to learn and use Automesh Generation
Shear & Moment Diagrams Static, Modal, Dynamic
AISC Code Check Enforced Displacements
Large Problems to 3,000 Joints P-δ Analysis

Complete Static Package — Only \$795

Celestial Software, 2150 Shattuck Ave., Suite 1200,
Berkeley, CA 94704

Tel: 510-843-0977 / Fax: 510-848-9849

Fifty-node fully function evaluation package for only \$49.95

1989-1993 California S.E. Exam Solution Manual

The City of San Diego Building Department is offering complete problem statements and solutions to the problems of 1989-1993 California Structural Exam (except the bridge problems).

All solutions are based on the 1991 UBC incorporating the 1989 AISC (ASD) manual and the 1989 ACI code. Edited by Ben Yousefi, S.E., the 600-page manual is the result of a workshop offered to the public in the San Diego area, and is the property of the City of San Diego.

The cost of the manual is \$150. The 1987 and 1988 solutions based on the same codes are also available for an additional cost of \$25 each. To obtain an order form, call Elisa or Bernie at (619) 236-7075.

ROLLING

Beam-Angle-Tube-Pipe-Channel-Plate
Easy/Hardway Heavy Capacities
Up to **36"** W.F. Beam

209-466-9707

N.J. McCutchen, Inc.

123 W. Sonora St., Stockton, CA 95203

GT STRUDL

New PC Version with Interactive Graphics
and Links to CAD systems

Static, Non-Linear & Dynamic Analyses and
Integrated Steel Design

Curved steel Girder Bridge Module

For information contact: Alex Krimotat at SC Solutions
(415) 903-5050

Structural & Miscellaneous Steel Detailing CAD Programs

AutoCAD parametric LISP programs for preparing structural AND misc. steel shop drawings. Anchor bolts to roof opening frames and "everything between". Imperial and metric versions with USA, Canadian and European sections. 30 DAY MONEY BACK GUARANTEE. Discounts up to 30%. Buy only what you need. Used in the field for 6 years. Programs written by a detailer with 38 years experience. Extremely "flexible" programs. FREE telephone support. No maintenance fee. Reasonable yearly update fee. EXCELLENT PROGRAMS at a REASONABLE PRICE. Call for a FREE demo disk, list of programs, and prices.

SSDCP

110 Shady Oak Circle, Florence, MS 39073
Tel: 601/845-2146 (fax same)

Advertisers' Index

Advertiser	Page Number	Circle No.
AISC for AutoCAD	49	1
Bay Studies	12	5
Nicholas J. Bouras	CII	33
Cadvantage	29	45
Chaparral Steel	11	43
Comeq	31	68
Compu-Tec	24	85
Computer Detailing	28	
Computers & Structures Inc. (CSI)	CIV	31
Chicago Metal Rolled	28	66
Das Consulting	38	82
Design Data	7	32
EJE Industries	31	46
Grinder Software	42	83
Integrated Engineering Software	39	88
LRFD	19	2
LRFD on CD	8	1
MDX Software	39	47
Metrosoft	47	51
Mound Architectural	47	97
Nucor Yamato Steel	16-17	39
Omnitech	45	52
Optimate	42	53
PC Simon	15	6
RAM	45	81
Research Engineers	5	34
Risa Technologies	25 & 43	40
St. Louis Screw & Bolt	40	36
SteelCAD	43	84
Steel Deck Institute	44	77
Steel Joist Institute	21	54
Structural Engineering	38	78
Structural Software	41	42
TradeARBED	3	35
U.S. Crane	CII	86
Vulcraft	26-27	37
Wasser	Insert	50
Max Weiss	30	56
Whitefab	45	55

THERE IS ONLY ONE DFA SUPERCAGE™ FOR THREE DIFFERENT APPLICATIONS



*Patent Pending

1. Attach directly to boom
point



2. Suspend from crane
hook with 4 or 5 part
lifting bridle assembly



3. With forklift

Please circle # 86

For More Information:

UNITED STATES CRANE, INC.

P.O. Box 593290, Orlando, FL 32859 1-(800)-327-0300 1-(407)-859-6000 FAX 1-(407)-857-9146
PERCAGE PRODUCTS ARE CERTIFIED TO MEET OR EXCEED APPLICABLE OSHA, STATE AND FEDERAL REGULATIONS

STATE OF THE ART

Structural Engineering Software

INTEGRATED ANALYSIS AND DESIGN SOFTWARE FOR TALL BUILDINGS

Developed by Ashraf Habibullah & Edward L. Wilson



BH.PST
UNDEFORMED
SHAPE

MECH
2ND

IONS
HIDDEN LINES



For further information:

Computers & Structures, Inc.
1995 University Avenue
Berkeley, California 94704

TEL: 510/845-2177
FAX: 510/845-4096

ETABS®
Building Analysis & Design

SAP90®
General Analysis & Design

ETABS is a registered trademark of Computers & Structures, Inc.
SAP90 is a registered trademark of Computers & Structures, Inc.
© 1993 Computers & Structures, Inc.